







THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

REV.	ECN NO.	DATE	SIGN	DESCRIPTION
B	C190348	2019/03/06	Vicky	Change Note




ACB-XXPMMS-SC7001

04: 4Pin
:
06: 6Pin



- Note:
- * Important Dimension To Check.
 - * Waterproof Rate: IP67, Unmated.
 - * Housing: Thermoplastic, Black.
 - * Pin: Copper Alloy, Gold Plated.
 - * Gasket: Rubber, Gray.
 - * Nut: Thermoplastic, Black.
 - * Use with waterproof cap or dust cap
Maximum Panel Thickness: 2.3mm
 - * Use without waterproof cap or dust cap
Maximum Panel Thickness: 3.5mm
 - * Gasket and Nut are packed separately in PE bags. (Gasket/Nut不組裝，散裝出貨)



Pin Assignments Front View

UNIT: mm		TITLE		ITEM NO		DRAWN BY		DATE	
TOLERANCE		MIDDLE		ACB-XXPMMS-SC7001		Vicky		2019-03-06	
.X ±0.25		PANEL SCREW M CONN M PIN		DWG NO		Rita		2019-03-06	
.XX ±0.1		SCALE		CUSTOMER		Max		2019-03-06	
.XXX ±0.05		SIZE		ALTW					
ANGLES ±1°		REV.							
		A.2							
		QC: Inspection item							

Amphenol LTW
安費諾亮泰企業股份有限公司