



N=Number of contacts  
 Dim.B = (N-1)x5.08  
 Dim.A = Nx5.08

Poles	3x2P-3x7P	3x8P-3x12P	3x13P-3x18P	3x19P-3x24P
Dim.B	±0.15	±0.20	±0.25	±0.30
Dim.A	±0.20	±0.25	±0.30	±0.40

SIGN	DATE	DESCRIPTION	APPROVER
△	2/24'09	The dimension changed from 28.0 to 28.1	Kind
△	2/24'09	The dimension changed from 4.3 to 4.0	Kind
△	2/24'09	The dimension changed from 10.0 to 10.16	Kind
△	2/24'09	Add cULus	Kind
△	2/24'09	The screw type changed from M2.5 to M3.0	Kind

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

**Material**

Terminal body

- Item 1 (metal housing): Brass(CuZn): Ni plated
- Item 2 Terminal screw: Steel Zinc plating "-" slot type
- Item 3 Solder pin : Brass , Tin plated (Short)
- Item 4 Solder pin : Brass , Tin plated (Middle)
- Item 5 Solder pin : Brass , Tin plated (Long)
- Item 6 Insulator (housing): Thermoplastic (UL94V-0) Electrical cULus

● Voltage rating: 300VAC

● Current rating: 10A

● Wire range:

● Solid wire(AWG): 14-24

● Stranded wire(AWG): 14-24

● Torque(Lb-In): 3.5

△ ● Screw: M3.0

● Wire strip length: 6-7mm

● Withstanding Voltage: 1.6KV

● Operating temperature: -40°C to +115°C

● Soldering temperature: 250°C±10°C/5 Sec

△ ● Safety Approval: cULus

YB xx 21 x 0 xxxx G

- 06 3x2P CONTACTS
- 09 3x3P CONTACTS
- ... ..
- 72 3x24 CONTACTS
- 0 Black
- 5 Green
- 6 Blue
- 8 Grey
- 000:"@ "Logo (Standard)
- 000A:"ANYTEK"Logo
- Any special item by customer request, please contact sales department.

**ANYTEK**

**CUSTOMER COPY**

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		YB-5.08mm Series		DWG NO.		8YB0001	
PART NO.		YBxx21x0xxxxG		CUST NO.		Tolerance	
APPROVED	CHECKED	DESIGNED	DRAWN			UNIT: mm	X. ±0.50
		Aaron 2009.08.22	Aaron 2009.08.22			SCALE: NONE	X.X ±0.30
				SHEET: 01/01		REV.: E	X.XX ±0.10
							X° ±1°