

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

| P | LTR | DESCRIPTION | DATE | DWN | APVD |
|---|-----|-----------------|-----------|-----|------|
| | A | INITIAL RELEASE | 21APR2015 | DL | CW |
| | B | ECR-18-015555 | 30SEP2018 | GY | CW |
| | | | | | |
| | | | | | |

48.45
11.7
33.6

$\phi 5.8$
 $\phi 3.2$
24.5
PG/M

NOTES:

1. TECHNICAL CHARACTERISTICS:

BODY: PC

OPERATION TEMPERATURE: -40-+125°C

DEGREE OF PROTECTION: IP65 (MATED)

注释:

1. 技术参数:

主体材料: PC

工作温度: -40-+125°C

防护等级: IP65(配合)

26.8
26.8

| | | |
|----------------------|---------------------------|------|
| T1319031111-000 | H3A-TS-PG11 | PG11 |
| T1319031120-000 | H3A-TS-M20 | M20 |
| ASSEMBLY PART NUMBER | ASSEMBLY PART DESCRIPTION | PG/M |

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:

mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

| | |
|--------|----|
| 0 PLC | ±- |
| 1 PLC | ±- |
| 2 PLC | ±- |
| 3 PLC | ±- |
| 4 PLC | ±- |
| ANGLES | ±- |

MATERIAL

FINISH

-

-

DWN 21APR2015

DAVID LI

CHK 21APR2015

CHRIS WANG

APVD 21APR2015

XU XIANG

PRODUCT SPEC

108-137134

APPLICATION SPEC

114-137134

WEIGHT

-

CUSTOMER DRAWING

TE Connectivity

NAME

H3A-TS-PG/M

SIZE

A3

CAGE CODE

-

DRAWING NO

C-T13190311XX000

RESTRICTED TO

SCALE 3:2

SHEET 1 OF 1

REV B

1470-19 (3/13)