

# SMART GLOW ATO® BLADE FUSE RATED 12V



## Description

The Smart Glow ATO® fuse uses the industry standard Littelfuse ATO® fuse platform with an additional feature—It is designed to glow in the event of an open fuse for easier identification and replacement.

## Time-Current Characteristics

| % of Rating | Opening Time Min / Max (s) |
|-------------|----------------------------|
| 110         | 360,000 s / -              |
| 135         | 0.75 s / 600 s             |
| 200         | 0.15 s / 5 s               |
| 350         | 0.08 s / 0.50 s            |
| 600         | - / 0.10 s                 |

## Ratings

| Part Number    | Current Rating | Housing Color |
|----------------|----------------|---------------|
| 0ATO003_XGLO   | 3 A            |               |
| 0ATO005_XGLO   | 5 A            |               |
| 0ATO007.5_XGLO | 7.5 A          |               |
| 0ATO0010_XGLO  | 10 A           |               |
| 0ATO0015_XGLO  | 15 A           |               |
| 0ATO0020_XGLO  | 20 A           |               |
| 0ATO0025_XGLO  | 25 A           |               |
| 0ATO0030_XGLO  | 30 A           |               |

## Specifications

|                              |                       |
|------------------------------|-----------------------|
| Interrupting Rating:         | 1000A @ 14 VDC        |
| Voltage Rating:              | 12 VDC                |
| Operating Temperature Range: | -40°C to +105°C       |
| Terminals:                   | Tin plated Zinc alloy |

## Ordering Information

| Part Number   | Package Size |
|---------------|--------------|
| 0ATOxxx.MXGLO | 1000         |
| 0ATOxxx.HXGLO | 100          |
| 0ATOxxx.VXGLO | 5            |

## Dimensions

Dimensions in mm

