

SMART GLOW ATO® BLADE FUSE RATED 12V



Description

The Smart Glow ATO® fuse uses the industry standard Littelfuse ATO® fuse platform with an additional feature—it is designed to glow in the event of an open fuse for easier identification and replacement.

Time-Current Characteristics

| % of Rating | Opening Time Min / Max (s) |
|-------------|----------------------------|
| 110 | 360,000 s / - |
| 135 | 0.75 s / 600 s |
| 200 | 0.15 s / 5 s |
| 350 | 0.08 s / 0.50 s |
| 600 | - / 0.10 s |

Ratings

| Part Number | Current Rating | Housing Color |
|----------------|----------------|---------------|
| 0ATO003_XGLO | 3 A | |
| 0ATO005_XGLO | 5 A | |
| 0ATO007.5_XGLO | 7.5 A | |
| 0ATO0010_XGLO | 10 A | |
| 0ATO0015_XGLO | 15 A | |
| 0ATO0020_XGLO | 20 A | |
| 0ATO0025_XGLO | 25 A | |
| 0ATO0030_XGLO | 30 A | |

Specifications

| | |
|------------------------------|-----------------------|
| Interrupting Rating: | 1000A @ 14 VDC |
| Voltage Rating: | 12 VDC |
| Operating Temperature Range: | -40°C to +105°C |
| Terminals: | Tin plated Zinc alloy |

Ordering Information

| Part Number | Package Size |
|---------------|--------------|
| 0ATOxxx.MXGLO | 1000 |
| 0ATOxxx.HXGLO | 100 |
| 0ATOxxx.VXGLO | 5 |

Dimensions

Dimensions in mm

