

Main

Body type	Miniature
Device short name	XCMD
Range of product	OsiSense

Complementary

Line Rated Current	6 A
Associated body	ZCMD21
Body material	Zinc alloy
Contact operation	Snap action
Positive opening	With
Product weight	0.71 lb(US)
Switch actuation	Vertical
Torque value	8.5 ozf.in
Type of operator	Metal end plunger boot

Environment

ambient air temperature for operation	-13...158 °F
environmental characteristic	RoHS compliant
IP degree of protection	IP66 IP67 IP68
NEMA degree of protection	NEMA 1/2/4X/6/6P/12/13
product certifications	CE CSA UL listed
shock resistance	25 gn
standards	CENELEC EN 50047

Offer Sustainability

WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and	Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and
Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.	Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period	18 months
-----------------	-----------