









THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

REV.	ECN NO.	DATE	SIGN	DESCRIPTION
A	Initial Release	2012/10/22	Ruru	HB20-05PMFS-SS8001 To HB20-05PMFS-SW8001
B	LEN14A0098	2014/09/13	Feng_Li	Change Logo Direction
C	LE31650210	2016/05/03	Vicky	Update Note

F
E
D
C
B
A



- △ Note:
- * ⌀ Important Dimension.
 - * Waterproof Rate: IP68.
IP68: IM depth of water in 24 Hrs.
(防水等級: IP68)
IP68: 水深一米測試 24 小時
 - * Shell: Zinc Alloy ,Electrodeposition Coating,Black.
 - * Insulation: Nylon ,Black.
 - * Female Pin: Copper Alloy ,Gold Plated.
 - * Gasket: Silicone ,Gray.
 - * Screw: Stainless Steel.
 - * Recommended Panel Thickness 9mm(Max).

UNIT:mm		TITLE		ITEM NO		DRAWN BY		DATE	
		PANEL SCREW 5PIN M CONN F PIN		HB20-05PMFS-SW8001		Vicky		2016-05-03	
TOLERANCE		SCALE		DWG NO		CHECKED BY		DATE	
.X ±0.25		1:1		HB20-05PMFS-SW8001		Rita		2016-05-03	
.XX ±0.1		SIZE		CUSTOMER		APPROVED BY		DATE	
.XXX ±0.05		A4		ALTW		Lisa		2016-05-03	
ANGLES ±1°		REV.							
		C							
		WC-REV.							
		A.3							
		QC: Inspection item							

Amphenol LTW
安費諾亮泰企業股份有限公司