

PRODUCT NO.
73725

PRODUCT NUMBER CODE

73725-X X X X LF

HOUSING COLOR OPTION
0-WHITE
1-BLACK

SENSOR CONTACT OPTION
0-WITH SENSOR CONTACT
1-WITHOUT SENSOR CONTACT

SHIELD PLATING OPTION
1- 1.25μm MINIMUM NICKEL UNDERPLATE & 2.5μm MINIMUM BRIGHT TIN OVER ALL AREA. (HOLD DOWN STYLE "A")
2- 1.25μm MINIMUM NICKEL UNDERPLATED OVER ALL; 2.5 μm MINIMUM MATTE TIN PLATED ON HOLD DOWN AREA ONLY.(HOLD DOWN STYLE "B")
3- 1.25μm MINIMUM NICKEL UNDERPLATED OVER ALL; 2.5 μm MINIMUM MATTE TIN PLATED ON HOLD DOWN AREA ONLY.(HOLD DOWN STYLE "A")
4- 1.25μm MINIMUM NICKEL UNDERPLATED & 2.5μm MINIMUM BRIGHT TIN OVER ALL AREA. (HOLD DOWN STYLE "B")
5- 1.25μm MINIMUM NICKEL UNDERPLATED OVER ALL; 2.5μm MINIMUM MATTE TIN PLATED ON HOLD DOWN AREA ONLY (HOLD DOWN STYLE "C")
6- 1.25μm MINIMUM NICKEL ONLY. (HOLD DOWN STYLE "A")
7- 1.25μm MINIMUM NICKEL UNDERPLATED & 2.5 μm MINIMUM MATTE TIN PLATED OVER ALL. (HOLD DOWN STYLE "A")
8- 1.25μm MINIMUM NICKEL UNDERPLATED & 2.5 μm MINIMUM MATTE TIN PLATED ALL AREA. (HOLD DOWN STYLE "B")
9- 1.25μm MINIMUM NICKEL UNDERPLATED OVER ALL; 2.5 μm MINIMUM MATTE TIN PLATED ON HOLD DOWN AREA ONLY (HOLD DOWN STYLE "D")
S- 1.25μm MINIMUM NICKEL ONLY.(HOLD DOWN STYLE "A"). HIGH PERFORMANCE MATERIAL FOR 12,000 DURABILITY CYCLES
A- 1.25μm MINIMUM NICKEL PLATED OVER ALL 2.5 μm MINIMUM MATTE TIN PLATED ON HOLD DOWN AREA ONLY (HOLD DOWN STYLE "F")
B- 1.25μm MINIMUM NICKEL PLATED OVER ALL 2.5 μm MINIMUM MATTE TIN PLATED ON HOLD DOWN AREA ONLY (HOLD DOWN STYLE "F")


TERMINAL OPTION
50u" NI UNDERPLATE; 30u" GXT CONTACT AREA,100u" TIN TAIL AREA;
0- DIM "A": 2.29 (TERMINAL TAIL LENGTH);
1- DIM "A": 3.71 (TERMINAL TAIL LENGTH);

LEAD FREE OPTION
SEE NOTE 9


PACKAGING OPTION
B - TUBE
R - TAPE&REEL



SENSOR CONTACT




WITH SENSOR CONTACT



FRONT OF CONNECTOR

PC BOARD MOUNTING DIMENSIONS FOR 5 PIN




FOR 73725-X0X0B
HOLD DOWN STYLE "A"

NOTES:


- MATERIAL:
CONTACTS: COPPER ALLOY
SHIELD: COPPER ALLOY
HOUSING: UL 94V-0 THERMOPLASTIC, COLOR: SEE PRODUCT CODE
- PLATING:
CONTACTS: GOLD FLASH OVER PALLADIUM NICKEL (0.76μm MINIMUM) IN CONTACT AREA; 2.5 μm TIN MINIMUM IN SOLDER TAIL AREA.
SHIELD: 1.27 μm MINIMUM NICKEL UNDERPLATE OVER ALL SURFACES.
(THE PLATING MEASURE POINT ON THE SHIELD HOLD DOWN AREA ONLY).
- DATUMS & BASIC DIMENSIONS TO BE DETERMINED BY CUSTOMER
- RECOMMENDED PCB BOARD THICKNESS IS 1.00 ~ 1.60mm EXCEPT 73725-1191BLF; 73725-1191BLF CAN BE USED FOR THE PCB BOARD THICKNESS 2.30 ~ 2.65mm.
- MAXIMUM PANEL THICKNESS TO BE 2.67mm IF MOUNTED BEHIND PANEL
- METAL SHELL SLIVER 0.20 MAX.
- NI PLATING DOES NOT COMPLY WITH THE USB STANDARDS (TO BE CONTINUED)

mat'l. code				surface123/tolerance			projection		product family		
				ISO 1302	ISO 406	ISO 1101			HPL 511 USB 2.0		
ltr	ecn no	dr	date	tolerances unless otherwise specified			title				
AJ	ELX-N-27708	LZ	2017/08/15	angles	linear		mm		USB UP-RIGHT RECEPT		
AD	ELX-N-012006	A.ZH	06/25/2012	0±2°			scale 1:1				
AE	ELX-N-13463	A.ZH	11/14/2012	dr	PAMP	5/20/97			dwg no sheet 1 of 4 size		
AF	ELX-N-14592	J.HAN	06/10/2013	engr	R Y LIU	5/20/97			73725 A3		
AG	ELX-N-21594	LQ	08/04/2015	chr	R Y LIU	5/20/97					
AH	ELX-N-21919	LQ	08/04/2015	appd	JENN TSAO	5/20/97			type Product Customer Drawing		
sheet	revision										
index	sheet										

13. DATUM OF CUSTOMER'S PCB LAYOUT.




WITHOUT SENSOR CONTACT




FOR 73725-X1X0B
HOLD DOWN STYLE "A"


mat'l. code				surface ¹²³ /tolerance		projection		product family	
				ISO 1302 ✓ ISO 406 ISO 1101				HPL 511 USB 2.0	
ltr	ecn no	dr	date	tolerances unless otherwise specified				title	
AJ				angles linear .0±.30 0±2' .00±.20 .000±.10				USB UP-RIGHT RECEPT	
						scale 1:1			
				dr	PAMP	5/20/97	dwg no		sheet2 of 4
				engr	R Y LIU	5/20/97			size
				chr	R Y LIU	5/20/97	73725		A3
				appd	JENN TSAO	5/20/97	type		Product Customer Drawing
sheet index	revision								
	sheet								




WITHOUT SENSOR CONTACT
FOR 73725-X1X0B
HOLD DOWN STYLE "B"



WITHOUT SENSOR CONTACT
FOR 73725-XXA0XLF ONLY
73725-XXB0XLF
HOLD DOWN STYLE "F"




WITH SENSOR CONTACT
FOR 73725-X0X0B
HOLD DOWN STYLE "B"





WITHOUT SENSOR CONTACT
FOR 73725-X191XLF
HOLD DOWN STYLE "D"

mat'l. code				surface ¹²³ ISO 1302		toleranceISO 406 ISO 1101		projection 		product familyHPL 511 USB 2.0			
ltr	ecn no	dr	date	tolerances unless otherwise specified						title			
AJ				angles		.0±.30		 mm		USB UP-RIGHT RECEPT			
				linear		.00±.20							
				0°±2°		.000±.10		scale 1:1					
				dr	PAMP	5/20/97		Amphenol FCI		dwg no		sheet3 of 4	size
				engr	R Y LIU	5/20/97				73725		A3	
				chr	R Y LIU	5/20/97							
				appd	JENN TSAO	5/20/97							
sheet index		revision sheet								type Product Customer Drawing			

PRODUCT NO.
73725



PC BOARD MOUNTING DIMENSIONS FOR 4 PIN



WITHOUT SENSOR CONTACT
FOR 73725-X150B
HOLD DOWN STYLE "C"

mat'l. code				surface ¹²³ / tolerance		projection		product family				
ISO 1302 ✓				ISO 406 ISO 1101				HPL 511 USB 2.0				
ltr	ecn no	dr	date	tolerances unless otherwise specified				title				
AJ				angles	linear			USB UP-RIGHT RECEPT				
						scale 1:1						
				0°±2°								
				dr	PAMP	5/20/97	Amphenol FCI		dwg no		sheet 4 of 4	size
				engr	R Y LIU	5/20/97			73725			A3
				chr	R Y LIU	5/20/97						
				appd	JENN TSAO	5/20/97			type Product Customer Drawing			
sheet index		revision sheet										