

# Harmony™ XB7 monolithic 22 mm push buttons

Catalog  
**2012**





# Harmony™ XB7 monolithic 22 mm push buttons

---

|                          |    |
|--------------------------|----|
| Overview . . . . .       | 5  |
| Introduction . . . . .   | 8  |
| Specifications . . . . . | 9  |
| References . . . . .     | 11 |
| Dimensions . . . . .     | 17 |
| Mounting . . . . .       | 18 |



# Harmony™ XB7: Compact, robust, monolithic 22 mm push buttons for your machines

For your control systems that require high-performance, compact, and easy-to-install components...Harmony XB7 push buttons are your ideal solution. The new Emergency Stop push button design allows immediate identification of safety functions and status of contacts.

## > Simple installation, simple integration...

Easy to install and to integrate into your Control Systems

## > Designed for quality and conformity...


Conforms to industry standards and Machinery Directive

## > High performance for industrial applications...

Robust, durable controls for industry and buildings

Make the most of your energy<sup>SM</sup>






## Simple installation...

The monolithic design of the Harmony™ XB7 makes it **easy to mount** on machines or control panels with only one ring nut.

The 4 top-down terminals enable **easy wiring** with finger protection (IP 20).



**IEC 60529**  
compliant



## Simple integration...

New ergonomic design in 6 colors, plus illuminated functions with **integrated LED**.

### Complete product range



Push buttons ○ ● ● ● ● ●



Pilot lights ● ● ● ● ● ○

Long life: a duration of more than **70,000 hours** on pilot lights and **1 million** operations for push buttons.



Illuminated push buttons  
● ● ● ● ● ○



Handle selectors  
●



Key selectors  
●





Emergency stop push buttons  
●

**1 reference**  **1 function**

### Electrical reliability

Contact functions are designed for **load switching** (I/O interface) and resistance to vibrations.





## Designed for quality and conformity...

Harmony™ XB7 “Emergency stop” push buttons comply with EN/IEC and UL standards, EN 13850, EN/IEC 60947-5-5 and are designed for machines and industrial control panels. The emergency stop function consists of:

Red trigger action



Standardized yellow legend

Green mark on body allows contact state visualization



Off



On

**Green**  
mark for contact state



Worldwide availability



Conforming to  
**EN/IEC 60947-5-5**

International  
certifications:  
**CE, UL, CSA, CCC,  
GOST**



## High performance for industrial applications...

The Harmony XB7 push button is perfect for industry applications like packaging and other machine processes, and building applications, including: HVAC, electrical distribution, and lighting.

Assembly lines



Packaging machines



HVAC



Buildings




Degree of protection  
**IP 65**

# Harmony™ XB7 monolithic 22 mm push buttons

Push buttons, switches and pilot lights


## Complete products: Contact functions

### Spring return push buttons with/without marking




Flush

XB7 NA●●●●: see page 11



Projecting

XB7 NL●●●●: see page 11




### Latching push buttons without marking

Flush

XB7 NH●●: see page 11

### Selector switches and key switches



Standard handle, black


XB7 ND●●: see page 14



Key operated

XB7 NG●●: see page 14

### Emergency Stop push buttons



Turn to release/Push-pull/Key release

XB7 NS●●●●/XB7 NT●●●: see page 14

## Complete products: Signalling functions

### Pilot lights



With integral LED

XB7 EV0●●P: see page 13



### Illuminated push buttons, with projecting push

With integral LED, spring return or latching

XB7 NW●●●●, XB7 NJ●●●●1: see page 13

## Legend holders, legends, and accessories

See pages 15 and 16

# Harmony™ XB7 monolithic

## 22 mm push buttons

Push buttons, switches and pilot lights

| Environment                                         |                                                |     |                                                                                                                                                                                                                                                                                                                                                                                                  |
|-----------------------------------------------------|------------------------------------------------|-----|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Protective treatment                                | Standard version                               |     | "TH"                                                                                                                                                                                                                                                                                                                                                                                             |
| Ambient air temperature around the device           | For storage                                    | °C  | -40 to +70                                                                                                                                                                                                                                                                                                                                                                                       |
|                                                     | For operation                                  | °C  | -25 to +70 for integral LED version                                                                                                                                                                                                                                                                                                                                                              |
| Electric shock protection                           | Conforming to IEC 61140                        |     | Class II                                                                                                                                                                                                                                                                                                                                                                                         |
| Degree of protection                                | Conforming to IEC 60529                        |     | Front face:<br><input type="checkbox"/> IP 65 for push buttons, illuminated push buttons, pilot lights, selector switches and Emergency Stop push buttons<br><br>Rear face:<br><input type="checkbox"/> IP 20 (protection against direct contact)                                                                                                                                                |
|                                                     | Conforming to UL 50E                           |     | <input type="checkbox"/> Suitable for enclosure type 3: push buttons, illuminated push buttons, selector switches, Emergency Stop push buttons<br><input type="checkbox"/> Suitable for enclosure type 4: pilot lights with integral LED<br><input type="checkbox"/> Suitable for enclosure type 12: Emergency Stop push buttons, pilot lights with integral LED                                 |
| Conformity to standards                             | Generic standards<br>UL, CSA, GOST, CCC and CE |     | <input type="checkbox"/> EN/IEC 60947-1, EN/IEC 60947-5-1 for push buttons, pilot lights, illuminated push buttons and selector switches<br><input type="checkbox"/> UL, EN/IEC 60947-1, EN/IEC 60947-5-1, EN/IEC 60947-5-5, EN/IEC 60204-1 and EN/ISO 13850 for Emergency Stop trigger action push buttons<br><input type="checkbox"/> UL 508, CSA C22 n° 14, CCC, GB 14048.5 for all XB7 range |
| Terminal referencing                                | Conforming to EN 50005 and EN 50013            |     | Conforms                                                                                                                                                                                                                                                                                                                                                                                         |
| General specifications                              |                                                |     |                                                                                                                                                                                                                                                                                                                                                                                                  |
| Mechanical durability<br>(in operating cycles)      |                                                |     | <input type="checkbox"/> Push buttons: 1,000,000<br><input type="checkbox"/> Illuminated push buttons, spring return and latch type: 300,000<br><input type="checkbox"/> Selector switches and key switches: 300,000<br><input type="checkbox"/> Emergency Stop: 100,000                                                                                                                         |
| Vibration resistance                                | Conforming to IEC 60068-2-6                    |     | 5 gn (frequency 2 to 500 Hz)                                                                                                                                                                                                                                                                                                                                                                     |
| Mechanical shock resistance                         | Conforming to IEC 60068-2-27                   |     | Half sine wave acceleration 11 ms: 50 gn<br>Half sine wave acceleration 18 ms: 30 gn<br>Half sine wave acceleration 11 ms:<br>- 15 gn for Emergency Stop push buttons                                                                                                                                                                                                                            |
| Mounting<br>Conforming to<br>EN/IEC 60947-5-1       | Finished mounting hole                         | mm  | 22.5, recommended (22.3 + 0.4/0)                                                                                                                                                                                                                                                                                                                                                                 |
|                                                     | Mounting center                                | mm  | <input type="checkbox"/> 30 x 40 for all products (except Emergency Stop push buttons)<br><input type="checkbox"/> 40 x 40 for Emergency Stop push buttons                                                                                                                                                                                                                                       |
|                                                     | Support panel thickness                        | mm  | <input type="checkbox"/> Metal: 1 to 6<br><input type="checkbox"/> Plastic: 2 to 6                                                                                                                                                                                                                                                                                                               |
|                                                     | Mounting nut: head tightening torque           | N•m | <input type="checkbox"/> 2.2 (+/-0.2)                                                                                                                                                                                                                                                                                                                                                            |
| Cabling capacity<br>Conforming to<br>EN/IEC 60947-1 | Screw clamp terminal connection                | mm² | For all types of push buttons and pilot lights:<br><input type="checkbox"/> min: 1 x 0.34 mm² without cable end<br><input type="checkbox"/> max: 2 x 1.5 mm² with cable end or 2 x 2.5 mm² without cable end                                                                                                                                                                                     |
|                                                     | Forked "U" type tag connection                 |     | 2 max., fitted head to tail (for all types of push buttons and pilot lights)<br>Recommended fork width: 6.5 mm (7 mm max.) for M3 screw                                                                                                                                                                                                                                                          |
|                                                     | Faston clip connection                         | mm  | Type 6.35 x 0.8 mm (for pilot lights only)                                                                                                                                                                                                                                                                                                                                                       |
| Tightening torque of mounting screws                |                                                | N•m | <input type="checkbox"/> 0.8 (nominal recommended)<br><input type="checkbox"/> 1.2 (max.)                                                                                                                                                                                                                                                                                                        |
|                                                     |                                                |     | Screw heads compatible with Pozidriv, Phillips or JIS screwdrivers (size 1) and flat tipped screwdrivers (4 and 5.5 mm)                                                                                                                                                                                                                                                                          |

# Harmony™ XB7 monolithic 22 mm push buttons

Push buttons, switches and pilot lights

## Contact function specifications

|                                                                       |                                                     |    |                                                                                                                                   |
|-----------------------------------------------------------------------|-----------------------------------------------------|----|-----------------------------------------------------------------------------------------------------------------------------------|
| Type of contact                                                       | N/C, N/O or N/C+N/O                                 |    | <input type="checkbox"/> Slow break<br><input type="checkbox"/> Snap action for Emergency Stop push buttons                       |
| Positive operation                                                    | Conforming to EN/IEC 60947-5-1 Appendix K           |    | All functions incorporating a N/C contact are positive opening operation                                                          |
| Short-circuit protection                                              | Conforming to EN/IEC 60947-5-1                      | A  | 4 (using gG cartridge fuse conforming to IEC 269-1)                                                                               |
| Rated insulation voltage                                              | Conforming to EN/IEC 60947-1                        | V  | Ui = 250 (degree of pollution 3)                                                                                                  |
| Rated impulse withstand voltage                                       | Conforming to EN/IEC 60947-1                        | kV | Uimp = 6                                                                                                                          |
| Rated operational specifications<br>conforming to<br>EN/IEC 60947-5-1 | a.c. supply: utilization category                   |    |                                                                                                                                   |
|                                                                       | AC14, D300                                          |    | Ue = 240 V and Ie = 0.3 A or Ue = 120 V and Ie = 0.6 A                                                                            |
|                                                                       | AC15, C300                                          |    | Ue = 120 V and Ie = 1.5 A or Ue = 240 V and Ie = 0.75 A (Emergency Stop only)                                                     |
|                                                                       | DC13, R300                                          |    | Ue = 250 V and Ie = 0.1 A or Ue = 125 V and Ie = 0.22 A                                                                           |
| Electrical reliability<br>at 17 V and 5 mA                            | Failure rate in accordance with<br>EN/IEC 60947-5-4 |    | <input type="checkbox"/> $\lambda \leq 10^{-6}$<br><input type="checkbox"/> $\lambda \leq 5 \times 10^{-7}$ (Emergency Stop only) |

## Light function specifications

| Type of signaling units                |                                                           |             |     | Illuminated push buttons                                             | Pilot lights |
|----------------------------------------|-----------------------------------------------------------|-------------|-----|----------------------------------------------------------------------|--------------|
| Integral LED                           |                                                           |             |     |                                                                      |              |
| Current consumption                    | For all colors                                            | — / ~ 24 V  | mA  | 18 (27 max.)                                                         | 20 (27 max.) |
|                                        |                                                           | ~ 120 V     | mA  | 12 (17 max.)                                                         | 18 (21 max.) |
|                                        |                                                           | ~ 230 V     | mA  | 22 (27 max.)                                                         | 16 (20 max.) |
| Voltage limits                         | At nominal voltage                                        | — 24 V      | V   | 19.2 to 30                                                           |              |
|                                        |                                                           | ~ 24 V      | V   | 21.6 to 26.4                                                         |              |
|                                        |                                                           | ~ 120 V     | V   | 100 to 132                                                           |              |
|                                        |                                                           | ~ 230–240 V | V   | 195 to 264                                                           |              |
| Service life                           | At nominal voltage and at an ambient temperature of 25 °C |             | Hr  | 70,000                                                               |              |
| Overvoltage withstand                  | Level of protection                                       | ~ 120 V     | VA  | 100                                                                  |              |
|                                        |                                                           | ~ 230 V     | VA  | 200                                                                  |              |
| Resistance to electrostatic discharges | Conforming to IEC 61000-4-2                               |             | kV  | 6: on contact, on metal parts<br>8: in free air, in insulating parts |              |
| Resistance to electromagnetic fields   | Conforming to IEC 61000-4-3                               |             | V/m | 10                                                                   |              |
| Resistance to fast transients          | Conforming to IEC 61000-4-4                               |             | KV  | 2                                                                    |              |
| Surge withstand                        | Conforming to IEC 61000-4-5                               |             | KV  | 1                                                                    |              |
| Immunity to conducted disturbances     | Conforming to IEC 61000-4-6                               |             | V   | 10                                                                   |              |
| Brightness                             | At nominal voltage and for all colors                     |             | Lux | > 200                                                                |              |

# Harmony™ XB7 monolithic

## 22 mm push buttons

Push buttons, switches and pilot lights



XB7NA31

| Push buttons                                                                        |              |                                                                                   |                                                                                   |         |       |               |                 |                |        |
|-------------------------------------------------------------------------------------|--------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|---------|-------|---------------|-----------------|----------------|--------|
| Shape of head                                                                       | Type of push | Type of contact                                                                   |                                                                                   | Marking |       | Color of push | Sold in lots of | Unit reference | Weight |
|                                                                                     |              | N/O                                                                               | N/C                                                                               |         |       |               |                 |                |        |
|                                                                                     |              |  |  | Text    | Color |               |                 |                |        |
| Spring return push button without marking                                           |              |                                                                                   |                                                                                   |         |       |               |                 |                |        |
|    | Flush        | 1                                                                                 | –                                                                                 | –       | –     | White         | 10              | XB7NA11        | 0.021  |
|                                                                                     |              | 1                                                                                 | –                                                                                 | –       | –     | Black         | 10              | XB7NA21        | 0.021  |
|                                                                                     |              | 1                                                                                 | –                                                                                 | –       | –     | Green         | 10              | XB7NA31        | 0.021  |
|                                                                                     |              | 1                                                                                 | –                                                                                 | –       | –     | Yellow        | 10              | XB7NA81        | 0.021  |
|                                                                                     |              | 1                                                                                 | 1                                                                                 | –       | –     | White         | 10              | XB7NA15        | 0.021  |
|                                                                                     |              | 1                                                                                 | 1                                                                                 | –       | –     | Black         | 10              | XB7NA25        | 0.021  |
|                                                                                     |              | 1                                                                                 | 1                                                                                 | –       | –     | Green         | 10              | XB7NA35        | 0.021  |
|                                                                                     |              | 1                                                                                 | 1                                                                                 | –       | –     | Red           | 10              | XB7NA45        | 0.021  |
|                                                                                     |              | 1                                                                                 | 1                                                                                 | –       | –     | Blue          | 10              | XB7NA65        | 0.021  |
|                                                                                     |              | 1                                                                                 | 1                                                                                 | –       | –     | Yellow        | 10              | XB7NA85        | 0.021  |
|                                                                                     |              | –                                                                                 | 1                                                                                 | –       | –     | Red           | 10              | XB7NA42        | 0.021  |
|                                                                                     |              | 2                                                                                 | –                                                                                 | –       | –     | Black         | 10              | XB7NA23        | 0.021  |
|                                                                                     |              | 2                                                                                 | –                                                                                 | –       | –     | Green         | 10              | XB7NA33        | 0.021  |
|                                                                                     |              | –                                                                                 | 2                                                                                 | –       | –     | Red           | 10              | XB7NA44        | 0.021  |
|  | Projecting   | –                                                                                 | 1                                                                                 | –       | –     | Red           | 10              | XB7NL42        | 0.021  |
|                                                                                     |              | 1                                                                                 | 1                                                                                 | –       | –     | Red           | 10              | XB7NL45        | 0.021  |
|                                                                                     |              | –                                                                                 | 2                                                                                 | –       | –     | Red           | 10              | XB7NL44        | 0.021  |
| Latch type push button without marking                                              |              |                                                                                   |                                                                                   |         |       |               |                 |                |        |
|  | Flush        | 1                                                                                 | –                                                                                 | –       | –     | Black         | 10              | XB7NH21        | 0.021  |
|                                                                                     |              | 1                                                                                 | –                                                                                 | –       | –     | Green         | 10              | XB7NH31        | 0.021  |
|                                                                                     |              | 1                                                                                 | 1                                                                                 | –       | –     | Black         | 10              | XB7NH25        | 0.021  |
|                                                                                     |              | 1                                                                                 | 1                                                                                 | –       | –     | Green         | 10              | XB7NH35        | 0.021  |
|                                                                                     |              | 1                                                                                 | –                                                                                 | –       | –     | Yellow        | 10              | XB7NH81        | 0.021  |



XB7NH2

# Harmony™ XB7 monolithic 22 mm push buttons

Push buttons, switches and pilot lights



XB7NA3133



XB7NA4234

| Push buttons (continued)                                                            |              |                                                                                   |                                                                                   |         |       |               |                 |                |           |
|-------------------------------------------------------------------------------------|--------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|---------|-------|---------------|-----------------|----------------|-----------|
| Shape of head                                                                       | Type of push | Type of contact                                                                   |                                                                                   | Marking |       | Color of push | Sold in lots of | Unit reference | Weight kg |
|                                                                                     |              | N/O                                                                               | N/C                                                                               |         |       |               |                 |                |           |
|                                                                                     |              |  |  | Text    | Color |               |                 |                |           |
| Spring return push button with marking                                              |              |                                                                                   |                                                                                   |         |       |               |                 |                |           |
|    | Flush        | 1                                                                                 | –                                                                                 | I       | White | Green         | 10              | XB7NA3131      | 0.021     |
|                                                                                     |              | 1                                                                                 | –                                                                                 | II      | White | Green         | 10              | XB7NA3136      | 0.021     |
|                                                                                     |              | 1                                                                                 | –                                                                                 | START   | White | Green         | 10              | XB7NA3133      | 0.021     |
|                                                                                     |              | 1                                                                                 | –                                                                                 | ↓       | Black | White         | 10              | XB7NA11343     | 0.021     |
|                                                                                     |              | 1                                                                                 | –                                                                                 | ↑       | Black | White         | 10              | XB7NA11341     | 0.021     |
|                                                                                     |              | 1                                                                                 | –                                                                                 | ↓       | White | Black         | 10              | XB7NA21343     | 0.021     |
|                                                                                     |              | 1                                                                                 | –                                                                                 | ↑       | White | Black         | 10              | XB7NA21341     | 0.021     |
|                                                                                     |              | –                                                                                 | 1                                                                                 | O       | White | Red           | 10              | XB7NA4232      | 0.021     |
|                                                                                     |              | –                                                                                 | 1                                                                                 | STOP    | White | Red           | 10              | XB7NA4234      | 0.021     |
|                                                                                     |              | 2                                                                                 | –                                                                                 | I       | White | Green         | 10              | XB7NA3331      | 0.021     |
|                                                                                     |              | 2                                                                                 | –                                                                                 | II      | White | Green         | 10              | XB7NA3336      | 0.021     |
|                                                                                     |              | 2                                                                                 | –                                                                                 | START   | White | Green         | 10              | XB7NA3333      | 0.021     |
|                                                                                     |              | 1                                                                                 | 1                                                                                 | O       | White | Red           | 10              | XB7NA4532      | 0.021     |
|                                                                                     |              | 1                                                                                 | 1                                                                                 | STOP    | White | Red           | 10              | XB7NA4534      | 0.021     |
|                                                                                     |              | 1                                                                                 | 1                                                                                 | ↓       | Black | White         | 10              | XB7NA15343     | 0.021     |
|                                                                                     |              | 1                                                                                 | 1                                                                                 | ↑       | Black | White         | 10              | XB7NA15341     | 0.021     |
|                                                                                     |              | 1                                                                                 | 1                                                                                 | ↓       | White | Black         | 10              | XB7NA25343     | 0.021     |
|                                                                                     |              | 1                                                                                 | 1                                                                                 | ↑       | White | Black         | 10              | XB7NA25341     | 0.021     |
|  | Projecting   | –                                                                                 | 1                                                                                 | O       | White | Red           | 10              | XB7NL4232      | 0.021     |
|                                                                                     |              | –                                                                                 | 1                                                                                 | STOP    | White | Red           | 10              | XB7NL4234      | 0.021     |
|                                                                                     |              | 1                                                                                 | 1                                                                                 | O       | White | Red           | 10              | XB7NL4532      | 0.021     |
|                                                                                     |              | 1                                                                                 | 1                                                                                 | STOP    | White | Red           | 10              | XB7NL4534      | 0.021     |



XB7NL4232

# Harmony™ XB7 monolithic

## 22 mm push buttons

Push buttons, switches and pilot lights



| Illuminated push buttons, projecting push                                         |                                                 |               |                 |                                      |           |           |           |
|-----------------------------------------------------------------------------------|-------------------------------------------------|---------------|-----------------|--------------------------------------|-----------|-----------|-----------|
| with integral LED                                                                 |                                                 |               |                 |                                      |           |           |           |
| Shape of head                                                                     | Type of push and contacts                       | Color of lens | Sold in lots of | Unit reference by supply voltage (1) |           |           | Weight kg |
|                                                                                   |                                                 |               |                 | ~ / ~ 24 V                           | ~ 120 V   | ~ 230 V   |           |
|  | Spring return push with N/O or N/C contacts (1) | Green         | 10              | XB7NW33B1                            | XB7NW33G1 | XB7NW33M1 | 0.023     |
|                                                                                   |                                                 | Red           | 10              | XB7NW34B1                            | XB7NW34G1 | XB7NW34M1 | 0.023     |
|                                                                                   |                                                 |               | 10              | XB7NW34B2                            | XB7NW34G2 | XB7NW34M2 | 0.023     |
|                                                                                   |                                                 | Orange        | 10              | XB7NW35B1                            | XB7NW35G1 | XB7NW35M1 | 0.023     |
|                                                                                   |                                                 | Blue          | 10              | XB7NW36B1                            | XB7NW36G1 | XB7NW36M1 | 0.023     |
|                                                                                   |                                                 | Clear         | 10              | XB7NW37B1                            | XB7NW37G1 | XB7NW37M1 | 0.023     |
|                                                                                   |                                                 | Yellow        | 10              | XB7NW38B1                            | XB7NW38G1 | XB7NW38M1 | 0.023     |
|                                                                                   | Latch push                                      | Green         | 10              | XB7NJ03B1                            | XB7NJ03G1 | XB7NJ03M1 | 0.023     |
|                                                                                   |                                                 | Red           | 10              | XB7NJ04B1                            | XB7NJ04G1 | XB7NJ04M1 | 0.023     |
|                                                                                   |                                                 |               | 10              | XB7NJ04B2                            | XB7NJ04G2 | XB7NJ04M2 | 0.023     |
|                                                                                   |                                                 | Orange        | 10              | XB7NJ05B1                            | XB7NJ05G1 | XB7NJ05M1 | 0.023     |
|                                                                                   |                                                 | Blue          | 10              | XB7NJ06B1                            | XB7NJ06G1 | XB7NJ06M1 | 0.023     |
|                                                                                   |                                                 | Clear         | 10              | XB7NJ07B1                            | XB7NJ07G1 | XB7NJ07M1 | 0.023     |
|                                                                                   |                                                 | Yellow        | 10              | XB7NJ08B1                            | XB7NJ08G1 | XB7NJ08M1 | 0.023     |



| Pilot lights                                                                        |                                 |               |                 |                                      |           |           |           |
|-------------------------------------------------------------------------------------|---------------------------------|---------------|-----------------|--------------------------------------|-----------|-----------|-----------|
| with integral LED                                                                   |                                 |               |                 |                                      |           |           |           |
| Shape of head                                                                       | Type of light source (included) | Color of lens | Sold in lots of | Unit reference by supply voltage (2) |           |           | Weight kg |
|                                                                                     |                                 |               |                 | ~ / ~ 24 V                           | ~ 120 V   | ~ 230 V   |           |
|  | Integral LED                    | Green         | 10              | XB7EV03BP                            | XB7EV03GP | XB7EV03MP | 0.020     |
|                                                                                     |                                 | Red           | 10              | XB7EV04BP                            | XB7EV04GP | XB7EV04MP | 0.020     |
|                                                                                     |                                 | Yellow        | 10              | XB7EV05BP                            | XB7EV05GP | XB7EV05MP | 0.020     |
|                                                                                     |                                 | Blue          | 10              | XB7EV06BP                            | XB7EV06GP | XB7EV06MP | 0.020     |
|                                                                                     |                                 | Clear         | 10              | XB7EV07BP                            | XB7EV07GP | XB7EV07MP | 0.020     |
|                                                                                     |                                 | Orange        | 10              | XB7EV08BP                            | XB7EV08GP | XB7EV08MP | 0.020     |

(1) All product references ending with "1" correspond to products with N/O contacts (Example: XB7NW34B1). All product references ending with "2" correspond to products with N/C contacts (Example: XB7NW34B2).

(2) For Faston® connection version (1 x 6.35 mm and 2 x 2.8 mm), add the number "3" to the end of the reference. Example: XB7EV07BP becomes XB7EV07BP3.

# Harmony™ XB7 monolithic 22 mm push buttons

Push buttons, switches and pilot lights

## Selector switches and key switches

| Shape of head                                                                     | Type of operator       | Type of contact                                                                   |                                                                                   | Number and type of positions (1)     |                                                                                     | Sold in lots of | Unit reference | Weight |
|-----------------------------------------------------------------------------------|------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|--------------------------------------|-------------------------------------------------------------------------------------|-----------------|----------------|--------|
|                                                                                   |                        | NO                                                                                | NC                                                                                |                                      |                                                                                     |                 |                |        |
|                                                                                   |                        |  |  |                                      |                                                                                     |                 |                |        |
|  | Standard handle, black | 1                                                                                 | —                                                                                 | 2, stay put                          |  | 10              | XB7ND21        | 0.026  |
|                                                                                   |                        | 1                                                                                 | 1                                                                                 | 2, stay put                          |  | 10              | XB7ND25        | 0.026  |
|                                                                                   |                        | 2                                                                                 | —                                                                                 | 3, stay put                          |  | 10              | XB7ND33        | 0.026  |
|  | Key (key n° 455)       | 1                                                                                 | —                                                                                 | 2, key withdrawal in LH position     |  | 10              | XB7NG21        | 0.050  |
|                                                                                   |                        | 2                                                                                 | —                                                                                 | 3, key withdrawal in center position |  | 10              | XB7NG33        | 0.050  |

XB7ND2●

XB7NG33


## Ø 40 mm Emergency stop trigger action and mechanically latching push buttons

| Shape of head                                                                       | Type of push         | Standards                                                                             | Type of contact |    | Color of push | Sold in lots of | Unit reference | Weight<br>kg |
|-------------------------------------------------------------------------------------|----------------------|---------------------------------------------------------------------------------------|-----------------|----|---------------|-----------------|----------------|--------------|
|                                                                                     |                      |                                                                                       | NO              | NC |               |                 |                |              |
|    | Turn to release      | EN/IEC 60204-1, EN/ISO 13850, EN/IEC 60947-5-5, Machinery directive 2006/42/EC and UL | —               | 1  | Red           | 10              | XB7NS8442      | 0.045        |
|                                                                                     |                      |                                                                                       | 1               | 1  | Red           | 10              | XB7NS8445      | 0.045        |
|                                                                                     |                      |                                                                                       | —               | 2  | Red           | 10              | XB7NS8444      | 0.045        |
|  | Push-pull            |                                                                                       | —               | 1  | Red           | 10              | XB7NT842       | 0.040        |
|                                                                                     |                      |                                                                                       | 1               | 1  | Red           | 10              | XB7NT845       | 0.040        |
|                                                                                     |                      |                                                                                       | —               | 2  | Red           | 10              | XB7NT844       | 0.040        |
|  | Key release (n° 455) |                                                                                       | —               | 2  | Red           | 10              | XB7NS9444      | 0.072        |
|                                                                                     |                      |                                                                                       | —               | 1  | Red           | 10              | XB7NS9445      | 0.072        |

XB7 NS84●

(1) The symbol "⌘" indicates key withdrawal position.

# Harmony™ XB7 monolithic 22 mm push buttons Push buttons, switches and pilot lights



ZBY 2101

## Standard (30 x 40 mm) legend holders for 8 x 27 mm legends

| Text           | Sold in lots of | Unit reference | Weight kg |
|----------------|-----------------|----------------|-----------|
| Without legend | 10              | ZBZ32          | 0.001     |

## Legend holder, 30 x 40 mm with legend (black or red background)

### with blank legend

| Text    | Sold in lots of | Unit reference | Weight kg |
|---------|-----------------|----------------|-----------|
| Without | 10              | ZBY2101        | 0.001     |

### with marked legend (sold singly)

- Start functions: White characters on black background.
- Stop functions: White characters on red background.

| Text     | Unit reference | Weight kg | Text    | Unit reference | Weight kg |
|----------|----------------|-----------|---------|----------------|-----------|
| Auto     | ZBY2115        | 0.001     | Reset   | ZBY2323        | 0.001     |
| Down     | ZBY2308        | 0.001     | Reverse | ZBY2306        | 0.001     |
| Forward  | ZBY2305        | 0.001     | Right   | ZBY2309        | 0.001     |
| Hand     | ZBY2316        | 0.001     | Start   | ZBY2303        | 0.001     |
| Inch     | ZBY2321        | 0.001     | Stop    | ZBY2304        | 0.001     |
| Left     | ZBY2310        | 0.001     | Up      | ZBY2307        | 0.001     |
| Off      | ZBY2312        | 0.001     | O       | ZBY2146        | 0.001     |
| On       | ZBY2311        | 0.001     | I       | ZBY2147        | 0.001     |
| Power on | ZBY2326        | 0.001     | O-I     | ZBY2178        | 0.001     |

## Standard (30 x 50 mm) legend holders for 18 x 27 mm legends

| Text           | Sold in lots of | Unit reference | Weight kg |
|----------------|-----------------|----------------|-----------|
| Without legend | 10              | ZBZ 3          | 0.001     |

## Circular legends, yellow, for mushroom head push buttons

### used for "Emergency stop" function (1)

| Conforming to standards             | Diameter mm | Marking on yellow background | Unit reference | Weight kg |
|-------------------------------------|-------------|------------------------------|----------------|-----------|
| EN/IEC 60204-1 and EN/ISO 13850 (1) | 60          | —                            | ZBY9140        | 0.004     |
|                                     |             | EMERGENCY STOP               | ZBY9330        | 0.004     |
|                                     | 90          | —                            | ZBY8140        | 0.008     |
|                                     |             | EMERGENCY STOP               | ZBY8330        | 0.008     |

### used for "Emergency switching off" function

| Conforming to standard | Diameter mm | Marking on yellow background | Unit reference | Weight kg |
|------------------------|-------------|------------------------------|----------------|-----------|
| EN/IEC 60204-1         | 60          | —                            | ZBY9101        | 0.004     |
|                        |             | EMERGENCY SWITCHING OFF      | ZBY9360        | 0.004     |
|                        | 90          | —                            | ZBY8101        | 0.008     |
|                        |             | EMERGENCY SWITCHING OFF      | ZBY8360        | 0.008     |

## Nameplates, 30 x 40 mm, blank


| Text color | Background color | Unit reference |
|------------|------------------|----------------|
| White      | Black            | ZBY42101       |
| White      | Red              | ZBY44101       |
| Black      | Yellow           | ZBY41101       |
| Black      | White            | ZBY45101       |

## Nameplates, 30 x 50 mm, blank

| Text color | Background color | Unit reference |
|------------|------------------|----------------|
| White      | Black            | ZBY62101       |
| White      | Red              | ZBY64101       |
| Black      | Yellow           | ZBY61101       |
| Black      | White            | ZBY65101       |



ZBY9330



ZBY9360



ZBY42101




ZBY62101

(1) For compliance with standard EN/ISO 13850, paragraph 4.4.6, the Emergency stop logo  has been added.

# Harmony™ XB7 monolithic 22 mm push buttons


Push buttons, switches and pilot lights



ZB5AZ902



ZB5AZ901



ZB5AZ905



ZB5SZ3

## Accessories

| Description                                        | Color | Sold in lots of | Unit reference | Weight kg |
|----------------------------------------------------|-------|-----------------|----------------|-----------|
| Anti-rotation plate                                | –     | 10              | ZB5AZ902       | 0.008     |
| Mounting nut                                       | –     | 10              | ZB5AZ901       | 0.002     |
| Mounting nut tightening tool                       | –     | 1               | ZB5AZ905       | 0.016     |
| Plastic circular blanking plug (with mounting nut) | Black | 10              | ZB5SZ3         | 0.009     |


# Harmony™ XB7 monolithic 22 mm push buttons

Push buttons, switches and pilot lights

## Dimensions


### Push buttons, flush type

**XB7NA●●●●, XB7NH●●**



### Push buttons, projecting type


**XB7NL●●●●**



e : support panel thickness: 1 to 6 mm (metal), 2 to 6 mm (plastic).


### Selector switches, standard handle

**XB7ND●●**



### Key switches


**XB7NG●●**



e : support panel thickness: 1 to 6 mm (metal), 2 to 6 mm (plastic).


### Emergency Stop push buttons (Turn to release)

**XB7NS84●●**




### Emergency Stop push buttons (Push-pull)

**XB7NT84●●**



### Emergency Stop push buttons with key


**XB7NS94●●**



e : support panel thickness: 1 to 6 mm (metal), 2 to 6 mm (plastic).

## Dimensions (continued)



| Pilot lights with screw terminal<br>XB7EV...P | Pilot lights with Faston® terminal<br>XB7EV...P3 | Illuminated push buttons<br>XB7NW..., XB7NJ... |
|-----------------------------------------------|--------------------------------------------------|------------------------------------------------|
|-----------------------------------------------|--------------------------------------------------|------------------------------------------------|



e : support panel thickness: 1 to 6 mm (metal), 2 to 6 mm (plastic).

## Faston clip connection (for pilot lights only)


## "U" type tag connection



(1) 6.5 recommended, 7 mm max.  
(2) M3 screw clamp terminal.

## Mounting

### Diameter of finished mounting holes



(1) Minimum value.  
(2) 40 mm for Emergency Stop push buttons only.  
(3) Standard value: Ø 22.3 (0; + 0.4).



<http://www.schneider-electric.us/>

**Schneider Electric USA, Inc.**

8001 Knightdale Blvd.  
Knightdale, NC 27545

USA Customer Care Center  
Tel: 888-778-2733

**Schneider Electric Canada**

5985 McLaughlin Rd.  
Mississauga, Ontario, Canada L5R 1B8

Canada Customer Care Center  
Tel: 800-565-6699

ART. 960710

The information and dimensions in this catalog are provided for the convenience of our customers. While this information is believed to be accurate, Schneider Electric reserves the right to make updates and changes without prior notification and assumes no liability for any errors or omissions.

Harmony, Schneider Electric and logo are trademarks or registered trademarks of Schneider Electric or its affiliates in the United States and other countries. Other trademarks used herein are the property of their respective owners.

Design: Schneider Electric  
Photos: Schneider Electric

© 2012 Schneider Electric. All rights reserved.

DIA5ED2120503EN-US

07/2012