

**GENERAL SPECIFICATION**

This specification describes the performance characteristics of a single phase, 30 Watts, Single Output Switching Adapter.

1) INPUT

| INPUT | | | | |
|--------------------|-------|----------|--------|---------------------|
| Description | Min. | Typical | Max. | Condition |
| Input Voltage | 90VAC | 115/230V | 264VAC | Full Range; 50/60Hz |
| Input Current(RMS) | - | - | 1A | 90 VAC 50Hz |
| Line Frequency | 47Hz | 50/60Hz | 63Hz | - |
| Inrush Current | - | - | 60A | 230VAC Cold Start |
| Efficiency | - | 75% | - | 115VAC at full load |

2) OUTPUT

| OUTPUT | | | | |
|--------------------------------------|------------------|----------------|------|----------------|
| SINGLE OUTPUT: DC 12V/2.5A, 30W MAX. | | | | |
| NOMINAL VOLTAGE | TOTAL REGULATION | OUTPUT CURRENT | | RIPPLE & NOISE |
| | | MIN. | MAX. | |
| +12V | ±3% | 0A | 2.5A | 120mV |

NOTE:1) 20MHz bandwidth ripple & noise is measured by using 0.1uF C.C. & 10uF/50V 20MHz bandwidth ripple & noise is measured by using 0.1uF C.C. & 10uF/50V

2) Regulation shows the percentage of absolute value of nominal output voltage.
The total output should be 30W max.

3) PROTECTION:**3.1) OVER VOLTAGE PROTECTION:**

If any over voltage occurs, the power supply should latch off before any output exceeds its limit below:

| NOMINAL | OVERVOLTAGE RANGE(V) | |
|------------|----------------------|----------|
| VOLTAGE(V) | FROM | TO |
| +12VDC | +13.5VDC | +15.5VDC |

The power supply will be automatically recovered after the over voltage fault being removed.

3.2) SHORT CIRCUIT PROTECTION

Short circuit occurred on +12V output should not cause any damage to the power supply but shut down the power supply. The power supply will be automatically recovered after the short circuit being removed.

3.3) OVERLOAD PROTECTION

An over load protection will be effected when overloading reaches +160% MAX. The power supply will be automatically recovered after the overload being removed

3.4) VIBRATION

10-55Hz amplitude (sweep 1 min.) less than 2G X, Y, Z 1 hour ea.

3.5) SHOCK: <20G

4) ENVIRONMENT

4.1) Operating temperature

| | |
|-------------------|----------------------------------|
| Temperature | 0 to 40 degree |
| Relative Humidity | 20 to 90 percent, non-condensing |

4.2) SHIPPING AND STORAGE:

| | |
|-------------------|----------------------------------|
| Temperature | -25 to +85 degree centigrade |
| Relative Humidity | 20 to 90 percent, non-condensing |

5) SAFETY REQUIREMENTS(MEET)

The adapter must comply with UL/CSA/TUV/IEC950 standards.

5.1) DIELECTRIC WITHSTAND

- Primary to Secondary : 3000 VAC for 60 Sec.
- Primary to Frame Ground : 1500 VAC for 60 Sec.

5.2) INSULATION RESISTANCE

- Primary to Secondary : 50 Meg. Ohms Min. 500 VDC
- Primary to Frame Ground : 20 Meg. Ohms Min. 500 VDC.

6) ELECTROMAGNETIC COMPABILITY

Tests for conformance to this requirements will be performed with host system.

6.1) FCC Requirements

The adapter shall comply with the FCC rules and regulations Part 15, Subpart J, "Class B" limits.

6.2) CE Requirements

The adapter shall confirm to the "Class B" requirements of EN55022.

**ETA-USA**

HIGH QUALITY SWITCHING POWER SUPPLIES

ETA-USA Tel: 408-778-2793 Fax: 408-779-2753 e-mail: sales@eta-usa.com

7) **RELIABILITY**

MTBF: 50,000 hours min. at max. load for 25 degree centigrade ambient temperature.

8) **BURN-IN TEST**

100% burn-in tested at max. load under 40 +/-5 degree centigrade.

9) **MECHANICAL DIMENSION**

Outside dimension: 106(L) X 60(W) X 30(H)mm
Input connector: IEC320-C7(2 PIN)
Depends on your requirements.

