



CUSTOMER TERMINAL	RoHS	LEAD(Pb)-FREE
Sn96%, Ag4%	Yes	Yes



* DIMENSION MAY BE EXCEEDED WITH SOLDER ONLY



ELECTRICAL SPECIFICATIONS @ 25°C unless otherwise noted:

PARAMETER	TEST CONDITIONS	VALUE
D.C. RESISTANCE	4-5	@20°C
D.C. RESISTANCE	1-8	tie(1+2, 7+8), @20°C
INDUCTANCE	4-5	100kHz, 100mVAC, Ls
DIELECTRIC	4-1	tie(1+2, 7+8), 625VAC, 1 second
URNS RATIO	(1-8):(4-5), tie(1+2, 7+8)	4:1, ±1%
URNS RATIO	(1-8):(2-7)	1:1, ±1%

GENERAL SPECIFICATIONS:

OPERATING TEMPERATURE RANGE: -40°C to +125°C including temp rise.

REV.	DATE
6A	8/09

DETAILS SUBJECT TO CHANGE

Packaging Specifications Method: Tape & Reel PKG-0410 www.midcom-inc.com	Tolerances unless otherwise specified: Angles: $\pm 1^{\circ}$ Decimals: $\pm .005$ [.13] Fractions: $\pm 1/64$ Footprint: $\pm .005$ [.13]	DRAWING TITLE TRANSFORMER eiSos p/n: 750311268	 www.midcom-inc.com	DRAWING NO. 750311268	
	This drawing is dual dimensioned. Dimensions in brackets are in millimeters.			REVISIONS: SEE SHEET 1	SCALE ---