

LOC		DIST		REVISIONS					
P	LTR	DESCRIPTION				DATE	DWN	APVD	
	A2	RELEASED AS PER ECR-09-009652				28.APR.2009	GG	TS	

NOTES
1 PARTS SHALL BE BLANK,SMOOTH,FREE OF BURS AND ALL OTHER FOREIGN MATERIAL
2 ENCLOSURE: IP68,5bar-30bar MIN
3 TEMPERATURE RANGE: -20°C TO +100°C

3.2 gal.Nir 6b

SCALE 2:1

SIZE	ØM	ØD	A	B	C	O-RING	TORQUE
M50x1.5	50	55.0	9.0	6.0	2.0	47.0x2.5	13.5 Nm
M40x1.5	40	45.0	8.0	4.0	2.0	37.0x2.0	13.5 Nm
M32x1.5	32	35.0	8.0	4.0	2.0	28.0x3.0	10.0 Nm
M25x1.5	25	28.0	7.0	4.0	2.0	21.0x1.5	7.0 Nm
M20x1.5	20	24.0	6.5	3.0	2.0	18.0x1.5	5.0 Nm
M16x1.5	16	20.0	6.0	3.0	2.0	13.0x1.5	4.0 Nm

DIMENSIONS:

mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:
n.ISO 8015:
n.ISO 2768-mH-E:
n.DIN 16901-120

0 PLC

1 PLC

2 PLC

3 PLC

4 PLC

ANGLES

±

DWN 11.04.2002

CHK 11.04.2002

APVD

PRODUCT SPEC

APPLICATION SPEC

WEIGHT

MATERIAL

FINISH

Tyco Electronics

Tyco Electronics, AMP.GmbH

53757 Sankt Augustin, Germany

NAME

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

SCHNEIDER

BRAUN

BLANKING PIECE WITH SEALING,METRIC

A 4

00779

C-1102773

SCALE 5:1

SHEET 1 OF 1

REV A2

CUSTOMER DRAWING

AMP 1469-35 REV 31MAR2000

Pro/ENGINEER DRAWING