

.047

.031

.101

.115

120 OHM, AWG 26, 19 STRANDS OF AWG 38,

8-28-06 Date: RADIO FREQUENCY, TWO CONDUCTOR CABLE Revision: В

THIS SPECIFICATION SHEET FORMS A PART OF THE LATEST ISSUE OF RAYCHEM SPECIFICATION 1200.

#### CONSTRUCTION **DETAILS**

## **ELECTRICAL CHARACTERISTICS**

DIMENSIONS ARE NOMINAL VALUES IN INCHES UNLESS OTHERWISE

**CONDUCTORS** AWG 26, 19 Strands of .020 AWG 38, Silver-Coated High Strength Copper Alloy

**DIELECTRICS** 

Rayfoam® H Colors - White/Light Blue

**FILLERS** 

Radiation-Crosslinked Modified ETFE

**SHIELD** 

**JACKET** 

Modified FEP

Flat, .0015 inch thick Tin-Coated Copper

CHARACTERISTIC IMPEDANCE 120 ± 10 ohms, Method D at 1 MHz

**CAPACITANCE - MUTUAL** 12.7 pF/ft. (nominal) 18.2 pF/ft. (maximum)

**VELOCITY OF PROPAGATION** 77% (nominal)

#### **ADDITIONAL** REQUIREMENTS

## **ELECTRICAL**

CONDUCTOR RESISTANCE 42.0 ohms/1000 ft. (nominal) **INSULATION RESISTANCE** 10,000 megohms (minimum)

for 1000 ft.

JACKET FLAWS SPARK TEST 1.0 kV (rms)

**IMPULSE TEST** 6.0 kV (peak) VOLTAGE WITHSTAND

(DIELECTRIC) 1500 volts (rms) (minimum)

### **ENVIRONMENTAL**

**FLAMMABILITY** Method B **HEAT SHOCK** 225°C

-55°C/3.25 inch mandrel LOW TEMPERATURE-COLD BEND

**VOLTAGE WITHSTAND** 

(POST ENVIRONMENTAL) 1000 volts (rms), 1 minute

#### **PHYSICAL**

INSULATION (DIELECTRIC)

(Prior to Cabling)

**ELONGATION TENSILE STRENGTH JACKET** 

**ELONGATION TENSILE STRENGTH** JACKET THICKNESS SHIELD COVERAGE

50%(minimum) 600 lbf/in2 (minimum)

200%(minimum) 2000 lbf/in<sup>2</sup> (minimum) .007 inch (nominal) 92%(minimum)

Outer jacket will be white (designated by a "-9" appended to the part number, e.g., 2026G2424-9) unless otherwise specified.

Designate outer jacket color with a dash number in accordance with MIL-STD-681. Other codes and suffixes may be added to the part number, as necessary, to capture any additional requirements imposed by the purchase order.

WEIGHT

9.8 lbs/1000 ft. (nominal)

Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice.

Tyco Electronics also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.



Wire & Cable

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: 2026G2424-9