




REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL	22MAY2015	DW	CW




NOTES:
 1. TECHNICAL CHARACTERISTICS:
 HOOD MATERIAL: DIE CAST ALUMINIUM ALLOY
 SURFACE: POWDER COATED, GREY
 OPERATION TEMPERATURE: -40-+125°C
 DEGREE OF PROTECTION: IP65 (MATED)

注释:
 1. 技术参数:
 上壳材料: 铝合金
 表面处理: 粉末涂层, 灰色
 工作温度: -40-+125°C
 防护等级: IP65(配合)



SCALE 1:2



T1240160216-000	H16B-TGH-2PG16	HIGH CONSTRUCTION	PG16	PG16
T1240160221-000	H16B-TGH-2PG21		PG21	PG21
T1240160225-000	H16B-TGH-2M25		M25	M25
T1240160232-000	H16B-TGH-2M32		M32	M32
T1240163225-000	H16B-TGH-M32/M25		M32	M25
PART NUMBER	DESCRIPTION	TYPE	IG1	IG2

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 22MAY2014 David Wang	STE TE Connectivity	
DIMENSIONS: mm		CHK 22MAY2014 Chris Wang		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD 22MAY2014 Xiang Xu	NAME H16B-TGH-2M/PG	
0 PLC ±-		PRODUCT SPEC 108-137013	SIZE CAGE CODE DRAWING NO RESTRICTED TO	
1 PLC ±-		APPLICATION SPEC 114-137013	A300779 C-T124016XXXX000	
2 PLC ±-		WEIGHT -	SCALE 1:1 SHEET 1 OF 1 REV A	
3 PLC ±-		Customer Drawing		
4 PLC ±-				
ANGLES ±-				
FINISH -				
-				