



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

## Protect It! 6-Outlet Surge Protector, 8-ft. Cord, 990 Joules, Low-Profile Right-Angle 5-15P plug

MODEL NUMBER: TLP608



### Highlights

- 6 outlets / 8-ft. cord
- 990 joule rating
- \$20,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)

### Package Includes

- TLP608
- Instruction manual with warranty information

### Description

Tripp Lite's TLP608 Surge Suppressor offers economical AC surge suppression for full protection of workstations, desktop PCs, telecom systems and other sensitive electronics. Built-in AC surge suppression shields connected equipment from damage and performance problems due to transient surges. TLP608 offers 6 total outlets, 8 foot cord and diagnostic LED to warn of suppressor damage. AC suppression rated at 990 joules shields equipment from surges and line noise. Attractive gray suppressor housing with keyhole mounting tabs and 1 designated transformer plug outlet offers convenient protection of desktop computer equipment and accessories. \$20,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only).

### Features

- 990 joules AC surge suppression shields equipment from the strongest surges and line noise
- 6 AC outlets with room for 1 transformer plugs without blocking outlets covers computers and peripherals
- 8 foot AC line cable
- Built-in power switch and 15 amp circuit breaker offers power control and overload protection over all outlets
- Right angle flat plug
- Fail-safe thermal fusing protects against fire and other damage in the event of an extreme, extended overvoltage or surge condition
- Diagnostic LEDs confirm surge suppression status
- Attractive gray suppressor housing with keyhole mounting tabs allow versatile placement options
- UL1449 3rd Edition Rated (500V all modes), UL1363 (Power Tap), UL497A (Communications), Meets FCC part 68 rules, cUL (Canada)
- Exceeds IEEE 587 category A & B surge suppression specifications
- \$20,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)
- Automatic shutoff cuts power to outlets when the protection circuit has been compromised

## Specifications

### OUTPUT

Frequency Compatibility

60 Hz



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

|  |  |
|--|--|
| Output Receptacles                           | (6) 5-15R  |
| Output (Watts)                               | 1875   |
| Circuit Breaker (amps)                       | 15   |
| Transformer Accommodation                    | 1 designated transformer plug, accepts up to 4 transformers without covering outlets |
| Outlet Orientation                           | Single row   |
| Right-Angle Outlets                          | No   |
| <b>INPUT</b>                                 |  |
| Nominal Input Voltage(s) Supported           | 120V AC  |
| Recommended Electrical Service               | 120V (110-125V)  |
| Input Connection Type                        | NEMA 5-15P Low-Profile   |
| Input Cord Length (ft.)                      | 8  |
| Input Cord Length (m)                        | 2.44   |
| Input Cord Gauge Type                        | 14 gauge, SJT  |
| Voltage Compatibility (VAC)                  | 120  |
| Maximum Surge Amps                           | 35500  |
| Right-Angle Plug                             | Yes  |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b> |  |
| Switches                                     | Combination AC circuit breaker and 2 position red illuminated on/off power switch    |
| Diagnostic LED Details                       | Built-in LED confirms suppressor "protection present" (green) status                 |
| <b>SURGE / NOISE SUPPRESSION</b>             |  |
| AC Suppression Joule Rating                  | 990  |
| AC Suppression Response Time                 | < 1 ns   |
| Protection Modes                             | Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression   |
| Clamping Voltage (RMS)                       | 150  |
| UL1449 Let Through Rating                    | 500V   |
| EMI / RFI Filtering                          | up to 20dB   |
| <b>DATALINE SURGE SUPPRESSION</b>            |  |
| Telephone/DSL Protection                     | No   |
| Cable (Coax) Protection                      | No   |
| Network (Ethernet) Protection                | No   |
| <b>PHYSICAL</b>                              |  |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

|  |   |
|--|---|
| Shipping Dimensions (hwd / in.)                            | 13.2 x 5.2 x 1.8  |
| Shipping Dimensions (hwd / cm)                             | 33.53 x 13.21 x 4.57  |
| Shipping Weight (lbs.)                                     | 1.32  |
| Shipping Weight (kg)                                       | 0.60  |
| Unit Dimensions (hwd / in.)                                | 10.80 x 1.85 x 1.23   |
| Unit Dimensions (hwd / cm)                                 | 27.43 x 4.70 x 3.12   |
| Unit Weight (lbs.)   | 1.12  |
| Unit Weight (kg)   | 0.51  |
| Material of Construction                                   | Plastic   |
| Integrated Keyhole Mounting Tabs                           | Keyhole mounting tabs enable wall mounting                          |
| Housing Color  | Cool Grey 2C  |
| Receptacle Color   | Cool Grey 2C  |
| Color (AC Line Cord)                                       | Cool Grey 2C  |
| Outlets Measurement (Center to Center)                     | 28.5mm  |
| Keyhole Slot Mounting Measurement (Center to Center)       | Distance between slots = 101mm; Distance between slot height = 28mm |
| <b>CERTIFICATIONS</b>                                      |   |
| UL1449 3rd Edition (AC Suppression)                        | UL1449 3RD EDITION  |
| UL1363 (Power Tap)   | UL1363  |
| UL497A (Communications)                                    | UL497A  |
| FCC Part 68 (Communications)                               | FCC Part 68   |
| cUL / CSA (Canada)   | cUL   |
| Industry Canada (Communications)                           | Industry Canada   |
| Approvals  | Exceeds IEEE 587 category A&B specifications                        |
| <b>WARRANTY</b>  |   |
| Product Warranty Period (Worldwide)                        | Lifetime limited warranty   |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$20,000 <a href="#">Ultimate Lifetime Insurance</a>                |

© 2017 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>