UNCONTROLLED DOCUMENT

Ø5.00 [0.197]

5.0 [0.197] MIN.

PART NUMBER	
SSI-LX5099IGWCA-50)

REV.	E.C.N. NUMBER AND REVISION COMMENTS	DATE
Α	E.C.N. #10893.	7.23.02
В	E.C.N. #11343.	8.2.06

REV. В

UNITS

mΑ mΑ mW mW/°C TC

ď

3 SEC. MAX

ELECTRO-OPTICAL CHARACTERISTICS TA=25°C If=			I _f = 20)mA	
PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH		635 (RED)		nm	
		565 (GREEN	I)	nm	
FORWARD VOLTAGE (R/G)		2.0/2.2	2.5/2.6	۷f	
REVERSE VOLTAGE	5.0			٧r	Ir=100µA
AXIAL INTENSITY (R/G)		10		mcd	lf=20mA
VIEWING ANGLE		60		2x theta	
EMITTED COLOR: RED	/GREEN				
EPOXY LENS FINISH: MILK	Y WHITE	DIFFUSED			

LIMITS OF SAFE OPERATION AT 25°C					
PARAMETER	COLORS	MAX			
PEAK FORWARD CURRENT*		150			
STEADY CURRENT	(R/G)	30/25			
POWER DISSIPATION		105			
DERATE FROM 25°C		-1.2			
OPERATING STORAGE TEMP		-40 to +85			

* t<10µS

SOLDERING TEMP.

2.0mm FROM BODY

- 1. SSL-LX5D99IGW-CA, BICOLOR LED.
- 2. RED CATHODE LEAD: LXP-WST24RDTOC, RED INSULATION, CUT 48mm LONG, STRIP 3mm BOTH ENDS.
- 3. COMMON ANODE: LXP-WST24BLTOC, BLACK INSULATION, CUT 48mm LONG, STRIP 3mm BOTH ENDS.
- 4. GREEN CATHODE LEAD: LXP-WST24GRTOC, GREEN INSULATION. CUT 48mm LONG, STIRP 3mm BOTH ENDS.
 - 5. LXP-HEATSHRINK-2, 1/16" x 13mm. (3 PCS.)
 - 6. CUT LED LEADS TO APPROX. 3/8" IN LENGTH.
 - 7. CRIMP WIRE LEADS TO CUT LED LEADS.

UNCONTROU FD	DOCUMENT

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECINAL PRECISION ARE: X=±1 (±0.039), X,X=±0.5 (±0.020), X,XX=±0.25 (±0.0010), X,XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= +DECINAL PRECISION MAX.= +0.00

REV. PART NUMBER SSI-LX5099IGWCA-50 T-1 (T-1 3/4) BICOLOR 635nm RED/565nm GREEN LED,

MILKY WHITE DIFFUSED LENS WITH 2" WIRE LEADS.

CONFIDENTIAL INFORMATION THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790 US WEB: www.lumex.com TW WEB: www.lumex.com.tw

+260

CHECKED BY: DRAWN BY: APPROVED BY: DATE: 5.21.02 1 OF 1 PAGE: SCALE: N/A CT

A NOTES:

8,60 [0,339]

50.80 + 10.00

2.000+0.394

3.00 [0.118] A

+/- 1,00(,040)