

EXTERNAL DESKTOP POWER SUPPLY

24VDC 200WATT

SW4044F



Features:

- Universal Input
- IEC-320-C14 Input Connector
- 3 Year Warranty
- Efficiency Level VI
- Safety approved to: UL,CUL,FCC,GS,CE,RCM



Description:

The Stontronics Range of 200 watt AC/DC switch mode power supplies provide 200 watts of continuous output power in a high quality compact enclosure suitable for many general power applications.

Specification	
Part Number	SW4044F
Input Voltage Range	100 → 240 V ac
Input Frequency Range	50 → 60Hz
Input Connector	Standard 3 pin IEC C14 input connector
Input Current Rated	2.8A Max.
Inrush Current	100A Max. / 240Vac (Cold start at 25 °C, full load)
Efficiency	88% Min
Input Power(Output: No Load)	<0.5 W (At 230Vac & No load)
Output Voltage Rating	24vdc
Output Current Range	8.3A Max.
Output Min Current	0.05A
Output Connection Type	2.1 x 5.5 x 12 mm Centre Positive – straight
Line and Load Regulation	+/-5%
Over Voltage Protection	V out * 150% Max.
Over Load Protection	I out * 150% Max.
Short Circuit Protection	Automatic recovery after short-circuit fault being removed
Ripple Voltage	240mV
Hi-Pot	3000Vac 10mA
Safety Approved	UL,CUL,GS,PSE,BSMI
EMI Standard	FCC Class B, CE
Operating Temperature Range	0 → +40 °C
Storage Temperature	-20 to 80°C
Operating Humidity	20% to 80%
Storage Humidity	10% to 90%
Dimensions	(L) 183.2mm x (W) 81mm x (H) 42.3mm
Product Weight	860gm
Regulator Type	Switched Mode Power Supply

General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

TT Electronics | Stontronics Ltd
Chancerygate Business Centre, Cradock Road, Reading RG2 0AH, UK
t: +44 (0) 118 931 1199


EXTERNAL DESKTOP POWER SUPPLY

24VDC 200WATT

SW4044F



Diagrams



General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.