Jun.1.2020 Copyright 2020 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

ELV, RoHS COMPLIANT

3 Delete dimension

Packing specification

(1)After placing parts in trays, stack in five layers.
(Top layer will be empty.)

(2) Place bound trays in box,
then place cardboard sheet on top.

(3) Using packing tape, affix sheet of
cardboard to box in four places.

(4) Place lid on box and seal with packing tape.

HRS DRAWING FOR REFERENCE

Note 1. Use the M4 size screw for fixing to panel.
Fastening torque shall be 2.4N・m± 20%.
2. Counter part is HVH-280-2/2S-HU(CL778-0504-0-00)
3. Following parts are available.
HOLDER :HVH-280-2/2P-HO(CL778-0506-0-00)
POWER CRIMP CONTACT : HVH-280-1214PCF(CL778-0501-0-00)
CHECK CRIMP CONTACT : ZE05-2022SCF(CL752-2001-0-00)
4. When installing the connector facing upwards,
make it into a casing shape in which water does not collect.
5. Assembly procedure refer to ETAD-T0573-00

HOUSING ASSY
(1:1)

A-A

NO.	MATERIAL	FINISH , REMARKS
2	SILICONE	WHITE
1	PBT	ORANGE, UL94 V-0

NO.	MATERIAL	FINISH , REMARKS
4	SWCH	SURFACE :NICKEL PLATING 5μmMIN
3	SUS	SURFACE :TIN PLATING 1μm MIN UNDER PLATING:NICKEL PLATING 0.5μm MIN

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	3	2	DIS-T-00003442	TS. SHIMIZU	AH. EDASHIGE	18. 07. 26

HIROSE ELECTRIC CO., LTD.

APPROVED	: HK. UMEHARA	16. 11. 28	DRAWING NO.	EDC-367811-00-00
CHECKED	: HK. UMEHARA	16. 11. 28	PART NO.	HVH-280-2/2P-HU
DESIGNED	: KO. NAKAMURA	16. 11. 28	CODE NO.	CL778-0500-0-00
DRAWN	: KO. NAKAMURA	16. 11. 28		3 1/1

FORM HC0011-5-7