

“Stay Connected” with



Power Components


a PennEngineering® Company



- Compact design—lightweight yet strong.
- Electro-tin plated for low contact resistance and corrosion protection when used with copper conductors.
- Require no special installation tools.
- UL and CSA certified for use with copper and aluminum conductors.
- Ports are marked with catalog description and conductor range.
- DFARS Compliant

Heyco® Aluminum Solderless Connectors

WIRE RANGE (AWG)	PART NO.	DESCRIPTION	PART DIMENSIONS							
			A Width		B Length		C Height		Bolt Size	
			in.	mm.	in.	mm.	in.	mm.	in.	mm.
Single Conductor										
4-14	1863	A35	.50	12,7	1.06	26,9	.50	12,7		
2-14	1864	A90	.50	12,7	1.16	29,5	.56	14,2	1/4	6,4
1/0-14	1884	A125	.63	16,0	1.47	37,3	.79	20,1		
Two Conductors										
2-14	1864-2	A90-2	.91	23,0	1.16	29,5	.56	14,2	1/4	6,4
1/0-14	1884-2	A125-2	1.12	28,4	1.47	37,3	.78	19,8		




- 100% conductivity for highest efficiency.
- Completely reuseable.
- Require no special installation tools.
- UL listed and CSA certified for use with copper conductors.
- Marked with catalog description and conductor range.
- DFARS Compliant

Heyco® Copper Lug Connectors

Copper Single Hole Offset Lugs

WIRE RANGE (AWG)	PART NO.	DESCRIPTION	CURRENT RATING AMPS	HEIGHT WITH MAX. WIRE	PART DIMENSIONS				Bolt Size		
					A Tang Width		B Length		in.	mm.	
				in.	mm.	in.	mm.	in.	mm.		
6-14	1851	CB 35	50	3/4	19,1	.38	9,7	1.38	35,1	3/16	4,8



Quick Specs

Materials
Certifications

6061-T6 aluminum alloy; electrolytic copper



Listed under Underwriters' Laboratories File E80121



Certified by the Canadian Standards Association File 242954 & 246619

Flammability Rating

94V-0