# XGSZ09L2



#### Main

Range of product	OsiSense XG	
Accessory / separate part category	Connection accessories	
Accessory / separate part type	Connecting cable	
Accessory / separate part designation	Pre-wired M12 female connector	
Accessory / separate part destination	For 24 V DC supply of connection box	
Cable length	6.56 ft (2 m)	

# Complementary

Product compatibility	TCSAMT31FP XGSZ33ETH	
Electrical connection	1 female connector M12 4 pins (A coding)	
Color	Black	
Product weight	0.25 lb(US) (0.115 kg)	

#### **Environment**

IP degree of protection	IP67
-------------------------	------

### **Offer Sustainability**

Not Green Premium product	Not Green Premium product	
Will be Compliant on 4Q2013	Will be Compliant on 4Q2013 Will be Compliant on 4Q2013	
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:	
Diisononyl phthalate (DINP), which is known to the Stat of California to cause cancer, and	e Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and	
Di-isodecyl phthalate (DIDP), which is known to the Star of California to cause birth defects or other reproductive harm.	teDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.	
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov	

### Contractual warranty

Warranty period 18 months	
---------------------------	--

# **Wiring Diagram**

### **Modbus Connections**



Pin no.		Signal
1	Red	+ 24 VDC
2	NC	-
3	Black	0 VDC