


# MALE PCB PINS

## PRINTED CIRCUIT PINS

### 8600/8954/8955

8XXX-X-05-XX-00-00-03-0

Square press-fit in .043 plated through-hole




| Basic Part Number | Pin Length A |
|-------------------|--------------|
| 8600-0            | .400         |
| 8600-1            | .850         |
| 8600-2            | 1.200        |
| 8954-0            | .136         |
| 8955-0            | .655         |

### 3159

3159-X-00-XX-00-00-08-0

Swage mount in .064 hole




| Basic Part Number | Board Thickness | Length V |
|-------------------|-----------------|----------|
| 3159-1            | .031            | .062     |
| 3159-2            | .062            | .094     |
| 3159-3            | .094            | .125     |
| 3159-4            | .125            | .156     |

### 8952

8952-0-05-XX-00-00-03-0


Square press-fit in .087 plated through-hole



### 8953

8953-0-05-XX-00-00-03-0


Square press-fit in .047 plated through-hole



### 3230

3230-X-00-XX-00-00-08-0

Swage mount in .094 hole




| Basic Part Number | Board Thickness | Length A | Length V |
|-------------------|-----------------|----------|----------|
| 3230-1            | .031            | .202     | .065     |
| 3230-2            | .062            | .228     | .095     |
| 3230-3            | .094            | .258     | .125     |
| 3230-4            | .125            | .288     | .155     |

### 3146

3146-2-00-XX-00-00-08-0

Swage mount in .076 hole

For a .062 thick board




### 3142

3142-2-00-XX-00-00-08-0

Swage mount in .062 hole

For a .062 thick board




### 3232

3232-3-00-XX-00-00-08-0

Swage mount in .062 hole

For a .094 thick board




### 3145

3145-2-00-XX-00-00-08-0

Swage mount in .076 hole

For a .062 thick board



#### SPECIFICATIONS:

**Pin Material:** Brass Alloy 360, 1/2 Hard  
( Except swage pins which are annealed )

**Dimensions:** Inches

**Tolerances On:** Lengths:  $\pm .005$   
Diameters:  $\pm .002$   
Angles:  $\pm 2^\circ$



**ORDER CODE:** XXXX - X - 0X - XX - 00 - 00 - XX - 0

**BASIC PART #**

**SPECIFY PIN FINISH:**

- 01 200  $\mu$ " TIN/LEAD OVER NICKEL
- ◆ 80 200  $\mu$ " TIN OVER NICKEL (RoHS)
- ◆ 15 10  $\mu$ " GOLD OVER NICKEL (RoHS)
- ◆ 21 20  $\mu$ " GOLD OVER NICKEL (RoHS)
- ◆ 34 50  $\mu$ " GOLD OVER NICKEL (RoHS)



Mill-Max Mfg. Corp. • 190 Pine Hollow Road, P.O. Box 300, Oyster Bay, NY 11771 • 516-922-6000 • Fax: 516-922-9253 • www.mill-max.com