

K-No.: 25088

Powerline transformer

Date: 22.07.2014

Customer: Standard type

Customers part No.:


Page 1 of 3

Mechanical outline (mm): (General Tolerances DIN ISO 2768-c)

 Toleranz der Stiftabstände
 $\pm 0,2$ mm
 (Tolerances grid distance)

 Kennzeichnung Stift 1
 (marking pin 1)

 DC=Date Code
 F=Factory


 Vorschlag zur Anordnung
 der Anschlußflächen
 (Example for pad position)


Connections:

 Unused pin(s):
 No. 6,7

Marking

VAC DC
 5024X090
 F

Schematic diagram:

Operational data/characteristic data (nominal values):
 $f = 10 \dots 1000$ kHz

 $I_{RMS} < 40$ mA (50/60Hz)

 $C_{K1+2-3} \leq 30$ pF

 $R_{Cu1} \leq 100$ m Ω , $R_{Cu2} \leq 100$ m Ω , $R_{Cu3} \leq 100$ m Ω

Operating temperature: -40 °C ... +85 °C

Storage temperature: -40 °C ... +85 °C

Inspection: (V: 100%-Test; AQL...: DIN ISO 2859-Teil1)

- | | | | | |
|----|------------|----------|--|-----------------------|
| 1) | (V) | M3014: | $U_{p,eff} = 3,0$ kV, 2 s, | N3 vs N1+N2 |
| 2) | (AQL 0,25) | M3011/1: | $L_3 = 880$ μ H $\pm 25\%$, $f = 10$ kHz, | $U_{AC,eff} = 100$ mV |
| 3) | (V) | M3011/6: | Polarity, Turns ratio: | Tolerance ± 2 % |
| 4) | (Fix05) | M3291: | Solderability test acc. to chapter 1 | |
| 5) | (AQL 1/S4) | M3200: | Mechanical test | |

see page 2

Applicable documents: See page 2

Date	Name	Index	Change
22.07.14	Pf.	82	Characteristic data: $I_{DC} < 40$ mA changed to $I_{RMS} < 40$ mA (50/60Hz). Lapidary change.
26.10.12	Pf.	82	Operational data: IDC < 40 mA inserted. Lapidary change.
Editor: KB-E		Design: BS.	KB-PM: Ert. check
			released: HH

K-No.: 25088

Powerline transformer

Date: 22.07.2014

Customer: Standard type

Customers part No.:

Page 2 of 3

Type test

1) High voltage test according to M3014

 $U_{p,eff} = 3 \text{ kV}$, 1 min, N1+N2 vs N3

2) M3292: Resistance to soldering heat acc. to chapter 2

Measurements after temperature balance of the test samples at room temperature

Applicable documents:

Designed, manufactured and tested in accordance to EN 60950 (VDE 0805, UL1950) and complies with the standards.

Parameters: Reinforced insulation: N1+N2 vs N3

Working voltage: 400 V r.m.s.

overvoltage category: 2

Pollution degree: 2

Insulation material group: 3

Housing material, casting resin and wire UL – listed

Packing: Drypack / MSL according VAC M3027

Editor: KB-E

Design: BS.

KB-PM: Ert.
check

released: HH

K-No.: 25088



Powerline transformer

Date: 22.07.2014

Customer: Standard type

Customers part No.:


Page 3 of 3

packing information / Verpackungsinformation


the first two nests must be crushed for better pockets.
 Die ersten zwei Nester gequetscht für besseres einfädeln.

leading 25 empty pockets
 Vorlauf 25 leere Nester


cover tape 400mm longer than carrier tape
 Deckband 400mm länger als Blistergurt



laging 25 empty pockets
 Nachlauf 25 leere Nester

laging: >25 empty pockets
 Nachlauf >25 leere Nester

leading: >25 empty pockets
 Vorlauf >25 leere Nester



Orientation of Pin 1 in carrier tape
 Anordnung von Stift 1 im Blistergurt

Insertion of components according orientation 3 shown in M-sheet 3510
 Einsetzen der Bauelemente nach M-Blatt 3510 Orientierung 3

quantities in packing: 450 pieces/tape (packing carton) 450 Bauelemente/Rolle
 Verpackungsmenge 5 tapes reel/carton (outside)=2250 pieces /carton(outside)
 5 Rollen/Karton =2250 Bauelemente /Außenkarton

Editor: KB-E

Design: BS.

 KB-PM: Ert.
 check

released: HH