


**Description**

- Voltage controlled crystal oscillator in a ceramic package with a hermetically sealed metal lid
- Model IQXV-52
- Model Issue number 1

**Frequency Parameters**

- Frequency 46.6560MHz
- Frequency Stability  $\pm 50.00\text{ppm}$
- Operating Temperature Range  $-40.00$  to  $85.00^\circ\text{C}$
- Ageing (@  $25^\circ\text{C}$ ):  $\pm 3\text{ppm max}$

**Electrical Parameters**

- Supply Voltage  $2.5\text{V} \pm 5\%$
- Current Draw  $25.00\text{mA}$

**Frequency Adjustment**

- Pulling  $\pm 100\text{ppm min}$
- Control Voltage  $1.25\text{V} \pm 1.05\text{V}$
- Input Impedance  $2\text{M}\Omega$  min
- Linearity:  $\pm 10\%$  max

**Output Details**

- Output Compatibility HCMOS
- Drive Capability  $15\text{pF max}$
- Rise and Fall Time  $5.0\text{ns max}$
- Duty Cycle  $45/55\%$
- Start Up Time:  $10\text{ms max}$
- Start Up Time:  $10\text{ms max}$
- Start Up Time:  $10\text{ms max}$

**Output Control**

- Standby Operation:  
Logic '1' ( $>70\%$  Vs) to pad 2 enables oscillator output  
Logic '0' ( $<30\%$  Vs) to pad 2 disables oscillator output: when disabled the oscillator output goes to the high impedance state  
No connection pad 2 enables oscillator output

**Output Levels**

- VoH:  $>90\%$  of Vs
- VoL:  $<10\%$  of Vs

**Noise Parameters**




- Period Jitter (pk-pk):  $100\text{ps max}$
- Period Jitter (one sigma):  $25\text{ps max}$

**Environmental Parameters**

- Storage Temperature Range:  $-55$  to  $125^\circ\text{C}$
- Drop:  $1.2\text{m}$  drop (3 times) onto a hard surface
- Vibration:  $1.5\text{mm}$  amplitude,  $10-55-10\text{Hz}$ , full sine wave,  $2\text{mins}$  in 3 mutually perpendicular planes, duration  $2\text{hrs}$  in each plane


**Compliance**

- RoHS Status (2011/65/EU) Compliant
- REACH Status Compliant
- MSL Rating (JDEC-STD-033): Not Applicable


**Outline (mm)**


Underside View

Pad Connections  
 1. Voltage Control  
 2. Standby Operation  
 3. GND  
 4. Output  
 5. N/C  
 6. +Vs

**Solder Pad Layout**

**Sales Office Contact Details:**

UK: +44 (0)1460 270200  
 Germany: 0800 1808 443

France: 0800 901 383  
 USA: +1.760.318.2824

Email: [info@iqdfrequencyproducts.com](mailto:info@iqdfrequencyproducts.com)  
 Web: [www.iqdfrequencyproducts.com](http://www.iqdfrequencyproducts.com)

**Packaging Details**

- Pack Style: Bulk      Loose in bulk pack  
Pack Size: 1
- *Alternative packing option available*

---

**Sales Office Contact Details:**

UK: +44 (0)1460 270200  
Germany: 0800 1808 443

France: 0800 901 383  
USA: +1.760.318.2824

Email: [info@iqdfrequencyproducts.com](mailto:info@iqdfrequencyproducts.com)  
Web: [www.iqdfrequencyproducts.com](http://www.iqdfrequencyproducts.com)