


US Power Supply Cord with IEC Connector C19, straight



See below:
[Approvals and Compliances](#)

Description

- 1 Function :
- Power Cord , Protection class I
- Pin temperature 70 °C
- custom specific versions on request

Technical Data

| | | | |
|---------------------------------|---|-------------------------|--|
| Ratings UL/CSA | 15 A / 125 VAC; 50/60Hz | appliance inlet/-outlet | C19 acc. to UL 498, CSA C22.2 no. 42 (for cold conditions) pin-temperature 70 °C, 16 A, Protection Class I |
| Allowable Operation Temperature | -40 °C to 70 °C | | |
| IP-Protection | from front side IP 40 acc. to IEC 60529 | | |
| Insulation cover | Suitable for appliances with protection class I acc. to IEC 61140 | | |
| Material: Housing | black | | |



Approvals and Compliances

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in [Details about Approvals](#)

Approvals




The approval mark is used by the testing authorities to certify compliance with the safety requirements placed on electronic products.

Approval Reference Type:

| Approval Logo | Certificates | Certification Body | Description |
|---|-------------------------------|--------------------|---------------------------|
|  | UL Approvals | UL | UL File Number: |
|  | CSA Approvals | CSA | CSA Certification Record: |


Product standards

Product standards that are referenced

| Organization | Design | Standard | Description |
|---|-----------------------|------------------|---|
|  | Designed according to | IEC 60320-1 | Appliance couplers for household and similar general purposes |
|  | Designed according to | UL 498 | Standard for Attachment Plugs and Receptacles |
|  | Designed according to | CSA C22.2 no. 42 | General Use Receptacles, Attachment Plugs, and Similar Wiring Devices |



Application standards

Application standards where the product can be used

| Organization | Design | Standard | Description |
|---|--------------------------------|--------------|---|
|  | Designed for applications acc. | IEC/UL 60950 | IEC 60950-1 includes the basic requirements for the safety of information technology equipment. |

Compliances

The product complies with following Guide Lines

| Identification | Details | Initiator | Description |
|--|--|-------------|---|
| CE | CE declaration of conformity | SCHURTER AG | The CE marking declares that the product complies with the applicable requirements laid down in the harmonisation of Community legislation on its affixing in accordance with EU Regulation 765/2008. |
|  | RoHS | SCHURTER AG | EU Directive RoHS 2011/65/EU |
|  | REACH | SCHURTER AG | On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force. |

All Variants

| Connector | | cable | | | | Plug | | | | Order Number | |
|-----------|--------|--------------|-------------------------|------------|-------|---------------|---------|-----------|-------|--------------|-----------|
| Type | V-Lock | Cord Type | Conductor cross section | Length [m] | Color | Type | Country | Standard | Style | | |
| C19 | | SJT 3x14 AWG | 3 x 14 AWG | 2.5 | black | North America | USA | NEMA 5-15 | - | - | 6009.5195 |

 Most Popular.

Availability for all products can be searched real-time:<https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER>

Packaging unit 25 Pcs

Mating Inlets/Plugs

Category / Description

[Appliance Inlet Overview complete](#)



| | |
|--|------|
| IEC Appliance Inlet C20 or C24, Split panel or screw-on mounting, PCB Terminal | GSP4 |
| IEC Appliance Inlet C20, Screw-on Mounting, Rear Side, PCB Terminal | 1601 |
| IEC Appliance Inlet C20, Screw-on Mounting, Front Side, Solder or Quick-connect Terminal | 4798 |
| IEC Appliance Inlet C20, Snap-in Mounting, Front Side, Solder or Quick-connect Terminal | 4793 |
| IEC Appliance Inlet C20, Snap-in Mounting, Front Side, Solder or Quick Connect Terminal | 1624 |

[Appliance Inlet further types to 6009.5195](#)

...



[Appliance inlets/-outlets Overview complete](#)

| | |
|---|------|
| Plug Coupler IEC C20 / IEC J, Screw-on Mounting | 4730 |
|---|------|

[Appliance inlets/-outlets further types to 6009.5195](#)



[IEC Inlet Filter Overview complete](#)

| | |
|---|------|
| C20F, 20 A, prewired, Standard and Medical Version, Solder, quick connect or wires (stranded), Capacitor: X2, Screw, Mounting Front-/Rear-Side, Power Entry Modules with Filter | C20F |
|---|------|

[IEC Inlet Filter further types to 6009.5195](#)

Category / Description



[Plug Overview complete](#)

| | |
|--|------|
| 0922, Mounting: Power Cord, Wire connections 3 x (16-12AWG), Plug: IEC I | 0922 |
| Plug further types to 6009.5195 | |



[Power Entry Module Overview complete](#)

| | |
|---|------|
| IEC Appliance Inlet C20 with Line Switch, 2-pole | EC11 |
| 0 0 0 0 0 | 6136 |
| IEC Appliance Inlet C20 with Circuit Breaker TA45 | EF11 |
| Power Entry Module further types to 6009.5195 | |



[Power Entry Module with line filter Overview complete](#)

| | |
|--|------|
| EC12, 20 A, prewired, Standard and Medical Version, Quick connect terminals 6.3 x 0.8 mm, Capacitor: X2, Screw, Mounting Front-Side, Power Entry Modules with Filter | EC12 |
| IEC Appliance Inlet C20 with Filter, Circuit Breaker TA45 (recessed) | EF12 |
| Power Entry Module with line filter further types to 6009.5195 | |