



Main

Range of product	Twido
Accessory / separate part category	Connection accessories
Accessory / separate part type	Tap isolation box
Accessory / separate part designation	Tap isolation box
Accessory / separate part destination	RS485 serial link
Product specific application	Line end adaptor (RC 120 Ohm, 1 nF) Lines prepolarised (2 R 620 Ohm) RS485 line isolation

Complementary

Range compatibility	Modicon M238 logic controller Twido programmable controller
[Us] rated supply voltage	24 V
Supply circuit type	DC
Supply	External
Electrical connection	2 connectors RJ45 for tap-off 1 screw terminal block
Mounting support	35 mm symmetrical DIN rail
Product weight	0.22 lb(US) (0.1 kg)

Environment

Contractual warranty

Warranty period	18 months
-----------------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.