


TSI SPECIFICATION SHEET CABLE, RADIO FREQUENCY, TWIN CONDUCTOR, BALANCED LINE

TWC-124-1A

MARK: TROMPETER ELECTRONICS TWINAX, TWC-124-1A (*)

(*) VENDOR ID LETTER



REQUIREMENTS:

1. IMPEDENCE (OF PAIR)	124 ± 5 OHMS		
2. OPERATING VOLTAGE	0.3 KVRMS MAX/0.6 KVDC		
3. BEND RADIUS	1.5 INCH MIN		
4. CAPACITANCE	12.4 PF/FT		
5. CONDUCTOR LOOP RESISTANCE	570.6 OHMS/1000 FT MAX		
6. VELOCITY OF PROPAGATION	66% NOM		
7. ATTENUATION: FREQUENCY	dB/100 FT NOM	FREQUENCY	dB/100 FT NOM
1 MHz	3.25	40 MHz	11.80
3 MHz	4.40	50 MHz	13.20
4 MHz	4.80	100 MHz	18.70
5 MHz	5.20	200 MHz	26.40
7 MHz	5.60	500 MHz	41.70
10 MHz	5.90	700 MHz	49.40
20 MHz	8.30	1000 MHz	59.00
30 MHz	10.20		
8. WEIGHT	16.1 LB/1000 FT		
9. OPERATING TEMPERATURE RANGE	-40° C TO +80° C		

DESCRIPTION	CONSTRUCTIONAL DETAILS
INNER CONDUCTORS	TWO CONDUCTORS, EACH 7 STRANDS OF AWG SIZE 38 TINNED COPPER WIRE. NOM DIA .012
DIELECTRICS	TWO EACH POLYETHYLENE PER L-P-390C, TYPE II, C1.H, 1 EA GR.3, NATURAL, 1 EA GR.2, BLUE. .043 ± .002 DIA TYP
FILLERS	TWO EACH POLYETHYLENE PER L-P-390C, TYPE II C1.L GR.3 .028 DIA NOM
CABLE CORE	.085 ± .003 OD DIELECTRICS AND FILLERS TO HAVE A RIGHT HAND OR LEFT HAND LAY, 8 TWISTS PER FOOT. A NYLON-THREAD WRAP SHALL THEN BE APPLIED WITH SUFFICIENT COVERAGE TO MAINTAIN THE POSITION OF THE COMPONENTS.
SHIELD	SINGLE BRAID, AWG SIZE 36 TINNED COPPER WIRE SHIELD COVERAGE 93%. .105 O.D.
JACKET	BLUE (PER EIA-359-A, MUNSELL COLOR CHART, SYMBOL CENTROID) POLYVINYLCHLORIDE .150 ± .005 O.D.

TSI	DWN	DAR	10-17-00	MATERIAL	CODE IDENT	DRAWING NO.	REV
	CHK	<i>D. Curran</i>	11-24-04				
	ENG	<i>R. J. ...</i>	11-24-04				
	APPR	<i>T. Cla...</i>	11-24-04				
	SCALE	DATE	5-15-79	SHEET			

DATE 11/24/04

M. Sch...

APPR

DWN DAR

EO 13677

REV J