

This document was generated on 05/25/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0754921044

Status: Active

Overview: gbx backplane connector system

Description: 1.85mm by 1.85mm (.073 by .073") Pitch 2-Pair GbX® Backplane Connector System,

Power Module, 4 Circuits, 1.27µm (50µ") Gold (Au)

Documents:

<u>Drawing (PDF)</u>
<u>RoHS Certificate of Compliance (PDF)</u>

Product Specification PS-75221-999 (PDF)

Agency Certification

UL E29179

General

Product Family Backplane Connectors

Series 75492
Application Backplane

Application Tooling Documents http://www.molex.com/pdm_docs/ats/

TM-622022099.pdf">Tooling Manual
Blade Length A 4.50mm, B 4.50mm

Component Type Power Header

Overview gbx backplane connector system

Product Name GbX@ Style N/A

Physical

Comments

Circuits (Loaded) 4
Circuits (maximum) 4

Circuits Detail Rows A & B
Color - Resin Gray (Dark)
Durability (mating cycles max) 200

First Mate / Last Break

Flammability

Guide to Mating Part

Keying to Mating Part

None

Material - Metal High Performance Alloy (HPA)


Material - Plating Mating Gold
Material - Plating Termination Tin-Lead

Material - Resin High Temperature Thermoplastic

Number of Columns N/A 2 **Number of Pairs** Number of Rows Orientation Vertical PC Tail Length (in) 0.090 In PC Tail Length (mm) 2.28 mm **PCB** Locator Yes **PCB** Retention Yes PCB Thickness Recommended (in) 0.063 In PCB Thickness Recommended (mm) 1.60 mm Packaging Type Tube

Packaging Type
Pitch - Mating Interface (in)
Pitch - Mating Interface (mm)
Pitch - Term. Interface (in)
Pitch - Term. Interface (mm)
Pitch - Term. Interface (mm)
Plating min: Mating (µin)
Plating min: Mating (µm)

Tube
0.730 In
0.730 In
0.102 In
0.102 In
1.25



China RoHS

EU RoHS

RoHS Compliant by Exemption REACH SVHC

Contains SVHC: No Halogen-Free

Status

Halogen-Free

Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
For a multiple part number RoHS Certificate of Compliance, click here

Please visit the <u>Contact Us</u> section for any non-product compliance questions.

Search Parts in this Series

75492 Series

Mates With

75292 GbX® Daughtercard

Application Tooling \mid FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Description Product #
GbX® Shield 0622022100
Removal Tool

GbX® 2 Pair 1-Up 0622022480

Power Module

 $\begin{array}{lll} \mbox{Plating min: Termination (μin)} & 30 \\ \mbox{Plating min: Termination (μm)} & 0.75 \\ \mbox{Polarized to PCB} & Yes \\ \mbox{Stackable} & No \\ \mbox{Surface Mount Compatible (SMC)} & Yes \\ \mbox{Temperature Range - Operating} & 105^{\circ}\mbox{C} \\ \end{array}$

Termination Interface: Style Through Hole - Compliant Pin

Electrical

Current - Maximum per Contact 6A
Data Rate 8.0 Gbps
Shielded No

Voltage - Maximum 120V AC (RMS)/DC

Material Info

Reference - Drawing Numbers

Packaging Specification PK-70873-578
Product Specification PS-75221-999
Sales Drawing SD-75492-001

GbX is a registered trademark of Amphenol Corporation.

This document was generated on 05/25/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

