


	1	2	3	4	5	6	7	8
Table 1:				REV.	ECN NO.	DATE	SIGN	DESCRIPTION
				A	Initial Release	2017-05-16	Fisher Wang	Rev. 01 to A
F	P/N.	connector	Cable	White Print				
	SSL12-J2LJ0-0XXFXX	White	White	Without				
	SSL12-J2LJ0-0XXHXX	Black	Black	With				
E								
D								
C								
B								
A	UNIT:mm ±0.5							
	TITLE				ITEM NO			
	SSL1.2 2P,JACK CONN+FLAT CABLE				DRAWN BY			
				Fisher Wang				
				DATE				
				2017-05-16				
				CHECKED BY				
				Victor Hung				
				DATE				
				2017-05-16				
				APPROVED BY				
				Kevin Hu				
				DATE				
				2017-05-16				
				CUSTOMER				
				ALTW				
				FMM10702-01-02A1				



- Notes:
- * $\varnothing$ Important Dimension To Check.
 - * Current Rating:5A
 - * Voltage Rating:300V DC/AC
 - * Waterproof Rate:IP68(mating)
1M Depth Of Water In 24 Hours.
 - * Housing: Thermoplastic, UL94V-0,
color see table 1.
 - * Terminal:Copper Alloy, Gold Plated.
 - * Seals: Silicone, Gray.
 - * Cable:UL21996, Flat Cable, UV Resistance,
color see table 1.
 - * Temperature Range: -40~+105℃

Amphenol LTW
安費諾亮泰企業股份有限公司

Cable Length Tolerance:

01M: ±40mm
02M~06M: ±60mm
06M~10M: ±100mm
11M~30M: ±200mm
31M~99M: ±500mm

XX: 1M~99M
01: 1M
02: 2M
:
99: 99M

F: White
H: Black

18: 18AWG(W=5.3,H=3.4)
20: 20AWG(W=5.0,H=3.2)

2	Red 紅
1	Brown 棕
Conn	Wire Color
Pin Out	