

	1	2	3	4	5	6	7	8
Table 1:				REV.	ECN NO.	DATE	SIGN	DESCRIPTION
				A	Initial Release	2017-05-16	Fisher Wang	Rev. 01 to A
F	P/N.		connector	Cable	White Print			
	SSL12-J2LJ0-0XXFXX		White	White	Without			
	SSL12-J2LJ0-0XXHXX		Black	Black	With			
E								
D								
C								
B								
	SSL12-J2LJ0-0XX X XX XX: 1M~99M 01: 1M 02: 2M : 99: 99M F: White H: Black 18: 18AWG(W=5.3,H=3.4) 20: 20AWG(W=5.0,H=3.2) Cable Length Tolerance: 01M: ±40mm 02M~06M: ±60mm 06M~10M: ±100mm 11M~30M: ±200mm 31M~99M: ±500mm Notes: * Important Dimension To Check. * Current Rating:5A * Voltage Rating:300V DC/AC * Waterproof Rate:IP68(mating) 1M Depth Of Water In 24 Hours. * Housing: Thermoplastic, UL94V-0, color see table 1. * Terminal:Copper Alloy, Gold Plated. * Seals: Silicone, Gray. * Cable:UL21996, Flat Cable, UV Resistance, color see table 1. * Temperature Range: -40~+105℃							
A								
	UNIT:mm ±0.5 TITLE SSL1.2 2P,JACK CONN+FLAT CABLE SCALE Free SIZE A4 SHEET 1 OF 1 REV. A WC-REV. A.2 Inspection item Amphenol LTW 安費諾亮泰企業股份有限公司 ITEM NO DWG NO CUSTOMER DRAWN BY CHECKED BY APPROVED BY DATE DATE DATE							

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.