

## Device connector, front mounting - CA-09S1NC22S00 - 1619912

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Device connector for front wall, straight, shielded: Yes, SPEEDCON locking, M23, Number of positions: 8+1, Type of contact: Socket, Solder-in connection, Flat gasket, 4x Ø3.2

The figure shows the 6-pos. product version

### Product Features



### Key commercial data

|                      |          |
|----------------------|----------|
| Packing unit         | 1 pc     |
| Custom tariff number | 85366990 |
| Country of origin    | Germany  |

### Technical data

#### Temperature range

|                                 |                   |
|---------------------------------|-------------------|
| Ambient temperature (operation) | -40 °C ... 125 °C |
|---------------------------------|-------------------|

#### Data of the insulating body

|                                                    |                      |
|----------------------------------------------------|----------------------|
| Insulator material                                 | PBT                  |
| Contact material                                   | CuZn                 |
| Contact surface material                           | Ni/Au                |
| Direction of rotation of contact chamber numbering | Standard             |
| Coding                                             | N                    |
| Contact connection method                          | Solder-in connection |
| Type of contacts                                   | Socket               |
| Number of positions                                | 9                    |
| Contact diameter of power contacts                 | 2 mm                 |
| Nominal current per power contact at 25°C          | 20 A                 |
| Nominal voltage, power contact                     | 300 V                |

## Device connector, front mounting - CA-09S1NC22S00 - 1619912

### Technical data

#### Data of the insulating body

|                                            |       |
|--------------------------------------------|-------|
| Contact diameter of signal contacts        | 1 mm  |
| Nominal current per signal contact at 25°C | 8 A   |
| Nominal voltage, signal contact            | 300 V |
| Surge voltage category                     | II    |
| Pollution degree                           | 3     |

#### Housing data

|                                        |                                                                      |
|----------------------------------------|----------------------------------------------------------------------|
| Housing material                       | Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn) |
| Type of locking                        | SPEEDCON locking                                                     |
| Degree of protection (when plugged in) | IP67                                                                 |
| Thread type                            | M23                                                                  |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 272607xx |
| eCl@ss 4.1 | 27260701 |
| eCl@ss 5.0 | 27143424 |
| eCl@ss 5.1 | 27143424 |
| eCl@ss 6.0 | 27143424 |
| eCl@ss 7.0 | 27440209 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC001121 |
| ETIM 4.0 | EC002635 |
| ETIM 5.0 | EC002635 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 43172015 |
| UNSPSC 7.0901 | 43201404 |
| UNSPSC 11     | 43172015 |
| UNSPSC 12.01  | 43201404 |
| UNSPSC 13.2   | 43201404 |

### Approvals

#### Approvals

## Device connector, front mounting - CA-09S1NC22S00 - 1619912

### Approvals

#### Approvals

UL Recognized / cUL Recognized / cULus Recognized

#### Ex Approvals

#### Approvals submitted

### Approval details

|                                                                                                 |       |
|-------------------------------------------------------------------------------------------------|-------|
| UL Recognized  |       |
|                                                                                                 |       |
| mm²/AWG/kcmil                                                                                   | 18    |
| Nominal current I <sub>N</sub>                                                                  | 8 A   |
| Nominal voltage U <sub>N</sub>                                                                  | 300 V |


|                                                                                                    |       |
|----------------------------------------------------------------------------------------------------|-------|
| cUL Recognized  |       |
|                                                                                                    |       |
| mm²/AWG/kcmil                                                                                      | 18    |
| Nominal current I <sub>N</sub>                                                                     | 6 A   |
| Nominal voltage U <sub>N</sub>                                                                     | 300 V |

|                                                                                                      |  |
|------------------------------------------------------------------------------------------------------|--|
| cULus Recognized  |  |
|------------------------------------------------------------------------------------------------------|--|


### Drawings

## Device connector, front mounting - CA-09S1NC22S00 - 1619912


Schematic diagram




Dimensional drawing



Dimensional drawing



Drilling diagram



8+1-pos.

Installation dimensions