







REV.	ECN NO.	DATE	SIGN	DESCRIPTION
B	LEN-050040	2009/11/13	Li Xiu Zhi	Change View



Note:

- * $\varnothing$ Important Dimension.
- * Waterproof Rate : IP66
- * Housing: Nylon+GF, Black
- * Female Pin: Copper Alloy, Gold Plated
- * Seals: EPDM, Black
- * Clamping Ring: Nylon, Black
- * Sealing Nut: Nylon, Black
- * Seals B1 for Cable OD: $\varnothing 4.5\text{mm} \sim \varnothing 6.5\text{mm}$
(防水墊圈B1線徑: $\varnothing 4.5\text{mm} \sim \varnothing 6.5\text{mm}$)
- * Seals B2 for Cable OD: $\varnothing 3.5\text{mm} \sim \varnothing 5.3\text{mm}$
(防水墊圈B2線徑: $\varnothing 3.5\text{mm} \sim \varnothing 5.3\text{mm}$)
- * One Set Unassembled in One PE Bag
(每一組未組裝, 放置於一個PE袋, 並封口)
- * PE Bag: 90mm*85mm



UNIT: mm		TOLERANCE		TITLE		ITEM NO.		DRAWN BY		DATE	
.X ±0.25		.XX ±0.1		Standard, Assy Lock 3Pin M Conn F Pin		BD-03BMFA-LL6001		SamChang		2012-03-15	
.XXX ±0.05		ANGLES ±1°		SCALE 1:1		DWG NO. BD-03BMFA-LL6001		CHECKED BY Jeffrey		DATE 2012-03-26	
REV. B		WC-REV. A.2		SHEET 1 OF 1		CUSTOMER ALTW		APPROVED BY Kevin		DATE 2012-03-26	

Amphenol LTW
安費諾亮泰企業股份有限公司