



**N-channel 450 V - 3.3  $\Omega$  typ., 0.6 A Zener-protected,  
SuperMESH3™ Power MOSFET in a SOT-223 package**

Datasheet - production data



**Figure 1. Internal schematic diagram**



## Features

| Order code | $V_{DSS}$ | $R_{DS(on)} \text{ max}$ | $I_D$ | $P_w$ |
|------------|-----------|--------------------------|-------|-------|
| STN3N45K3  | 450 V     | < 4 $\Omega$             | 0.6 A | 3 W   |

- 100% avalanche tested
- Extremely high dv/dt capability
- Gate charge minimized
- Very low intrinsic capacitance
- Improved diode reverse recovery characteristics
- Zener-protected

## Applications

- Switching applications

## Description

This SuperMESH3™ Power MOSFET is the result of improvements applied to STMicroelectronics' SuperMESH™ technology, combined with a new optimized vertical structure. This device boasts an extremely low on-resistance, superior dynamic performance and high avalanche capability, rendering it suitable for the most demanding applications.

**Table 1. Device summary**

| Order code | Marking | Package | Packaging     |
|------------|---------|---------|---------------|
| STN3N45K3  | 3N45K3  | SOT-223 | Tape and reel |

## Contents

|          |                                     |           |
|----------|-------------------------------------|-----------|
| <b>1</b> | <b>Electrical ratings</b>           | <b>3</b>  |
| <b>2</b> | <b>Electrical characteristics</b>   | <b>4</b>  |
| 2.1      | Electrical characteristics (curves) | 6         |
| <b>3</b> | <b>Test circuits</b>                | <b>9</b>  |
| <b>4</b> | <b>Package mechanical data</b>      | <b>10</b> |
| <b>5</b> | <b>Packaging mechanical data</b>    | <b>12</b> |
| <b>6</b> | <b>Revision history</b>             | <b>14</b> |

# 1 Electrical ratings

Table 2. Absolute maximum ratings

| Symbol         | Parameter                                                                                   | Value      | Unit |
|----------------|---------------------------------------------------------------------------------------------|------------|------|
| $V_{DS}$       | Drain-source voltage ( $V_{GS} = 0$ )                                                       | 450        | V    |
| $V_{GS}$       | Gate- source voltage                                                                        | $\pm 30$   | V    |
| $I_D$          | Drain current (continuous) at $T_{amb} = 25$ °C                                             | 0.6        | A    |
| $I_{DM}^{(1)}$ | Drain current (pulsed)                                                                      | 2.4        | A    |
| $P_{TOT}$      | Total dissipation at $T_{amb} = 25$ °C                                                      | 3          | W    |
| $I_{AR}^{(2)}$ | Avalanche current, repetitive or not-repetitive                                             | 0.6        | A    |
| $E_{AS}^{(3)}$ | Single pulse avalanche energy<br>(starting $T_j = 25$ °C, $I_D = I_{AR}$ , $V_{DD} = 50$ V) | 45         | mJ   |
| $dv/dt^{(4)}$  | Peak diode recovery voltage slope                                                           | 12         | V/ns |
| $V_{esd(g-s)}$ | G-S ESD (HBM C = 100 pF, R = 1.5 kΩ)                                                        | 1000       | V    |
| $T_{stg}$      | Storage temperature                                                                         | -55 to 150 | °C   |
| $T_j$          | Max. operating junction temperature                                                         | 150        | °C   |

1. Pulse width limited by safe operating area.
2. Pulse width limited by  $T_j$  max.
3. Starting  $T_j = 25$  °C,  $I_D = I_{AR}$ ,  $V_{DD} = 50$  V.
4.  $I_{SD} \leq 0.6$  A,  $di/dt \leq 400$  A/μs,  $V_{DS}$  peak  $\leq V_{(BR)DSS}$ ,  $V_{DD} = 80\%$   $V_{(BR)DSS}$ .

Table 3. Thermal data

| Symbol            | Parameter                           | Value | Unit |
|-------------------|-------------------------------------|-------|------|
| $R_{thj-a}^{(1)}$ | Thermal resistance junction-ambient | 37.8  | °C/W |

1. When mounted on FR-4 board of 1 inch<sup>2</sup>, 2oz Cu, t < 30 sec

## 2 Electrical characteristics

( $T_C = 25^\circ\text{C}$  unless otherwise specified)

Table 4. On /off states

| Symbol                      | Parameter                                        | Test conditions                                                                  | Min. | Typ. | Max.     | Unit                           |
|-----------------------------|--------------------------------------------------|----------------------------------------------------------------------------------|------|------|----------|--------------------------------|
| $V_{(\text{BR})\text{DSS}}$ | Drain-source breakdown voltage                   | $I_D = 1 \text{ mA}$ , $V_{GS} = 0$                                              | 450  |      |          | V                              |
| $I_{\text{DSS}}$            | Zero gate voltage drain current ( $V_{GS} = 0$ ) | $V_{DS} = 450 \text{ V}$<br>$V_{DS} = 450 \text{ V}$ , $T_C = 125^\circ\text{C}$ |      |      | 1<br>50  | $\mu\text{A}$<br>$\mu\text{A}$ |
| $I_{\text{GSS}}$            | Gate-body leakage current ( $V_{DS} = 0$ )       | $V_{GS} = \pm 20 \text{ V}$                                                      |      |      | $\pm 10$ | $\mu\text{A}$                  |
| $V_{GS(\text{th})}$         | Gate threshold voltage                           | $V_{DS} = V_{GS}$ , $I_D = 50 \mu\text{A}$                                       | 3    | 3.75 | 4.5      | V                              |
| $R_{\text{DS}(\text{on})}$  | Static drain-source on resistance                | $V_{GS} = 10 \text{ V}$ , $I_D = 0.6 \text{ A}$                                  |      | 3.3  | 4        | $\Omega$                       |

Table 5. Dynamic

| Symbol                   | Parameter                             | Test conditions                                                                                  | Min. | Typ. | Max. | Unit     |
|--------------------------|---------------------------------------|--------------------------------------------------------------------------------------------------|------|------|------|----------|
| $C_{\text{iss}}$         | Input capacitance                     | $V_{DS} = 50 \text{ V}$ , $f = 1 \text{ MHz}$ , $V_{GS} = 0$                                     | -    | 164  | -    | pF       |
| $C_{\text{oss}}$         | Output capacitance                    |                                                                                                  | -    | 17   | -    | pF       |
| $C_{\text{rss}}$         | Reverse transfer capacitance          |                                                                                                  | -    | 3    | -    | pF       |
| $C_{o(\text{tr})}^{(1)}$ | Equivalent capacitance time related   | $V_{DS} = 0 \text{ to } 360 \text{ V}$ , $V_{GS} = 0$                                            | -    | 13   | -    | pF       |
| $C_{o(\text{er})}^{(2)}$ | Equivalent capacitance energy related |                                                                                                  | -    | 18   | -    | pF       |
| $R_G$                    | Intrinsic gate resistance             | $f = 1 \text{ MHz}$ open drain                                                                   | -    | 8    | -    | $\Omega$ |
| $Q_g$                    | Total gate charge                     | $V_{DD} = 360 \text{ V}$ , $I_D = 1.8 \text{ A}$ ,<br>$V_{GS} = 10 \text{ V}$<br>(see Figure 16) | -    | 9.5  | -    | nC       |
| $Q_{\text{gs}}$          | Gate-source charge                    |                                                                                                  | -    | 2    | -    | nC       |
| $Q_{\text{gd}}$          | Gate-drain charge                     |                                                                                                  | -    | 6    | -    | nC       |

1.  $C_{\text{oss eq}}$  time related is defined as a constant equivalent capacitance giving the same charging time as  $C_{\text{oss}}$  when  $V_{DS}$  increases from 0 to 80%  $V_{DSS}$
2.  $C_{\text{oss eq}}$  energy related is defined as a constant equivalent capacitance giving the same charging time as  $C_{\text{oss}}$  when  $V_{DS}$  increases from 0 to 80%  $V_{DSS}$

Table 6. Switching times

| Symbol       | Parameter           | Test conditions                                                                                                                        | Min. | Typ. | Max | Unit |
|--------------|---------------------|----------------------------------------------------------------------------------------------------------------------------------------|------|------|-----|------|
| $t_{d(on)}$  | Turn-on delay time  | $V_{DD} = 225 \text{ V}$ , $I_D = 0.9 \text{ A}$ ,<br>$R_G = 4.7 \Omega$ , $V_{GS} = 10 \text{ V}$<br>(see <a href="#">Figure 15</a> ) | -    | 6.5  | -   | ns   |
| $t_r$        | Rise time           |                                                                                                                                        | -    | 5.4  | -   | ns   |
| $t_{d(off)}$ | Turn-off-delay time |                                                                                                                                        | -    | 17   | -   | ns   |
| $t_f$        | Fall time           |                                                                                                                                        | -    | 22   | -   | ns   |

Table 7. Source drain diode

| Symbol          | Parameter                     | Test conditions                                                                                                                                                    | Min. | Typ. | Max. | Unit |
|-----------------|-------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|------|------|------|
| $I_{SD}$        | Source-drain current          |                                                                                                                                                                    | -    |      | 0.6  | A    |
| $I_{SDM}^{(1)}$ | Source-drain current (pulsed) |                                                                                                                                                                    | -    |      | 2.4  | A    |
| $V_{SD}^{(2)}$  | Forward on voltage            | $I_{SD} = 0.6 \text{ A}$ , $V_{GS} = 0$                                                                                                                            | -    |      | 1.5  | V    |
| $t_{rr}$        | Reverse recovery time         | $I_{SD} = 1.8 \text{ A}$ , $di/dt = 100 \text{ A}/\mu\text{s}$<br>$V_{DD} = 60 \text{ V}$ (see <a href="#">Figure 20</a> )                                         | -    | 175  |      | ns   |
| $Q_{rr}$        | Reverse recovery charge       |                                                                                                                                                                    | -    | 550  |      | nC   |
| $I_{RRM}$       | Reverse recovery current      |                                                                                                                                                                    | -    | 6    |      | A    |
| $t_{rr}$        | Reverse recovery time         | $I_{SD} = 1.8 \text{ A}$ , $di/dt = 100 \text{ A}/\mu\text{s}$<br>$V_{DD} = 60 \text{ V}$ , $T_j = 150 \text{ }^\circ\text{C}$<br>(see <a href="#">Figure 20</a> ) | -    | 185  |      | ns   |
| $Q_{rr}$        | Reverse recovery charge       |                                                                                                                                                                    | -    | 600  |      | nC   |
| $I_{RRM}$       | Reverse recovery current      |                                                                                                                                                                    | -    | 6.5  |      | A    |

1. Pulse width limited by safe operating area.
2. Pulsed: Pulse duration = 300  $\mu\text{s}$ , duty cycle 1.5%.

Table 8. Gate-source Zener diode

| Symbol        | Parameter                     | Test conditions                         | Min | Typ | Max | Unit |
|---------------|-------------------------------|-----------------------------------------|-----|-----|-----|------|
| $V_{(BR)GSO}$ | Gate-source breakdown voltage | $I_{GS} = \pm 1 \text{ mA}$ , $I_D = 0$ | 30  | -   | -   | V    |

The built-in back-to-back Zener diodes have been specifically designed to enhance not only the device's ESD capability, but also to make them capable of safely absorbing any voltage transients that may occasionally be applied from gate to source. In this respect, the Zener voltage is appropriate to achieve efficient and cost-effective protection of device integrity. The integrated Zener diodes thus eliminate the need for external components.

## 2.1 Electrical characteristics (curves)

Figure 2. Safe operating area




Figure 3. Thermal impedance




Figure 4. Output characteristics




Figure 5. Transfer characteristics




Figure 6. Gate charge vs gate-source voltage




Figure 7. Static drain-source on resistance




Figure 8. Capacitance variations




Figure 9. Output capacitance stored energy




Figure 10. Normalized gate threshold voltage vs temperature




Figure 11. Normalized on-resistance vs temperature







Figure 12. Source-drain diode forward characteristics


Figure 13. Normalized  $B_{VDSS}$  vs temperature

**Figure 14. Maximum avalanche energy vs starting  $T_j$**




### 3 Test circuits


**Figure 15. Switching times test circuit for resistive load**




**Figure 16. Gate charge test circuit**




**Figure 17. Test circuit for inductive load switching and diode recovery times**




**Figure 18. Unclamped inductive load test circuit**



**Figure 19. Unclamped inductive waveform**



**Figure 20. Switching time waveform**




## 4 Package mechanical data

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: [www.st.com](http://www.st.com).  
ECOPACK® is an ST trademark.

Table 9. SOT-223 mechanical data

| Dim. | mm   |      |      |
|------|------|------|------|
|      | Min. | Typ. | Max. |
| A    |      |      | 1.80 |
| A1   | 0.02 |      | 0.1  |
| B    | 0.60 | 0.70 | 0.85 |
| B1   | 2.90 | 3.00 | 3.15 |
| c    | 0.24 | 0.26 | 0.35 |
| D    | 6.30 | 6.50 | 6.70 |
| e    |      | 2.30 |      |
| e1   |      | 4.60 |      |
| E    | 3.30 | 3.50 | 3.70 |
| H    | 6.70 | 7.00 | 7.30 |
| V    |      |      | 10°  |

Figure 21. SOT-223 mechanical data drawing



## 5 Packaging mechanical data

Table 10. SOT-223 tape and reel mechanical data

| Tape      |      |      |      | Reel              |      |      |
|-----------|------|------|------|-------------------|------|------|
| Dim.      | mm   |      |      | Dim.              | mm   |      |
|           | Min. | Typ. | Max. |                   | Min. | Max. |
| A0        | 6.75 | 6.85 | 6.95 | A                 |      | 180  |
| B0        | 7.30 | 7.40 | 7.50 | N                 | 60   |      |
| K0        | 1.80 | 1.90 | 2.00 | W1                |      | 12.4 |
| F         | 5.40 | 5.50 | 5.60 | W2                |      | 18.4 |
| E         | 1.65 | 1.75 | 1.85 | W3                | 11.9 | 15.4 |
| W         | 11.7 | 12   | 12.3 |                   |      |      |
| P2        | 1.90 | 2    | 2.10 | Base quantity pcs |      | 1000 |
| P0        | 3.90 | 4    | 4.10 | Bulk quantity pcs |      | 1000 |
| P1        | 7.90 | 8    | 8.10 |                   |      |      |
| T         | 0.25 | 0.30 | 0.35 |                   |      |      |
| D $\phi$  | 1.50 | 1.55 | 1.60 |                   |      |      |
| D1 $\phi$ | 1.50 | 1.60 | 1.70 |                   |      |      |

Figure 22. Tape for SOT-223 (dimensions are in mm)





Figure 23. Reel for TO-223 (dimensions are in mm)



## 6 Revision history

Table 11. Document revision history

| Date        | Revision | Changes                                                                   |
|-------------|----------|---------------------------------------------------------------------------|
| 25-Jun-2013 | 1        | First release. Part number previously included in datasheet<br>DocID17206 |

**Please Read Carefully:**

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

**UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.**

**ST PRODUCTS ARE NOT AUTHORIZED FOR USE IN WEAPONS. NOR ARE ST PRODUCTS DESIGNED OR AUTHORIZED FOR USE IN: (A) SAFETY CRITICAL APPLICATIONS SUCH AS LIFE SUPPORTING, ACTIVE IMPLANTED DEVICES OR SYSTEMS WITH PRODUCT FUNCTIONAL SAFETY REQUIREMENTS; (B) AERONAUTIC APPLICATIONS; (C) AUTOMOTIVE APPLICATIONS OR ENVIRONMENTS, AND/OR (D) AEROSPACE APPLICATIONS OR ENVIRONMENTS. WHERE ST PRODUCTS ARE NOT DESIGNED FOR SUCH USE, THE PURCHASER SHALL USE PRODUCTS AT PURCHASER'S SOLE RISK, EVEN IF ST HAS BEEN INFORMED IN WRITING OF SUCH USAGE, UNLESS A PRODUCT IS EXPRESSLY DESIGNATED BY ST AS BEING INTENDED FOR "AUTOMOTIVE, AUTOMOTIVE SAFETY OR MEDICAL" INDUSTRY DOMAINS ACCORDING TO ST PRODUCT DESIGN SPECIFICATIONS. PRODUCTS FORMALLY ESCC, QML OR JAN QUALIFIED ARE DEEMED SUITABLE FOR USE IN AEROSPACE BY THE CORRESPONDING GOVERNMENTAL AGENCY.**

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2013 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan -  
Malaysia - Malta - Morocco - Philippines - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

[www.st.com](http://www.st.com)

