9007C54B





Main

Range of product	9007
Series name	Heavy duty
Head type	Rotary head
Type of operator	Spring return lever arm (standard pre-travel) (to be ordered separately
Switch actuation	CW
Cable entry	NPT conduit entry, cable outer diameter: 0.5 in
Contacts type and composition	1 NO/1 NC
Contact operation	Snap action

Complementary

-		
Body material	Zinc alloy	
Switch function	SPDT-DB	
Contact form	Form Z	
Contacts material	Silver alloy (Ag/Ni)	_
Minimum torque for tripping	4 lbf.in	
[le] rated operational current	10 A, Q600 10 A, A600	
[Ui] rated insulation voltage	<= 600 V	
Local signalling	Without	
Product certifications	CE CSA UL listed	
Provided equipment	Receptacle	

Environment

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1150 - Schneider Electric declaration of conformity	Compliant - since 1150 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and	Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and
Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.	eDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period	18 months