# Austin MiniLynx™: SMT Non-Isolated DC-DC Power Modules

2.4Vdc -5.5Vdc input; 0.75Vdc to 3.63Vdc output; 3A Output Current

### **RoHS Compliant**



### **Applications**

- Distributed power architectures
- Intermediate bus voltage applications
- Telecommunications equipment
- Servers and storage applications
- Networking equipment
- Enterprise Networks
- Latest generation IC's (DSP, FPGA, ASIC) and Microprocessor powered applications

#### **Features**

- Compliant to RoHS EU Directive 2011/65/EU (-Z versions)
- Compliant to RoHS EU Directive 2011/65/EU under exemption 7b (Lead solder exemption). Exemption 7b will expire after June 1, 2016 at which time this product will no longer be RoHS compliant (non-Z versions)
- Delivers up to 3A output current
- High efficiency 94% at 3.3V full load ( $V_{IN} = 5.0V$ )
- Small size and low profile:
   20.3 mm x 11.4 mm x 7.27 mm
   (0.80 in x 0.45 in x 0.286 in)
- Low output ripple and noise
- High Reliability:
   Calculated MTBF = 11.9M hours at 25°C Full-load
- Constant switching frequency (300 kHz)
- Output voltage programmable from 0.75 Vdc to 3.63Vdc via external resistor
- Line Regulation: 0.4% (typical)
- Load Regulation: 0.4% (typical)
- Temperature Regulation: 0.4 % (typical)
- Remote On/Off
- Output overcurrent protection (non-latching)
- Wide operating temperature range (-40°C to 85°C)
- UL\* 60950-1Recognized, CSA<sup>†</sup> C22.2 No. 60950-1-03
   Certified, and VDE<sup>‡</sup> 0805:2001-12 (EN60950-1) Licensed
- ISO\*\* 9001 and ISO 14001 certified manufacturing facilities

### **Description**

Austin MiniLynx<sup>TM</sup> SMT (surface mount technology) power modules are non-isolated dc-dc converters that can deliver up to 3A of output current with full load efficiency of 94.0% at 3.3V output. These modules provide a precisely regulated output voltage programmable via an external resistor from 0.75Vdc to 3.63Vdc over a wide range of input voltage ( $V_{IN} = 2.4 - 5.5$ Vdc). Their open-frame construction and small footprint enable designers to develop cost- and space-efficient solutions.

- \* UL is a registered trademark of Underwriters Laboratories, Inc.
- † CSA is a registered trademark of Canadian Standards Association.
- <sup>‡</sup> *VDE* is a trademark of Verband Deutscher Elektrotechniker e.V.
- \*\* ISO is a registered trademark of the International Organization of Standards

# Austin MiniLynx™: SMT Non-Isolated DC-DC Power Modules

2.4Vdc - 5.5Vdc input; 0.75Vdc to 3.63Vdc output; 3A Output Current

### **Absolute Maximum Ratings**

Stresses in excess of the absolute maximum ratings can cause permanent damage to the device. These are absolute stress ratings only, functional operation of the device is not implied at these or any other conditions in excess of those given in the operations sections of the data sheet. Exposure to absolute maximum ratings for extended periods can adversely affect the device reliability.

| Parameter                            | Device | Symbol          | Min  | Max | Unit |
|--------------------------------------|--------|-----------------|------|-----|------|
| Input Voltage                        | All    | V <sub>IN</sub> | -0.3 | 5.8 | Vdc  |
| Continuous                           |        |                 |      |     |      |
| Operating Ambient Temperature        | All    | T <sub>A</sub>  | -40  | 85  | °C   |
| (see Thermal Considerations section) |        |                 |      |     |      |
| Storage Temperature                  | All    | $T_{stg}$       | -55  | 125 | °C   |

### **Electrical Specifications**

Unless otherwise indicated, specifications apply over all operating input voltage, resistive load, and temperature conditions.

| Parameter   | Device                        | Symbol                   | Min | Тур | Max  | Unit             |
|---|-------------------------------|--------------------------|-----|-----|------|------------------|
| Operating Input Voltage   | $V_{O,set} \le V_{IN} - 0.5V$ | V <sub>IN</sub>          | 2.4 | _   | 5.5  | Vdc              |
| Maximum Input Current   | All                           | I <sub>IN,max</sub>      |     |     | 3.0  | Adc              |
| $(V_{IN}=V_{IN, min} \text{ to } V_{IN, max}, I_{O}=I_{O, max} V_{O, set}=3.3 Vdc)$   |                               |                          |     |     |      |                  |
| Input No Load Current   | $V_{O,set} = 0.75Vdc$         | I <sub>IN,No load</sub>  |     | 10  |      | mA               |
| $(V_{IN} = 5.0 \text{Vdc}, I_0 = 0, \text{module enabled})$   | V <sub>O,set</sub> = 3.3Vdc   | I <sub>IN,No</sub> load  |     | 17  |      | mA               |
| Input Stand-by Current  | All                           | I <sub>IN,stand-by</sub> |     | 0.6 |      | mA               |
| (V <sub>IN</sub> = 5.0Vdc, module disabled)   |                               |                          |     |     |      |                  |
| Inrush Transient  | All                           | l²t                      |     |     | 0.04 | A <sup>2</sup> s |
| Input Reflected Ripple Current, peak-to-peak (5Hz to 20MHz, 1µH source impedance; V <sub>IN, min</sub> to V <sub>IN, max, lo= lomax</sub> ; See Test configuration section) | All                           |                          |     | 35  |      | mAp-p            |
| Input Ripple Rejection (120Hz)  | All                           |                          |     | 30  |      | dB               |

CAUTION: This power module is not internally fused. An input line fuse must always be used.

This power module can be used in a wide variety of applications, ranging from simple standalone operation to being part of a complex power architecture. To preserve maximum flexibility, internal fusing is not included, however, to achieve maximum safety and system protection, always use an input line fuse. The safety agencies require a fast-acting fuse with a maximum rating of 6 A (see Safety Considerations section). Based on the information provided in this data sheet on inrush energy and maximum dc input current, the same type of fuse with a lower rating can be used. Refer to the fuse manufacturer's data sheet for further information.

GE

# Austin MiniLynx<sup>TM</sup>: SMT Non-Isolated DC-DC Power Modules 2.4Vdc – 5.5Vdc input; 0.75Vdc to 3.63Vdc output; 3A Output Current

## **Electrical Specifications** (continued)

| Parameter  | Device                 | Symbol              | Min    | Тур                 | Max  | Unit                  |
|--|------------------------|---------------------|--------|---------------------|------|-----------------------|
| Output Voltage Set-point   | All                    | V <sub>O, set</sub> | -2.0   | V <sub>O, set</sub> | +2.0 | % V <sub>O, set</sub> |
| (V <sub>IN=IN, min</sub> , I <sub>O</sub> =I <sub>O, max</sub> , T <sub>A</sub> =25°C)           |                        |                     |        |                     |      |                       |
| Output Voltage   | All                    | V <sub>O, set</sub> | -3%    | _                   | +3%  | % V <sub>O, set</sub> |
| (Over all operating input voltage, resistive load, and temperature conditions until end of life) |                        |                     |        |                     |      |                       |
| Adjustment Range<br>Selected by an external resistor   | All                    | Vo                  | 0.7525 |                     | 3.63 | Vdc                   |
| Output Regulation  |                        |                     |        |                     |      |                       |
| Line ( $V_{IN}=V_{IN, min}$ to $V_{IN, max}$ )   | All                    |                     | _      | 0.4                 | _    | % V <sub>O, set</sub> |
| Load (Io=Io, min to Io, max)   | All                    |                     | _      | 0.4                 | _    | % V <sub>O, set</sub> |
| Temperature ( $T_{ref}=T_{A, min}$ to $T_{A, max}$ )   | All                    |                     | _      | 0.4                 | _    | % V <sub>O, set</sub> |
| Output Ripple and Noise on nominal output  |                        |                     |        |                     |      |                       |
| ( $V_{IN}=V_{IN,nom}$ and $I_{O}=I_{O,min}$ to $I_{O,max}$                                       |                        |                     |        |                     |      |                       |
| Cout = $1\mu$ F ceramic// $10\mu$ Ftantalum capacitors)  |                        |                     |        |                     |      |                       |
| RMS (5Hz to 20MHz bandwidth)   | All                    |                     | _      | 10                  | 15   | mV <sub>rms</sub>     |
| Peak-to-Peak (5Hz to 20MHz bandwidth)  | All                    |                     | _      | 25                  | 50   | mV <sub>pk-pk</sub>   |
| External Capacitance   |                        |                     |        |                     |      |                       |
| $ESR \ge 1  m\Omega$   | All                    | C <sub>O, max</sub> | _      | _                   | 1000 | μF                    |
| ESR ≥ 10 mΩ  | All                    | C <sub>O, max</sub> | _      |                     | 5000 | μF                    |
| Output Current   | All                    | l <sub>o</sub>      | 0      |                     | 3    | Adc                   |
| Output Current Limit Inception (Hiccup Mode )  | All                    | I <sub>O, lim</sub> | _      | 220                 | _    | % I <sub>o</sub>      |
| $(V_O=90\% \text{ of } V_{O,set})$   |                        |                     |        |                     |      |                       |
| Output Short-Circuit Current   | All                    | I <sub>O, s/c</sub> | _      | 2                   | _    | Adc                   |
| (Vo≤250mV) ( Hiccup Mode )   |                        |                     |        |                     |      |                       |
| Efficiency   | V <sub>0,set</sub> =   | η                   |        | 81.5                |      | %                     |
| $V_{IN} = V_{IN, nom}$ , $T_A = 25$ °C   | $V_{O, set} = 1.2 Vdc$ | η                   |        | 87.0                |      | %                     |
| $I_0 = I_{0, max}, V_0 = V_{0, set}$   | $V_{O,set} = 1.5Vdc$   | η                   |        | 89.0                |      | %                     |
|  | $V_{O,set} = 1.8Vdc$   | η                   |        | 90.0                |      | %                     |
|  | $V_{O,set} = 2.5Vdc$   | η                   |        | 93.0                |      | %                     |
|  | $V_{O,set} = 3.3Vdc$   | η                   |        | 94.0                |      | %                     |
| Switching Frequency  | All                    | f <sub>sw</sub>     | _      | 300                 | _    | kHz                   |
| Dynamic Load Response  |                        |                     |        |                     |      |                       |
| $(dIo/dt=2.5A/\mu s; V_{IN} = V_{IN, nom}; T_A=25$ °C)   | All                    | $V_{pk}$            | _      | 250                 | _    | mV                    |
| Load Change from Io= 50% to 100% of Io,max; $1\mu F$ ceramic// $10~\mu F$ tantalum               |                        |                     |        |                     |      |                       |
| Peak Deviation   |                        |                     |        |                     |      |                       |
| Settling Time (Vo<10% peak deviation)  | All                    | ts                  | _      | 50                  | _    | μS                    |
| $(dIo/dt=2.5A/\mu s; V_{IN} = V_{IN, nom}; T_A=25$ °C)   | All                    | $V_{pk}$            | _      | 250                 | _    | mV                    |
| Load Change from Io= 100% to 50%of Io,max: $1\mu\text{F}$ ceramic// $10~\mu\text{F}$ tantalum    |                        |                     |        |                     |      |                       |
| Peak Deviation   |                        |                     |        |                     |      |                       |
| Settling Time (Vo<10% peak deviation)  | All                    | ts                  | _      | 50                  | _    | μs                    |

GE

# Austin MiniLynx<sup>TM</sup>: SMT Non-Isolated DC-DC Power Modules 2.4Vdc – 5.5Vdc input; 0.75Vdc to 3.63Vdc output; 3A Output Current

## **Electrical Specifications** (continued)

| Parameter   | Device | Symbol          | Min | Тур | Max | Unit |
|---|--------|-----------------|-----|-----|-----|------|
| Dynamic Load Response   |        |                 |     |     |     |      |
| (dIo/dt=2.5A/ $\mu$ s; V V <sub>IN</sub> = V <sub>IN, nom</sub> ; T <sub>A</sub> =25°C)<br>Load Change from Io= 50% to 100% of Io,max;<br>Co = 2x150 $\mu$ F polymer capacitors<br>Peak Deviation | All    | V <sub>pk</sub> | _   | 60  | _   | mV   |
| Settling Time (Vo<10% peak deviation)   | All    | ts              | _   | 100 | _   | μς   |
| (dlo/dt=2.5A/ $\mu$ s; V <sub>IN</sub> = V <sub>IN,nom</sub> ; T <sub>A</sub> =25°C)<br>Load Change from lo= 100% to 50%of lo,max:<br>Co = 2x150 $\mu$ F polymer capacitors                       | All    | $V_{pk}$        | _   | 60  | _   | mV   |
| Peak Deviation  |        |                 |     |     |     |      |
| Settling Time (Vo<10% peak deviation)   | All    | ts              | _   | 100 | _   | μS   |

### **General Specifications**

| Parameter  | Min        | Тур       | Max | Unit    |
|--|------------|-----------|-----|---------|
| Calculated MTBF (I <sub>0</sub> =I <sub>0, max</sub> , T <sub>A</sub> =25°C) | 11,965,153 |           |     | Hours   |
| Weight   | _          | 2.8 (0.1) | _   | g (oz.) |

# Austin MiniLynx™: SMT Non-Isolated DC-DC Power Modules

2.4Vdc - 5.5Vdc input; 0.75Vdc to 3.63Vdc output; 3A Output Current

### **Feature Specifications**

Unless otherwise indicated, specifications apply over all operating input voltage, resistive load, and temperature conditions. See Feature Descriptions for additional information.


| Parameter   | Device | Symbol           | Min  | Тур | Max                  | Unit                  |
|---|--------|------------------|------|-----|----------------------|-----------------------|
| On/Off Signal interface   |        |                  |      |     |                      |                       |
| Device code with Suffix "4" – Positive logic  |        |                  |      |     |                      |                       |
| (On/Off is open collector/drain logic input;  |        |                  |      |     |                      |                       |
| Signal referenced to GND - See feature description section)   |        |                  |      |     |                      |                       |
| Input High Voltage (Module ON)  | All    | ViH              | _    | _   | V <sub>IN, max</sub> | V                     |
| Input High Current  | All    | Іін              | _    | _   | 10                   | μΑ                    |
| Input Low Voltage (Module OFF)  | All    | VIL              | -0.2 | _   | 0.3                  | V                     |
| Input Low Current   | All    | lıL              | _    | 0.2 | 1                    | mA                    |
| Device Code with no suffix – Negative Logic   |        |                  |      |     |                      |                       |
| (On/OFF pin is open collector/drain logic input with  |        |                  |      |     |                      |                       |
| external pull-up resistor; signal referenced to GND)  |        |                  |      |     |                      |                       |
| Input High Voltage (Module OFF)   | All    | VIH              | 1.5  | _   | V <sub>IN,max</sub>  | Vdc                   |
| Input High Current  | All    | lін              |      | 0.2 | 1                    | mA                    |
| Input Low Voltage (Module ON)   | All    | VIL              | -0.2 | _   | 0.3                  | Vdc                   |
| Input low Current   | All    | lıL              |      | _   | 10                   | μΑ                    |
| Turn-On Delay and Rise Times  |        |                  |      |     |                      |                       |
| (I <sub>0</sub> =I <sub>0, max</sub> , V <sub>IN</sub> = V <sub>IN, nom</sub> , T <sub>A</sub> = 25 °C, )   |        |                  |      |     |                      |                       |
| Case 1: On/Off input is set to Logic Low (Module ON) and then input power is applied (delay from instant at which V <sub>IN</sub> =V <sub>IN, min</sub> until Vo=10% of Vo,set) | All    | Tdelay           | _    | 3.9 | _                    | msec                  |
| Case 2: Input power is applied for at least one second and then the On/Off input is set to logic Low (delay from instant at which Von/Off=0.3V until Vo=10% of Vo, set)         | All    | Tdelay           | _    | 3.9 | _                    | msec                  |
| Output voltage Rise time (time for Vo to rise from 10% of Vo,set to 90% of Vo, set)   | All    | Trise            | _    | 4.2 | 8.5                  | msec                  |
| Output voltage overshoot – Startup  |        |                  |      | _   | 1                    | % V <sub>O, set</sub> |
| I <sub>O</sub> = I <sub>O, max</sub> ; V <sub>IN</sub> = 3.0 to 5.5Vdc, T <sub>A</sub> = 25 °C  |        |                  |      |     |                      |                       |
| Remote Sense Range  |        |                  | _    | -   | 0.5                  |                       |
| Overtemperature Protection  | All    | T <sub>ref</sub> | _    | 140 | _                    | °C                    |
| (See Thermal Consideration section)   |        |                  |      |     |                      |                       |
| Input Undervoltage Lockout  |        |                  |      |     |                      |                       |
| Turn-on Threshold   | All    |                  |      | 2.2 |                      | V                     |
| Turn-off Threshold  | All    |                  |      | 2.0 |                      | V                     |

## Austin MiniLynx™: SMT Non-Isolated DC-DC Power Modules

2.4Vdc - 5.5Vdc input; 0.75Vdc to 3.63Vdc output; 3A Output Current

#### **Characteristic Curves**


The following figures provide typical characteristics for the Austin MiniLynx™ SMT modules at 25°C.



97 94 91 91 88 85 79 VIN = 2.5V VIN = 3.3V VIN = 5.0V OUTPUT CURRENT, Io (A)

Figure 1. Converter Efficiency versus Output Current (Vout = 0.75Vdc).

Figure 4. Converter Efficiency versus Output Current (Vout = 1.8Vdc).







Figure 2. Converter Efficiency versus Output Current (Vout = 1.2Vdc).

Figure 5. Converter Efficiency versus Output Current (Vout = 2.5Vdc).






Figure 3. Converter Efficiency versus Output Current (Vout = 1.5Vdc).

Figure 6. Converter Efficiency versus Output Current (Vout = 3.3Vdc).

# Austin MiniLynx™: SMT Non-Isolated DC-DC Power Modules

2.4Vdc - 5.5Vdc input; 0.75Vdc to 3.63Vdc output; 3A Output Current

#### Characteristic Curves (continued)

The following figures provide typical characteristics for the Austin MiniLynx™ SMT modules at 25°C.




Figure 7. Input voltage vs. Input Current (Vout =2.5Vdc).

Figure 10. Transient Response to Dynamic Load Change from 50% to 100% of full load (Vo = 3.3Vdc).




Figure 8. Typical Output Ripple and Noise (Vin = 5.0V dc, Vo = 0.75Vdc, Io=3A).

Figure 11. Transient Response to Dynamic Load Change from 100% to 50% of full load (Vo = 3.3 Vdc).




Figure 9. Typical Output Ripple and Noise (VIN = 5.0V dc, Vo = 3.3Vdc, Io=3A).

Figure 12. Transient Response to Dynamic Load Change from 50% to 100% of full load (Vo = 3.3 Vdc, Cext = 2x150  $\mu F$  Polymer Capacitors).

# Austin MiniLynx™: SMT Non-Isolated DC-DC Power Modules

2.4Vdc - 5.5Vdc input; 0.75Vdc to 3.63Vdc output; 3A Output Current

#### Characteristic Curves (continued)

The following figures provide typical characteristics for the Austin MiniLynx™ SMT modules at 25°C.




Figure 13. Transient Response to Dynamic Load Change from 100% of 50% full load (Vo = 3.3Vdc, Cext =  $2\times150~\mu F$  Polymer Capacitors).




Figure 16. Typical Start-Up with application of Vin (VIN = 5.0Vdc, Vo = 3.3Vdc, Io = 3A).




Figure 14. Typical Start-Up Using Remote On/Off (VIN = 5.0Vdc, VO = 3.3Vdc, IO = 3A).




Figure 17 Typical Start-Up Using Remote On/Off with Prebias (VIN = 3.3Vdc, VO = 1.8Vdc, IO = 1.0A, VD = 1.0Vdc).




Figure 15. Typical Start-Up Using Remote On/Off with Low-ESR external capacitors (7x150uF Polymer) (VIN = 5.0Vdc, VO = 3.3Vdc, IO = 3A,  $CO = 1050\mu$ F).




Figure 18. Output short circuit Current (VIN = 5.0Vdc, Vo = 0.75Vdc).

# Austin MiniLynx™: SMT Non-Isolated DC-DC Power Modules

2.4Vdc - 5.5Vdc input; 0.75Vdc to 3.63Vdc output; 3A Output Current

#### Characteristic Curves (continued)

The following figures provide thermal derating curves for the Austin MiniLynx™ SMT modules.




Figure 19. Derating Output Current versus Local Ambient Temperature and Airflow (VIN = 5.0, Vo=3.3Vdc).




Figure 22. Derating Output Current versus Local Ambient Temperature and Airflow (VIN = 3.3dc, Vo=2.5 Vdc).




Figure 20. Derating Output Current versus Local Ambient Temperature and Airflow ( $V_{IN} = 5.0 Vdc$ ,  $V_{O} = 1.8 Vdc$ ).




Figure 23. Derating Output Current versus Local Ambient Temperature and Airflow (VIN = 3.3dc, Vo=1.2 Vdc)




Figure 21. Derating Output Current versus Local Ambient Temperature and Airflow (VIN = 5.0Vdc, Vo=0.75 Vdc).





Figure 24. Derating Output Current versus Local Ambient Temperature and Airflow (VIN = 3.3dc, Vo=0.75 Vdc).

### **Test Configurations**


# Austin MiniLynx™: SMT Non-Isolated DC-DC Power Modules

2.4Vdc - 5.5Vdc input; 0.75Vdc to 3.63Vdc output; 3A Output Current




NOTE: Measure input reflected ripple current with a simulated source inductance ( $L_{\text{TEsT}}$ ) of 1µH. Capacitor  $C_{\text{S}}$  offsets possible battery impedance. Measure current as shown above.

Figure 25. Input Reflected Ripple Current Test Setup.



NOTE: All voltage measurements to be taken at the module terminals, as shown above. If sockets are used then Kelvin connections are required at the module terminals to avoid measurement errors due to socket contact resistance.

Figure 26. Output Ripple and Noise Test Setup.



NOTE: All voltage measurements to be taken at the module terminals, as shown above. If sockets are used then Kelvin connections are required at the module terminals to avoid measurement errors due to socket contact resistance.

Figure 27. Output Voltage and Efficiency Test Setup.

Efficiency 
$$\eta = \frac{V_0. I_0}{V_{IN}. I_{IN}} \times 100 \%$$

### **Design Considerations**

### **Input Filtering**

The Austin MiniLynx<sup>TM</sup> SMT module should be connected to a low-impedance source. A highly inductive source can affect the stability of the module. An input capacitance must be placed directly adjacent to the input pin of the module, to minimize input ripple voltage and ensure module stability.

To minimize input voltage ripple, low-ESR polymer and ceramic capacitors are recommended at the input of the module. Figure 28 shows the input ripple voltage (mVp-p) for various outputs with  $1\times22\mu\text{F}$  (TDK: C3225X5R0J226V) ceramic capacitor at the input of the module. Figure 29 shows the input ripple with  $1\times47\mu\text{F}$  (TDK: C3225X5R0J476M) ceramic capacitor at full load.




Figure 28. Input ripple voltage for various outputs with 1x22 µF ceramic capacitor at the input (full-load).




Figure 29. Input ripple voltage for various outputs with 1x47 µF ceramic capacitor at the input (full load).

### Austin MiniLynx™: SMT Non-Isolated DC-DC Power Modules

2.4Vdc - 5.5Vdc input; 0.75Vdc to 3.63Vdc output; 3A Output Current

# **Design Considerations** (continued) **Output Filtering**

The Austin MiniLynx<sup>TM</sup> SMT module is designed for low output ripple voltage and will meet the maximum output ripple specification with 1  $\mu\text{F}$  ceramic and 10  $\mu\text{F}$  tantalum capacitors at the output of the module. However, additional output filtering may be required by the system designer for a number of reasons. First, there may be a need to further reduce the output ripple and noise of the module. Second, the dynamic response characteristics may need to be customized to a particular load step change.

To reduce the output ripple and improve the dynamic response to a step load change, additional capacitance at the output can be used. Low ESR polymer and ceramic capacitors are recommended to improve the dynamic response of the module. For stable operation of the module, limit the capacitance to less than the maximum output capacitance as specified in the electrical specification table.

### **Safety Considerations**

For safety agency approval the power module must be installed in compliance with the spacing and separation requirements of the end-use safety agency standards, i.e., UL 60950-1, CSA C22.2 No. 60950-1-03, and VDE 0850:2001-12 (EN60950-1) Licensed.

For the converter output to be considered meeting the requirements of safety extra-low voltage (SELV), the input must meet SELV requirements. The power module has extra-low voltage (ELV) outputs when all inputs are ELV.

The input to these units is to be provided with a fast-acting fuse with a maximum rating of 6A in the positive input lead.

### Austin MiniLynx™: SMT Non-Isolated DC-DC Power Modules

2.4Vdc - 5.5Vdc input; 0.75Vdc to 3.63Vdc output; 3A Output Current

#### **Feature Description**

#### Remote On/Off

The Austin MiniLynx™ SMT power modules feature an On/Off pin for remote On/Off operation. Two On/Off logic options are available in the Austin MiniLynx™ series modules. Positive Logic On/Off signal, device code suffix "4", turns the module ON during a logic High on the On/Off pin and turns the module OFF during a logic Low. Negative logic On/Off signal, no device code suffix, turns the module OFF during logic High on the On/Off pin and turns the module ON during logic Low.

For positive logic modules, the circuit configuration for using the On/Off pin is shown in Figure 30. The On/Off pin is an open collector/drain logic input signal (Von/Off) that is referenced to ground. During a logic-high (On/Off pin is pulled high internal to the module) when the transistor Q1 is in the Off state, the power module is ON. Maximum allowable leakage current of the transistor when Von/off =  $V_{\text{IN,max}}$  is  $10\mu\text{A}$ . Applying a logic-low when the transistor Q1 is turned-On, the power module is OFF. During this state VOn/Off must be less than 0.3V. When not using positive logic On/off pin, leave the pin unconnected or tie to  $V_{\text{IN.}}$ 




Figure 30. Circuit configuration for using positive logic On/OFF.

For negative logic On/Off devices, the circuit configuration is shown is Figure 31. The On/Off pin is pulled high with an external pull-up resistor (typical  $R_{pull-up} = 5k$ , +/- 5%). When transistor Q1 is in the Off state, logic High is applied to the On/Off pin and the power module is Off. The minimum On/off voltage for logic High on the On/Off pin is 1.5Vdc. To turn the module ON, logic Low is applied to the On/Off pin by turning ON Q1. When not using the negative logic On/Off, leave the pin unconnected or tie to GND.




Figure 31. Circuit configuration for using negative logic On/OFF.

#### **Overcurrent Protection**

To provide protection in a fault (output overload) condition, the unit is equipped with internal current-limiting circuitry and can endure current limiting continuously. At the point of current-limit inception, the unit enters hiccup mode. The unit operates normally once the output current is brought back into its specified range. The typical average output current during hiccup is 2A.

#### Input Undervoltage Lockout

At input voltages below the input undervoltage lockout limit, module operation is disabled. The module will begin to operate at an input voltage above the undervoltage lockout turn-on threshold.

#### **Overtemperature Protection**

To provide over temperature protection in a fault condition, the unit relies upon the thermal protection feature of the controller IC. The unit will shutdown if the thermal reference point  $T_{\text{ref}}$ , exceeds 140°C (typical), but the thermal shutdown is not intended as a guarantee that the unit will survive temperatures beyond its rating. The module will automatically restart after it cools down.

#### **Output Voltage Programming**

The output voltage of the Austin MiniLynx<sup>TM</sup> SMT can be programmed to any voltage from 0.75 Vdc to 3.63 Vdc by connecting a single resistor (shown as Rtrim in Figure 32) between the TRIM and GND pins of the module. Without an external resistor between TRIM pin and the ground, the output voltage of the module is 0.7525 Vdc. To calculate the value of the resistor Rtrim for a particular output voltage Vo, use the following equation:

$$Rtrim = \left\lceil \frac{21070}{Vo - 0.7525} - 5110 \right\rceil \Omega$$

### Feature Descriptions (continued)

Output Voltage Programming (continued)

# Austin MiniLynx™: SMT Non-Isolated DC-DC Power Modules

2.4Vdc - 5.5Vdc input; 0.75Vdc to 3.63Vdc output; 3A Output Current

For example, to program the output voltage of the Austin MiniLynx $^{\text{TM}}$  module to 1.8 Vdc, *Rtrim* is calculated is follows:

$$Rtrim = \left[ \frac{21070}{1.8 - 0.7525} - 5110 \right]$$
$$Rtrim = 15.004k\Omega$$




Figure 32. Circuit configuration to program output voltage using an external resistor.

Table 1 provides *Rtrim* values required for some common output voltages.

Table 1

| V <sub>O, set</sub> (V) | Rtrim (KΩ) |
|-------------------------|------------|
| 0.7525                  | Open       |
| 1.2                     | 41.973     |
| 1.5                     | 23.077     |
| 1.8                     | 15.004     |
| 2.5                     | 6.947      |
| 3.3                     | 3.160      |

Using 1% tolerance trim resistor, set point tolerance of ±2% is achieved as specified in the electrical specification. The POL Programming Tool, available at www.gecriticalpower.com under the Design Tools section, helps determine the required external trim resistor needed for a specific output voltage.

#### **Voltage Margining**

Output voltage margining can be implemented in the Austin MiniLynx  $^{\text{TM}}$  modules by connecting a resistor,  $R_{\text{margin-up}}$ , from the Trim pin to the ground pin for margining-up the output voltage and by connecting a resistor,  $R_{\text{margin-down}}$ , from the Trim pin to the Output pin for margining-down. Figure 33 shows the circuit configuration for output voltage margining. The POL Programming Tool, available at www.gecriticalpower.com under the Design Tools section, also calculates the values of  $R_{\text{margin-up}}$  and  $R_{\text{margin-down}}$  for a specific output voltage and % margin. Please consult your local GE technical representative for additional details.




Figure 33. Circuit Configuration for margining Output voltage.

# Austin MiniLynx™: SMT Non-Isolated DC-DC Power Modules

2.4Vdc - 5.5Vdc input; 0.75Vdc to 3.63Vdc output; 3A Output Current

#### **Thermal Considerations**

Power modules operate in a variety of thermal environments; however, sufficient cooling should always be provided to help ensure reliable operation.

Considerations include ambient temperature, airflow, module power dissipation, and the need for increased reliability. A reduction in the operating temperature of the module will result in an increase in reliability. The thermal data presented here is based on physical measurements taken in a wind tunnel. The test set-up is shown in Figure 35. Note that the airflow is parallel to the long axis of the module as shown in figure 34. The derating data applies to airflow in either direction of the module's long axis.




Figure 34. Tref Temperature measurement location.

The thermal reference point,  $T_{\rm ref}$  used in the specifications is shown in Figure 34. For reliable operation this temperature should not exceed 115°C.

The output power of the module should not exceed the rated power of the module (Vo,set  $\times$  Io,max).

Please refer to the Application Note "Thermal Characterization Process For Open-Frame Board-Mounted Power Modules" for a detailed discussion of thermal aspects including maximum device temperatures.




Figure 35. Thermal Test Set-up.

GE


# Austin MiniLynx™: SMT Non-Isolated DC-DC Power Modules


2.4Vdc - 5.5Vdc input; 0.75Vdc to 3.63Vdc output; 3A Output Current

### **Mechanical Outline**

Dimensions are in millimeters and (inches).

Tolerances: x.x mm  $\pm$  0.5 mm (x.xx in.  $\pm$  0.02 in.) [unless otherwise indicated] x.xx mm  $\pm$  0.25 mm (x.xxx in  $\pm$  0.010 in.)





SIDE VIEW

Co-planarity (max): 0.102 [0.004]

# Austin MiniLynx™: SMT Non-Isolated DC-DC Power Modules


2.4Vdc - 5.5Vdc input; 0.75Vdc to 3.63Vdc output; 3A Output Current

### **Recommended Pad Layout**

Dimensions are in millimeters and (inches).

Tolerances: x.x mm  $\pm$  0.5 mm (x.xx in.  $\pm$  0.02 in.) [unless otherwise indicated] x.xx mm  $\pm$  0.25 mm (x.xxx in  $\pm$  0.010 in.)

| PIN | FUNCTION |
|-----|----------|
| 1   | On/Off   |
| 2   | Vin      |
| 3   | GND      |
| 4   | Trim     |
| 5   | Vout     |




# Austin MiniLynx™: SMT Non-Isolated DC-DC Power Modules


2.4Vdc - 5.5Vdc input; 0.75Vdc to 3.63Vdc output; 3A Output Current

### **Packaging Details**

The Austin MiniLynx™ SMT version is supplied in tape & reel as standard. Modules are shipped in quantities of 400 modules per reel.



#### Surface Mount Tape and Reel Details



All Dimensions are in millimeters and (in inches).

#### **Reel Dimensions**

Outside diameter: 330.2 mm (13.00)
Inside diameter: 177.8 mm (7.00")
Tape Width: 44.0 mm (1.73")

### Austin MiniLynx™: SMT Non-Isolated DC-DC Power Modules

2.4Vdc - 5.5Vdc input; 0.75Vdc to 3.63Vdc output; 3A Output Current

#### **Surface Mount Information**

#### Pick and Place

The Austin MiniLynx™ SMT modules use an open frame construction and are designed for a fully automated assembly process. The modules are fitted with a label designed to provide a large surface area for pick and placing. The label meets all the requirements for surface mount processing, as well as safety standards and is able to withstand maximum reflow temperature. The label also carries product information such as product code, serial number and location of manufacture.




Figure 36. Pick and Place Location.

#### **Nozzle Recommendations**

The module weight has been kept to a minimum by using open frame construction. Even so, these modules have a relatively large mass when compared to conventional SMT components. Variables such as nozzle size, tip style, vacuum pressure and pick & placement speed should be considered to optimize this process. The minimum recommended nozzle diameter for reliable operation is 3mm. The maximum nozzle outer diameter, which will safely fit within the allowable component spacing, is 8 mm max.

#### **Tin Lead Soldering**

The Austin MiniLynx<sup>TM</sup> SMT power modules are lead free modules and can be soldered either in a lead-free solder process or a conventional Tin/Lead (Sn/Pb) process. It is recommended that the customer review data sheets in order to customize the solder reflow profile for each application board assembly. The following instructions must be observed when soldering these units. Failure to observe these instructions may result in the failure of or cause damage to the modules, and can adversely affect long-term reliability.

The Austin MiniLynx<sup>TM</sup> SMT power modules are lead free modules and can be soldered either in a lead-free solder process or a conventional Tin/Lead (Sn/Pb) process. It is recommended that the customer review data sheets in order to customize the solder reflow profile for each application board assembly. The following instructions must be observed when soldering these units. Failure to observe these instructions may result in the failure of or cause damage to the modules, and can adversely affect long-term reliability.




Figure 37. Reflow Profile for Tin/Lead (Sn/Pb) process.




Figure 38. Time Limit Curve Above 205°C Reflow for Tin Lead (Sn/Pb) process.

### Austin MiniLynx™: SMT Non-Isolated DC-DC Power Modules

2.4Vdc - 5.5Vdc input; 0.75Vdc to 3.63Vdc output; 3A Output Current

### Surface Mount Information (continued)

#### **Lead Free Soldering**

The –Z version Austin MiniLynx SMT modules are lead-free (Pb-free) and RoHS compliant and are both forward and backward compatible in a Pb-free and a SnPb soldering process. Failure to observe the instructions below may result in the failure of or cause damage to the modules and can adversely affect long-term reliability.

#### **Pb-free Reflow Profile**

Power Systems will comply with J-STD-020 Rev. C (Moisture/Reflow Sensitivity Classification for Nonhermetic Solid State Surface Mount Devices) for both Pb-free solder profiles and MSL classification procedures. This standard provides a recommended forced-air-convection reflow profile based on the volume and thickness of the package (table 4-2). The suggested Pb-free solder paste is Sn/Ag/Cu (SAC). The recommended linear reflow profile using Sn/Ag/Cu solder is shown in Figure. 39.

#### **MSL Rating**

The Austin MiniLynx<sup>TM</sup> SMT modules have a MSL rating of 2a

#### Storage and Handling

The Austin MiniLynx<sup>™</sup> modules have a MSL rating of 1. The recommended storage environment and handling procedures for moisture-sensitive surface mount packages is detailed in J-STD-033 Rev. A (Handling, Packing, Shipping and Use of Moisture/Reflow Sensitive Surface Mount Devices). Moisture barrier bags (MBB) with desiccant are required for MSL ratings of 2 or greater. These sealed

packages should not be broken until time of use. Once the original package is broken, the floor life of the product at conditions of  $\leq 30^{\circ}\text{C}$  and 60% relative humidity varies according to the MSL rating (see J-STD-033A). The shelf life for dry packed SMT packages will be a minimum of 12 months from the bag seal date, when stored at the following conditions:  $< 40^{\circ}$  C, < 90% relative humidity.

### **Post Solder Cleaning and Drying Considerations**

Post solder cleaning is usually the final circuit-board assembly process prior to electrical board testing. The result of inadequate cleaning and drying can affect both the reliability of a power module and the testability of the finished circuit-board assembly. For guidance on appropriate soldering, cleaning and drying procedures, refer to Board Mounted Power Modules: Soldering and Cleaning Application Note (AN04-001).




Figure 39. Recommended linear reflow profile using Sn/Ag/Cu solder.

# Austin MiniLynx™: SMT Non-Isolated DC-DC Power Modules

2.4Vdc - 5.5Vdc input; 0.75Vdc to 3.63Vdc output; 3A Output Current

### **Ordering Information**

Please contact your GE Sales Representative for pricing, availability and optional features.

**Table 2. Device Codes** 

| Device Code    | Input<br>Voltage Range | Output<br>Voltage | Output<br>Current | Efficiency<br>3.3V@ 3A | On/Off<br>Logic | Connector<br>Type | Comcodes    |
|----------------|------------------------|-------------------|-------------------|------------------------|-----------------|-------------------|-------------|
| AXH003A0X-SR   | 2.4 – 5.5Vdc           | 0.75 - 3.63Vdc    | 3 A               | 94.0 %                 | Negative        | SMT               | 108991196   |
| AXH003A0X-SRZ  | 2.4 – 5.5Vdc           | 0.75 – 3.63Vdc    | 3 A               | 94.0 %                 | Negative        | SMT               | CC109101301 |
| AXH003A0X4-SR  | 2.4 – 5.5Vdc           | 0.75 - 3.63Vdc    | 3 A               | 94.0 %                 | Positive        | SMT               | 108991205   |
| AXH003A0X4-SRZ | 2.4 – 5.5Vdc           | 0.75 – 3.63Vdc    | 3 A               | 94.0 %                 | Positive        | SMT               | 109100014   |

<sup>-</sup>Z refers to RoHS-compliant codes

# Contact Us

For more information, call us at

USA/Canada:

+1 877 546 3243, or +1 972 244 9288

Asia-Pacific:

+86.021.54279977\*808

Europe, Middle-East and Africa:

+49.89.878067-280

### www.gecriticalpower.com

GE Critical Power reserves the right to make changes to the product(s) or information contained herein without notice, and no liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

