

Cable gland - G-INS-N3/4-M68L-PNES-GY - 1411154

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable gland, Cable gland material: Polyamide 6, External cable diameter 13 mm ... 18 mm, Shielding: No, Connecting thread: 3/4 inch NPT, Color: silver grey

Product Features



Key commercial data

Packing unit	1 pc
Minimum order quantity	5 pc
Weight per Piece (excluding packing)	24.0 GRM
Custom tariff number	39269097
Country of origin	Turkey

Technical data

Dimensions

Length	47.5 mm
Length without connecting thread	35.5 mm
Connecting thread diameter	25.9 mm
Wrench size, union nut	33 mm
Wrench size, support	33 mm
Hexagon angular dimension GRP	37.8 mm
Length of the connecting thread	15 mm
External cable diameter	13 mm ... 18 mm

Ambient conditions

Degree of protection	IP68 (5 bar, 30 min.)
Ambient temperature (operation)	-30 °C ... 80 °C (for a short period up to 150 °C)

General

Cable gland - G-INS-N3/4-M68L-PNES-GY - 1411154

Technical data

General

Cable gland material	Polyamide 6
Seal material	Neoprene
Cable seal material	Neoprene
Shielded	No
Thread type on connection side	3/4 inch NPT
Torque	7 Nm ... 9 Nm (Union nut)
Inflammability class according to UL 94	V2
Color	silver grey

Classifications

eCl@ss

eCl@ss 5.1	27149109
eCl@ss 6.0	27149109
eCl@ss 8.0	27149109

ETIM

ETIM 4.0	EC000441
ETIM 5.0	EC000441

Approvals

Approvals

Approvals

CSA / UL Listed

Ex Approvals

Approvals submitted

Approval details

CSA 

Cable gland - G-INS-N3/4-M68L-PNES-GY - 1411154

Approvals

UL Listed 

Drawings

Dimensional drawing

