





F

- I. Material:thermo plastic,ul94 v-0
- 2. Bulkhead thickness range: 0.79-2.54
- 3. Color:black

Note:

Pro/E File - REV C - 2009-06-09

- 4. Applicable components
 Applicable power crimp contact: 10132418-*****LF
 Applicable contact secondary lock:10073097-DGC001LF
 Applicable signal contact 76347-DGC302LF
 Applicable latch 10066441-DGC001LF for STR version
- 5. Product Spec: GS-12-474
- 6. Application Spec: GS-20-0445
- 7. The part is been sold as loose piece and fci guarantees is the part in compliance with this customer drawing statement. The product spec for cable assemly can be only as the reference document because the testing and spec is based on using fci raw cable and cable assemble. If the raw cable and cable assembly is outside suppliers sourced by cusotmers, customers or cable assembly suppliers should be fully responsible for the cable assy quality.

spec ref	*			dr	Yong Zhang		2014/10/12	proje	ection	1 1/1	NΛ	size	scale	
tolerance std	TOLERANCES UNLESS OTHERWISE SPECIFIED			eng	e n g Yong Zhang		2015/06/29	⊕ - ⊟		MM		A 4 I : I		
				chr -		-			→		ecn no	ELX-N-21259-1		
				appr Guo-Feng Jin		2015/06/30	product	duct family		rel level	Released			
surface	linear	0 . X	±0.5	FCi	~ :	– SACP PM					0 U		rev	
		0.XX	±0.25		- JACF FM 				D 1006		66440-DG	C0200LF		
		0.XXX	±0.10			+ Pow	verBlade Cabl	e Housi	e Housing		» p			В
	angular	0°	±°	www.	fci.com	cat. no	>.	*	Pr	oduct -	Customer	· Drw	sheet 2 of	2

<u>で</u>

С

pyright FCI

D

PDS: Rev :B

STATUS:Released

Printed: Jul 01, 2015