# XZCPA1164L10



Main		
Accessory / separate part category	Cabling accessory	
Accessory / separate part type	Pre-wired connectors	
Series name	Application	

## Complementary

Electrical connection	M12, 5 pins (included earth pin) elbowed female connector	
Cable connector fixing	Screw-on	
Collar material	Stainless steel 316L	
Status LED	Without	
Cable length	32.81 ft (10 m)	
Cable outer diameter	0.22 in (5.7 mm)	
Cable composition	5 x 0.34 mm <sup>2</sup>	
Wire insulation material	PVC	
System Voltage	60 V AC 75 V DC	
Line Rated Current	4 A	
Contact resistance	5000 µOhm	
Insulating resistance	1 GΩ	
Product weight	1.07 lb(US) (0.485 kg)	

## Environment

IP degree of protection	IP69K
ambient air temperature for operation	-13185 °F (-2585 °C) (static)
ambient air temperature for storage	-31212 °F (-35100 °C)

## **Offer Sustainability**

Not Green Premium product		
Compliant - since 0601 - Schneider Electric declaration of conformity		
WARNING: This product can expose you to chemicals including:		
Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and		
Di-isodecyl phthalate (DIDP), which is known to the StateDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth of California to cause birth defects or other reproductive defects or other reproductive harm. harm.		
For more information go to www.p65warnings.ca.gov		


#### Contractual warranty

Warranty period

18 months

## Dimensions






L: Lenght of cable

## **Connections and Schemes**

#### Connectors



BU : Blue BN : Brown BK : Black Y/G :Yellow / Green BK/WH :Black / White

