




HEYClip™ Unscrewing Snap Rivets

WILL FIT THESE PANELS				PART NO.	DESCRIPTION	PART DIMENSIONS						STYLE		
MOUNTING HOLE DIA.		ASSEMBLED PANEL THICKNESS				A Length	B Head Height	C Head Diameter						
in.	mm.	in.	mm.	Black	in.	mm.	in.	mm.	in.	mm.				
HUSR Series														
.197	5,0	.059	1,5	.236	6,0	4330	HUSR 197-158	.43	11,0	.15	3,9	.47	12,0	1
.236	6,0	.059	1,5	.236	6,0	4331	HUSR 236-059	.43	11,0	.15	3,9	.63	16,0	
.315	8,0	.118	3,0	.394	10,0	4332	HUSR 315-118	.55	14,0	.16	4,0	.79	20,0	
		.276	7,0	.315	8,0	4333	HUSR 315-276	.80	20,3	.14	3,6	.79	20,0	

Standard color black.

- Phillips head screw driver required for removal.




HEYClip™ Tough Rivets

WILL FIT THESE PANELS				PART NO.	DESCRIPTION	PART DIMENSIONS									
MOUNTING HOLE DIAMETER		ASSEMBLED PANEL THICKNESS				A Length Below Panel	B Head Height	C Head Diameter							
Minimum	Maximum	Minimum	Maximum	Black	in.	mm.	in.	mm.	in.	mm.					
Mini - MTR Series															
.122	3,1	.128	3,3	.155	3,9	.180	4,6	12475	MTR 180-125	.37	9,4	.05	1,3	.22	5,5
.144	3,7	.154	3,9	.265	6,7	.290	7,4	12477	MTR 290-150	.47	11,9	.05	1,3	.30	7,6
Standard - TR Series															
.193	4,9	.205	5,2	.059	1,5	.181	4,6	12466	TR 181-199	.45	11,3	.08	2,1	.28	7,2
.250	6,4	.276	7,0	.098	2,5	.315	8,0	12468	TR 315-263	.90	22,8	.11	2,8	.59	15,0
.315	8,0	.325	8,3	.118	3,0	.315	8,0	12469	TR 315-320	.83	21,1	.09	2,3		

Standard color black.

ALL NEW!




Heyco® Removable Rivets

WILL FIT THESE PANELS				PART NO.	DESCRIPTION	PART DIMENSION					
Mounting Hole Diameter		Assembled Panel Thickness				A Length Below Panel	B Head Height	C Head Diameter			
in.	mm.	in.	mm.	Natural	in.	mm.	in.	mm.	in.	mm.	
.188	4,8	.062	1,6	12220	HRR 062-188	.50	12,7	.07	1,8	.38	9,5
		.125	3,2	12221	HRR 125-188						
.250	6,4	.062	1,6	12222*	HRR 062-250	.50	12,7	.07	1,8	.44	11,1
		.125	3,2	12223	HRR 125-250						
		.187	4,7	12224	HRR 187-250						

Standard color natural.

*Will also fit .210"/.218" square hole (for Darling Shelves).

- Two-piece rivet can be removed by retracting the pin then the body.
- Slot in line with pin for pin removal with small screw driver, fingernail or other sharp edge underneath the head of the pin.



	HUSR & HRR	MTR	TR
Material	Nylon 6/6	Heat stabilized Nylon 6	Nylon 6/6
Flammability Rating	94V-2	94 V-2	94HB
Temperature Range	32°F (0°C) to 185°F (85°C)	32°F (0°C) to 230°F (110°C)	32°F (0°C) to 230°F (110°C)