Product datasheet Characteristics

9001KA23

U
aii

Device short name	К
Mounting diameter	1.18 in (30 mm)

Complementary

Line Rated Current	10 A
Contact operation	Standard without fingersafe
Contacts type and composition	1 NC
Electrical connection	Screw terminals binder head
Permissible voltage	<= 600 V

Environment

product certifications	CE
	UL listed file E42259 CCN NKCR
	CSA LR24590 class 3211 03

Offer Sustainability

785901028864	785901028864
Compliant - since 0921 - Schneider Electric declaration of conformity	Compliant - since 0921 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Nickel compounds, which is known to the State of California to cause cancer, and	Nickel compounds, which is known to the State of California to cause cancer, and
Di-isodecyl phthalate (DIDP), which is known to the Stat of California to cause birth defects or other reproductive harm.	eDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov

Contractual warranty

Contractual warranty		
Warranty period	18 months	