









REV.	DATE	DESCRIPTION
NC	05/24/04	INITIAL RELEASE



RECOMMENDED CABLE
STRIPPING DIMENSIONS



RECOMMENDED
MOUNTING HOLE



NOTE:

1. CRIMPED FERRULE
HEX CRIMP SIZE .213"
2. CRIMPED CONTACT PIN
HEX CRIMP SIZE .068"

					UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [] ARE IN INCHES AND FOR CUSTOMER REFERENCE ONLY. UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE: 0.5 – 8mm ± 0.20mm 8 – 30mm ± 0.40mm 30 – 120mm ± 0.50mm UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE: .020 – .315 = ± 0.007” .315 – 1.180 = ± 0.015” 1.180 – 4.724 = ± 0.020” DO NOT SCALE DRAWING	APPROVALS		DATE		Amphenol Connex				
8						DRAWN	G.R.S.	05/24/04						
7	FERRULE	COPPER	NICKEL	1		CHECKED			PART DESCRIPTION BNC BULKHEAD CRIMP JACK (FOR RG–55/U, 142A/U, 223/U, 400/U CABLE)					
6	HEX NUT	BRASS	NICKEL	1		ISSUED								
5	LOCK WASHER	BRASS	NICKEL	1		SHEET	1 OF 1		PART NO. 112505					
4	GASKET	RUBBER	RED	1										
3	CONTACT PIN	PHOS. BRONZE	GOLD	1				DWG. NO. 112505.DWG						
2	INSULATOR	TEFLON	NATURAL	1										
1	BODY/HOUSING	BRASS	NICKEL	1					REV.	NC	SIZE	A	SCALE	NA
	DESCRIPTION	MATERIAL	FINISH	QTY			CAD FILE C:/112/112505.DWG							