

# **RAFIX 22 QR - Pushbutton, non-illuminated, protruding lens, round collar, metal front ring, latching**

**1.30.240.331/0700**



## **General information**

Form of lens	protruding lens
Color of lens	opaque slate-grey
Color of front ring	silver metallic
Form of collar	round

## **Dimensions**

Dimensions of collar	ø 29.8 mm
Overall height	12.45 mm
Mounting depth with contact block without cable	56.4 mm
Mounting hole	ø 22.3 mm
Mounting grid	50 x 30 mm

## **Mechanical design**

Mounting	ring nut
Contact function	latching
Illumination	no

## **Mechanical characteristics**

Operating travel	4 mm
Operating force max.	approx. 5 N for 1 switching element
Robustness max.	100 N

## **Other specifications**

Operating life (operations)	1,000,000 momentary / 500,000 latching cycle
Degree of protection from front side	IP65 (DIN EN 60529)
Ambient temp. operating min.	-25 °C
Ambient temp. operating max.	+70 °C
Storage temperature min.	-40 °C
Storage temperature max.	+80 °C
Environmental resistance	acc. to IEC 60068-2-14, -30, -33 and -78
ROHS compliant	yes
REACH compliant	yes

Panel cut-out to IEC 60947-5-1

