9001KP1Y31



Main

Range of product	Harmony 9001K
Product or component type	Pilot light
Device short name	K

Complementary

Pozel meterial	Chromium ploted motel	
Bezel material	Chromium plated metal	
Mounting diameter	1.18 in (30 mm)	
Lens type	Fresnel (plastic)	
Cap/operator or lens colour	Yellow	
Light source	Incandescent	
Bulb base	BA 9s	
Light block supply	Via transformer (f = 50/60 Hz)	
	Via integral transformer (f = 50/60 Hz)	
Connections - terminals	Screw clamp terminals (1 x 0.222 x 1.5 mm²) conforming to IEC 60947-1	
Shape of screw head	Round head	
Operating position	Any position	
[Us] rated supply voltage	110120 V AC	
Operating mode	Normal	
Device presentation	Complete product	

Environment

product certifications	CE	
	CSA LR25490 class 3211 03	
	UL listed file E42259 CCN NKCR	
NEMA degree of protection	NEMA 1/2/3/3R/4/6/12/13	

Offer Sustainability

785901032083	785901032083
Compliant - since 0921 - Schneider Electric declaration of conformity	Compliant - since 0921 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.	Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty paried		
warranty period romonths	Warranty period	18 months