

5

4

3


2

1


Mating face according to : MIL-C-24308 / DIN 41652 / CECC 75301-802

No. 1 contact

12,5 max.




nut thread



3,7 ± 0,3

Printed board layout
component side



0,6

6,2

25 ± 0,1

31,2 max.

4 x 2,74 = 10,96

3 x 2,74 = 8,22

2,74

No.1 contact

ø3,1 ± 0,1

⊕ ⊖ ø0,1

2,84

1,42

2,74

ø1 ± 0,1

⊕ ⊖ ø0,05

No.6 contact

25

No.9 contact

09 65 121 3701

M3

1

09 65 121 6701

M3

2

09 65 121 7701

M3

3

09 65 121 3702

4-40 UNC

1

09 65 121 6702

4-40 UNC

2

09 65 121 7702

4-40 UNC

3

Part number

Nut thread

Performance level

Mod.

Dat.

Name

Dat.

Name

Detail. 05/03/02

CV

Insp.

Stand.



All Dim. in mm
Orig. Size DIN A 4

D-Sub, 9 poles,
male, straight,
with solder pins 3.7,
and nuts.

Maßstab/
Scale

1,5:1

HARTING EURL
F-95972 Paris



TB 09 65 121 X70X

Blatt/ Page

2

Sub.