



Main

Range of product	Zelio Relay
Product or component type	Solid state relay
Device short name	SSR
Phase	1 phase
Mounting support	Symmetrical DIN rail
Line Rated Current	30 A
Output voltage	24...280 V AC
[Uc] control circuit voltage	4...32 V DC

Complementary

Contacts type and composition	1 NO
Tightening torque	Input : 0.6...0.7 N.m Output : 0.6...0.7 N.m
Connections - terminals	Screw terminals 1 x 0.2...1 x 5.3 mm ² input - AWG 24...AWG 10 Screw terminals 1 x 0.2...1 x 5.3 mm ² output - AWG 24...AWG 10
Local signalling	LED green input status
Switching voltage	4 V DC turn-on 1 V DC turn-off
Input current limits	8...12 mA
Solid state output type	Zero voltage switching SCR output
Load current	0.15...30 A
Absolute maximum voltage	600 V
Surge current	625 A 16.6 ms
Voltage drop	1.6 V on-state
Maximum I ² t for fusing	1620 A ² .s 8.3 ms
Leakage current	<= 10 mA off-state
DV/dt	500 V/μs off-state at maximum voltage
Response time	0.5 cycle turn-on 0.5 cycle turn-off

Environment


standards	UL E258297 CSA LR 40487 IEC 60950-1 IEC 62314
marking	CE
IP degree of protection	IP20
ambient air temperature for operation	-40...176 °F (-40...80 °C)
ambient air temperature for storage	-40...257 °F (-40...125 °C)

Offer Sustainability

Not Green Premium product	Not Green Premium product
Compliant - since 0940 - Schneider Electric declaration of conformity	Compliant - since 0940 - Schneider Electric declaration of conformity

Dimensions


DIN Rail Mounting



- (1) 35 mm/1.37 in. DIN rail.
 (2) Ø 4.4 mm x 5.5 mm / Ø 0.17 in. x 0.22 in. elongated hole

Thermal Derating Curves

10...45 A Relays



- X Ambient temperature (°C)
 Y Output current (Amps)

Note : These are typical curves, actual durability depends on load, environment, duty cycle, etc.