



Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range of product	8501X
Relay type	Control relay
Product or component type	Latching device

Complementary

[Uc] control circuit voltage	24 V DC
Coil Voltage Limits	Operational 0.8...1.1 Uc DC
Inrush Power in Watts	18 W
Sealed Power in Watts	18 W
Electrical connection	Screw clamp terminals
Wire Gauge	AWG 18...AWG 12 copper
Terminal Tightening Torque	Control circuit 9.03...12.04 lbf.in (1.02...1.36 N.m) screw terminals

Environment

Product certifications	CSA LR60905 class 3211 02 UL recognized E78403 CCN NKCR2 CE
------------------------	---

Ordering and shipping details

Category	21159 - 8501 X ACCESSORIES
Discount Schedule	CP2
GTIN	00785901147374
Package weight(Lbs)	0.45 kg (1 lb(US))
Returnability	No
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty

18 months
