



**Product:** [9460](#)

Electronic, 2 C #18 Str TC, PO Ins, OS, PVC Jkt, CM

[Request Sample](#)

## Product Description

Electronic, 2 Conductor 18AWG (16x30) Tinned Copper, PO Insulation, Overall Beldfoil® Shield, PVC Outer Jacket, CM

## Technical Specifications

### Product Overview

Suitable Applications:	for use with automatic stripping equipments; low voltage analog signals (4-20ma, 0-10v, ...); low voltage digital control (24v, ...); line level audio; computer communication; panel wiring
------------------------	--

### Physical Characteristics (Overall)

#### Conductor

AWG	Stranding	Material	No. of Pairs
18	16x30	TC - Tinned Copper	1

Conductor Count:	2
Total Number of Pairs:	1

#### Insulation

Material	Nominal Wall Thickness
PE - Polyethylene	0.0175 in

#### Color Chart

Number	Color
1	Black & Clear

#### Outer Shield Material

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	Alum / Poly	Beldfoil®	100 %	TC - Tinned Copper	20	Stranded

#### Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.23 in	0.03 in

### Electrical Characteristics

#### Conductor DCR

Nominal Conductor DCR
6.5 Ohm/1000ft

#### Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
29.8 pF/ft	44 pF/ft

#### Inductance

Nominal Inductance
0.18 µH/ft

## Impedance

### Nominal Characteristic Impedance

57 Ohm

## Current

### Max. Recommended Current [A]

5.2 Amps per conductor @ 25°C A

## Voltage

### UL Voltage Rating

300 V RMS

## Temperature Range

UL Temp Rating: 60°C (UL AWM Style 2092)

Operating Temp Range: -20°C To +60°C

## Mechanical Characteristics

Bulk Cable Weight: 34 lbs/1000ft

Max Recommended Pulling Tension: 70 lbs

Min Bend Radius/Minor Axis: 2.5 in

## Standards

NEC Articles: 800

NEC/(UL) Specification: CM

CEC/C(UL) Specification: CM

UL AWM Style: UL Style 2092 (300 V 60°C)

CPR Euroclass: Eca

## Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2003/96/EC (BFR): Yes

EU Directive 2011/65/EU (ROHS II): Yes

EU Directive 2012/19/EU (WEEE): Yes

EU Directive 2015/863/EU: Yes

EU Directive Compliance: EU Directive 2003/11/EC (BFR)

EU CE Mark: Yes

EU RoHS Compliance Date (yyyy-mm-dd): 2004-01-01

MII Order #39 (China RoHS): Yes

## Flammability, LSOH, Toxicity Testing

UL Flammability: UL1685 UL Loading

CSA Flammability: FT1

ISO/IEC Flammability: IEC 60332-1-2

UL voltage rating: 300 V RMS

## Plenum/Non-Plenum

Plenum (Y/N): No

## Part Number

### Variants

Item #	Color	UPC
9460 0105000	Black	612825253334
9460 0605000	Chrome	612825253365
9460 060U1000	Chrome	612825253341
9460 060U500	Chrome	612825253358

Footnote: C - CRATE REEL PUT-UP.

Footnote: Z - FINAL PUT-UP MAY VARY (= OR -) 10% FOR SPOOLS OR REELS AND (+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN.

## Product Notes

Notes:	The jacket and shield are bonded so both can be removed on automatic stripping equipment. Drain wire is on the inside of foil shield.
--------	---

## History

Update and Revision:	Revision Number: 0.306 Revision Date: 04-28-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.