


THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS					
GP	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
		B		INITIAL RELEASE	26AUG2015	DM	DM

NOTES:

- 1 EACH ITEM AND ASSEMBLY MUST COMPLY WITH EUROPEAN REDUCTION OF HAZARDOUS SUBSTANCES (RoHS) REGULATION. UNDER DIRECTIVE 2011/65/EU AND HARMONIZED STANDARD EN 50581:2012.
- 2 DO NOT SOLDER CONTACT, CRIMP ONLY
- 3 IDENTIFY POSITION PE, LOADING POSITIONER PE TO SOCKET PE
- 4 PE CONTACT CIRCUIT IDENTIFIED BY EXTENDED LENGTH POLARIZED "KEY"
- 5 ELECTRICAL TEST:
 100% OPEN SHORT&MISS WIRE TEST
 CONTACT RESISTANCE: 2 OHM MAX



CONNECTOR 1

2829462-1
 TE P/N

WIRING SCHEME	
CONNECTOR HOUSING (ITEM 1)	WIRE
PE/⊥	GREEN/YELLOW
N	BLUE
L	BROWN

QTY	UoM	DESCRIPTION	ITEM
0.661	M	Cable, H07RN-F, 14/3 Black, 10.9-14.0mm OD (Mueller 4101403)	6
1	PC	Cable Ring Nut 11-14mm OD	5
1	PC	Cable Clamp/Seal Assembly 11-14mm OD	4
1	PC	Contact/Positioner Assembly	3
3	PC	Pin Contacts	2
1	PC	Pin Housing Assembly	1

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN T.BURZYŃSKI 25MAY2015	TE Connectivity	
DIMENSIONS: mm		CHK A.V.ZANDVOORT 25MAY2015		
		APVD A.V.ZANDVOORT 25MAY2015	NAME SEALED 3 POS PIN - STD HARMONIZED	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		PRODUCT SPEC	SIZE	
0 PLC ± 0,5	1 PLC ± 0,5	APPLICATION SPEC	CAGE CODE	DRAWING NO
2 PLC ± 0,5	3 PLC ± -	WEIGHT	RESTRICTED TO	
4 PLC ± -	ANGLES ± 2°		A3	00779
MATERIAL	FINISH		C=2829462	
		CUSTOMER DRAWING		SCALE NTS
				SHEET 1 OF 1
				REV B