

PCB terminal block - ZFKDSA 2,5-5,08-15 - 1710484

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

> PCB terminal block, nominal current: 24 A, nom. voltage: 400 V, pitch: 5.08 mm, number of positions: 15, connection method: Spring-cage connection, mounting: Wave soldering, color: green. The article can be aligned to create different nos. of positions!



The figure shows the 10-pos. standard item

Your advantages

- ☑ Defined contact force ensures that contact remains stable over the long term
- ☑ Clamping space opened by means of fixed screwdriver enables convenient conductor connection
- Angled connection enables multi-row arrangement on the PCB
- The latching on the side enables various numbers of positions to be combined
- Two solder pins reduce the mechanical strain on the soldering spots















Key Commercial Data

Packing unit	50 pc
GTIN	4 055626 156378
GTIN	4055626156378

Technical data

Dimensions

Pitch	5.08 mm
Solder pin [P]	3.5 mm
Hole diameter	1.3 mm

General

Range of articles	ZFKDS(A) 2,5
Insulating material group	I
Rated voltage (III/2)	400 V
Nominal current I _N	24 A
Nominal cross section	2.5 mm ²
Flammability rating according to UL 94	V0



PCB terminal block - ZFKDSA 2,5-5,08-15 - 1710484

Technical data

General

Number of positions	15	
Standards and Regulations		
Flammability rating according to UL 94	V0	
Environmental Product Compliance		
China RoHS	Environmentally friendly use period: unlimited = EFUP-e	
	No hazardous substances above threshold values	

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC **E** B.01742

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com