




SIGN	DATE	DESCRIPTION	APPROVER
△	2010.12.08	Added "cULus" standard	Chen Bo
△	2012.02.23	Flange nut is changed	Aaron
△	2012.02.23	The dimension is added	Aaron
△	2012.02.23	The material is changed from Brass to Copper	Aaron
△	2014.06.05	change the dimension from 1.70 to 1.00	Ji long
△	2014.11.13	update drawing	Evan

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

- Fill the glue
- Material
- △ ● Item ① Long contact pin: Copper ,Tin plated
 - △ ● Item ② Short contact pin: Copper ,Tin plated
 - Item ③ Terminal (housing): Thermoplastic (UL94V-0)
 - Item ④ With flange nut: Brass ,M2.5
- Electrical
- Voltage rating: 300VAC
 - Current rating: 10A
 - Withstanding Voltage: 1.6KV
 - Operating temperature: -40°C to +115°C
 - Soldering temperature: 260°C±5°C/5 Sec
 - △ ● Safety Approval:
 - Critical dimension:

VF xx 3 2 x 1 xxxx G

No. OF POLES

04: 2x2 POLES

△ 24: 2x12 POLES

Color

0 Black (RAL9005)

2 Red (RAL3001/D)

3 Orange(RAL2011/P)

4 Yellow(RAL1018/A)

5 Green(RAL6018/T)

6 Blue (RAL5015/A)

8 Grey(RAL7035/D)

9 White(RAL1102)

C Green(RAL6018/U)

RoHS compliant (lead<4%) In copper Alloy

0000: "@ " Logo (Standard)

000A: "ANYTEK" Mark

Any special item by customer request. please contact sales department.

ANYTEK				CUSTOMER COPY			
ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD							
TITLE	VF-3.81 Series 2x2P-2x16P Right angle (With flange)						
PART NO.	VFxx32x1xxxxG			DWG NO.	8VF0203		
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.			Tolerance
		Evan 11/13`14	Evan 11/13`14		UNIT: mm		X. ±0.50
					SCALE: NONE		X.X ±0.30
					REV.: F		X.XX ±0.10
				SHEET: 01/01		X° ±1°	