

## FEATURES

- Micropower Operation
- Single 5V or  $\pm 15\text{V}$  Supply Operation
- Low Charge Injection
- Low  $R_{ON}$
- Low Leakage
- Guaranteed Break Before Make
- Latch Resistant Design
- TTL/CMOS Compatible
- Improved Second Source for DG201A/DG202

## KEY SPECIFICATIONS

- |                        |                                      |
|------------------------|--------------------------------------|
| ■ Supply Current ..... | $I^+ = 40\mu A$ , $I^- = 5\mu A$ Max |
| ■ Charge Injection     |                                      |
| ±15V Supplies .....    | ±25pC Max                            |
| Single 5V Supply ..... | 2pC Typ                              |
| ■ $R_{ON}$ .....       | 65Ω Typ                              |
| ■ Signal Range .....   | ±15V                                 |

## DESCRIPTION


The LTC®201A, LTC202, and LTC203 are micropower, quad CMOS analog switches which typically dissipate only 250µW from ±15V supplies and 40µW from a single 5V supply. The switches have 65Ω typical on resistance and a very high off resistance. A break-before-make characteristic, inherent in these switches, prevents the shorting of two channels. With a supply voltage of ±15V, the signal range is ±15V. These switches have special charge compensation circuitry which greatly reduces charge injection to a maximum of ±25pC (±15V supplies).

The LTC201A, LTC202, and LTC203 are designed for applications such as programmable gain amplifiers, analog multiplexers, sample-and-hold circuits, precision charge switching and remote switching. These three devices are differentiated by the type of switch action, as shown in the logic table.

 LTC and LT are registered trademarks of Linear Technology Corporation.

## TYPICAL APPLICATION

## Micropower 100Hz to 1MHz V-to-F Converter



# LTC201A/LTC202/LTC203

## ABSOLUTE MAXIMUM RATINGS

(Note 1)

Voltages Referenced to  $V^-$

|                                     |                                                          |
|-------------------------------------|----------------------------------------------------------|
| $V^+$ .....                         | 44V                                                      |
| GND .....                           | 25V                                                      |
| Digital Inputs, S, D (Note 2) ..... | -2V to ( $V^+ + 2V$ ) or<br>20mA, Whichever Occurs First |

Current

|                                                          |      |
|----------------------------------------------------------|------|
| Any Input Except S or D .....                            | 30mA |
| Continuous S or D .....                                  | 20mA |
| Peak S or D (Pulsed at 1ms,<br>10% Duty Cycle Max) ..... | 70mA |

ESD Susceptibility (Note 3) .....

Power Dissipation (Plastic) .....

Power Dissipation (Ceramic) .....

Operating Temperature Range

LTC201AC/LTC202C/LTC203C .....

LTC201AM/LTC202M/LTC203M .....

Storage Temperature Range .....

Lead Temperature (Soldering, 10 sec) .....

## LOGIC TABLE

| $IN_x$ | LTC201A<br>IN1 TO IN4 | LTC202<br>IN1 TO IN4 | LTC203   |          |
|--------|-----------------------|----------------------|----------|----------|
|        | IN1 TO IN4            | IN1 TO IN4           | IN1, IN4 | IN2, IN3 |
| 0      | ON                    | OFF                  | OFF      | ON       |
| 1      | OFF                   | ON                   | ON       | OFF      |

## PACKAGE/ORDER INFORMATION

|                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                    |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|
| <p>TOP VIEW</p> <p>N PACKAGE<br/>16-LEAD PDIP<br/><math>T_{JMAX} = 110^{\circ}\text{C}</math>, <math>\theta_{JA} = 120\text{C/W}</math></p> <p>S PACKAGE<br/>16-LEAD PLASTIC SO<br/><math>T_{JMAX} = 110^{\circ}\text{C}</math>, <math>\theta_{JA} = 130\text{C/W}</math></p> <p>J PACKAGE<br/>16-LEAD CERDIP<br/><math>T_{JMAX} = 150^{\circ}\text{C}</math>, <math>\theta_{JA} = 100\text{C/W}</math></p> | ORDER PART<br>NUMBER                                                               |
|                                                                                                                                                                                                                                                                                                                                                                                                             | <p>LTC201ACN<br/>LTC201ACS<br/>LTC202CN<br/>LTC202CS<br/>LTC203CN<br/>LTC203CS</p> |
|                                                                                                                                                                                                                                                                                                                                                                                                             | ORDER PART<br>NUMBER                                                               |
|                                                                                                                                                                                                                                                                                                                                                                                                             | <p>LTC201AMJ<br/>LTC201ACJ<br/>LTC202MJ<br/>LTC202CJ<br/>LTC203MJ<br/>LTC203CJ</p> |

### OBSOLETE PACKAGE

Consider the N16 or SO-16 Package for Alternate Source

Consult LTC Marketing for parts specified with wider operating temperature ranges.

## DIGITAL AND DC ELECTRICAL CHARACTERISTICS

The ● denotes the specifications which apply over full operating temperature range, otherwise specifications are at  $T_A = 25^{\circ}\text{C}$ .  $V^+ = 15\text{V}$ ,  $V^- = -15\text{V}$ , GND = 0V.

| PARAMETER                      | CONDITIONS                                                    |                      |   | LTC201AM/LTC202M/<br>LTC203M |      |                      | LTC201AC/LTC202C/<br>LTC203C |      |                      | UNITS                 |
|--------------------------------|---------------------------------------------------------------|----------------------|---|------------------------------|------|----------------------|------------------------------|------|----------------------|-----------------------|
|                                |                                                               |                      |   | MIN                          | TYP  | MAX                  | MIN                          | TYP  | MAX                  |                       |
| Analog Signal Range            |                                                               |                      | ● |                              |      | $\pm 15$             |                              |      | $\pm 15$             | V                     |
| $R_{ON}$                       | $V_S = \pm 10\text{V}$<br>$I_D = 1\text{mA}$                  | $T_{MIN}$            |   |                              |      | 110                  |                              |      | 125                  | $\Omega$              |
|                                |                                                               | $25^{\circ}\text{C}$ |   |                              | 65   | 110                  |                              | 65   | 125                  | $\Omega$              |
|                                |                                                               | $T_{MAX}$            |   |                              |      | 160                  |                              |      | 160                  | $\Omega$              |
| $\Delta R_{ON}$ vs $V_S$       |                                                               |                      |   |                              | 20   |                      |                              | 20   |                      | %                     |
| $\Delta R_{ON}$ vs Temperature |                                                               |                      |   |                              | 0.5  |                      |                              | 0.5  |                      | %/ $^{\circ}\text{C}$ |
| $R_{ON}$ Match                 | $V_S = 0\text{V}$ , $I_{DS} = 1\text{mA}$                     |                      |   |                              | 5    |                      |                              | 5    |                      | %                     |
| Off Input Leakage $I_S$ (OFF)  | $V_D = \pm 14\text{V}$ , $V_S = \pm 14\text{V}$<br>Switch Off |                      | ● |                              | 0.01 | $\pm 1$<br>$\pm 100$ |                              | 0.01 | $\pm 5$<br>$\pm 100$ | nA<br>nA              |

## DIGITAL AND DC ELECTRICAL CHARACTERISTICS

The ● denotes the specifications which apply over full operating temperature range, otherwise specifications are at  $T_A = 25^\circ\text{C}$ .  $V^+ = 15\text{V}$ ,  $V^- = -15\text{V}$ ,  $\text{GND} = 0\text{V}$ .

| PARAMETER                                            | CONDITIONS                                                              |   | LTC201AM/LTC202M/<br>LTC203M |      |                      | LTC201AC/LTC202C/<br>LTC203C |      |                      | UNITS         |
|------------------------------------------------------|-------------------------------------------------------------------------|---|------------------------------|------|----------------------|------------------------------|------|----------------------|---------------|
|                                                      |                                                                         |   | MIN                          | TYP  | MAX                  | MIN                          | TYP  | MAX                  |               |
| Off Output Leakage $I_D$ (OFF)                       | $V_D = \pm 14\text{V}$ , $V_S = \pm 14\text{V}$<br>Switch Off           | ● |                              | 0.01 | $\pm 1$<br>$\pm 100$ |                              | 0.01 | $\pm 5$<br>$\pm 100$ | nA<br>nA      |
| On Channel Leakage $I_D$ (ON)                        | $V_D = V_S = \pm 14\text{V}$<br>Switch On                               |   |                              | 0.02 | $\pm 1$              |                              | 0.02 | $\pm 5$              | nA            |
|                                                      |                                                                         | ● |                              |      | $\pm 200$            |                              |      | $\pm 200$            | nA            |
| Input High Voltage $V_{INH}$                         |                                                                         | ● | 2.4                          |      |                      | 2.4                          |      |                      | V             |
| Input Low Voltage $V_{INL}$                          |                                                                         | ● |                              |      | 0.8                  |                              |      | 0.8                  | V             |
| Input High or Low Current<br>$I_{INH}$ and $I_{INL}$ | $V_{IN} = 15\text{V}$ , $0\text{V}$                                     | ● |                              |      | $\pm 1$              |                              |      | $\pm 1$              | $\mu\text{A}$ |
| $C_S$ (OFF)                                          |                                                                         |   |                              | 5    |                      |                              | 5    |                      | pF            |
| $C_D$ (OFF)                                          |                                                                         |   |                              | 12   |                      |                              | 12   |                      | pF            |
| $C_D$ , $C_S$ (ON)                                   |                                                                         |   |                              | 30   |                      |                              | 30   |                      | pF            |
| $I^+$                                                | All Logic Inputs Tied Together<br>$V_{IN} = 0\text{V}$ or $4.0\text{V}$ |   | 16                           |      | 40                   | 16                           |      | 40                   | $\mu\text{A}$ |
|                                                      |                                                                         | ● |                              |      | 60                   |                              |      | 60                   | $\mu\text{A}$ |
| $I^-$                                                |                                                                         |   |                              | 0.1  | 5                    |                              | 0.1  | 5                    | $\mu\text{A}$ |
|                                                      |                                                                         | ● |                              |      | 10                   |                              |      | 10                   | $\mu\text{A}$ |

## AC ELECTRICAL CHARACTERISTICS

$V^+ = 15\text{V}$ ,  $V^- = -15\text{V}$ ,  $\text{GND} = 0\text{V}$  unless otherwise noted.

| PARAMETER                     | CONDITIONS                                                        |  | LTC201AM/LTC202M/<br>LTC203M |      |          | LTC201AC/LTC202C/<br>LTC203C |      |          | UNITS |
|-------------------------------|-------------------------------------------------------------------|--|------------------------------|------|----------|------------------------------|------|----------|-------|
|                               |                                                                   |  | MIN                          | TYP  | MAX      | MIN                          | TYP  | MAX      |       |
| $t_{ON}$                      | $V_S = 2\text{V}$ , $R_L = 1\text{k}\Omega$ , $C_L = 35\text{pF}$ |  |                              | 290  | 400      |                              | 290  | 400      | ns    |
| $t_{OFF}$                     |                                                                   |  |                              | 210  | 300      |                              | 210  | 300      | ns    |
| $t_{OPEN}$                    |                                                                   |  | 20                           | 85   |          | 20                           | 85   |          | ns    |
| Off Isolation                 | $V_S = 2V_{P-P}$ , $R_L = 1\text{k}\Omega$ , $f = 100\text{kHz}$  |  |                              | 75   |          |                              | 75   |          | dB    |
| Crosstalk                     |                                                                   |  |                              | 90   |          |                              | 90   |          | dB    |
| Charge Injection $O_{INJ}$    | $R_S = 0\Omega$ , $C_L = 1000\text{pF}$ , $V_S = 0\text{V}$       |  |                              | 5    | $\pm 25$ |                              | 8    | $\pm 25$ | pC    |
| Total Harmonic Distortion THD | $V_S = 2V_{P-P}$ , $R_L = 10\text{k}\Omega$                       |  |                              | 0.01 |          |                              | 0.01 |          | %     |

# LTC201A/LTC202/LTC203

## DIGITAL AND DC ELECTRICAL CHARACTERISTICS

The ● denotes the specifications which apply over full operating temperature range, otherwise specifications are at  $T_A = 25^\circ\text{C}$ .  $V^+ = 5\text{V}$ ,  $V^- = \text{GND} = 0\text{V}$  unless otherwise noted.

| PARAMETER                                            | CONDITIONS                                                                      |                    | LTC201AM/LTC202M/<br>LTC203M |      |           | LTC201AC/LTC202C/<br>LTC203C |      |           | UNITS               |
|------------------------------------------------------|---------------------------------------------------------------------------------|--------------------|------------------------------|------|-----------|------------------------------|------|-----------|---------------------|
|                                                      |                                                                                 |                    | MIN                          | TYP  | MAX       | MIN                          | TYP  | MAX       |                     |
| Analog Signal Range                                  |                                                                                 | ●                  | 0                            |      | 5         | 0                            |      | 5         | V                   |
| $R_{ON}$                                             | $V_S = \pm 1.5\text{V}, +3\text{V}$<br>$I_D = 0.25\text{mA}$                    | $T_{MIN}$          |                              |      | 450       |                              |      | 520       | $\Omega$            |
|                                                      |                                                                                 | $25^\circ\text{C}$ |                              | 280  | 450       |                              | 280  | 525       | $\Omega$            |
|                                                      |                                                                                 | $T_{MAX}$          |                              |      | 650       |                              |      | 650       | $\Omega$            |
| $\Delta R_{ON}$ vs $V_S$                             |                                                                                 |                    |                              | 20   |           |                              | 20   |           | %                   |
| $\Delta R_{ON}$ vs Temperature                       |                                                                                 |                    |                              | 0.5  |           |                              | 0.5  |           | %/ $^\circ\text{C}$ |
| $\Delta R_{ON}$ Match                                | $V_S = 2.5\text{V}, I_{DS} = 0.25\text{mA}$                                     |                    |                              | 5    |           |                              | 5    |           | %                   |
| Off Input Leakage $I_S$ (OFF)                        | $V_D = 4\text{V}, 1\text{V}; V_S = 1\text{V}, 4\text{V}$ (Note 4)<br>Switch Off |                    |                              | 0.01 | $\pm 1$   |                              | 0.01 | $\pm 5$   | nA                  |
|                                                      |                                                                                 | ●                  |                              |      | $\pm 100$ |                              |      | $\pm 100$ | nA                  |
| Off Output Leakage $I_D$ (OFF)                       | $V_D = 4\text{V}, 1\text{V}; V_S = 1\text{V}, 4\text{V}$ (Note 4)<br>Switch Off |                    |                              | 0.01 | $\pm 1$   |                              | 0.01 | $\pm 5$   | nA                  |
|                                                      |                                                                                 | ●                  |                              |      | $\pm 100$ |                              |      | $\pm 100$ | nA                  |
| On Channel Leakage $I_D$ (ON)                        | $V_D = V_S = 1\text{V}, 4\text{V}$ (Note 4)<br>Switch On                        |                    |                              | 0.01 | $\pm 1$   |                              | 0.01 | $\pm 5$   | nA                  |
|                                                      |                                                                                 | ●                  |                              |      | $\pm 200$ |                              |      | $\pm 200$ | nA                  |
| Input High Voltage $V_{INH}$                         |                                                                                 | ●                  | 2.4                          |      |           | 2.4                          |      |           | V                   |
| Input Low Voltage $V_{INL}$                          |                                                                                 | ●                  |                              |      | 0.8       |                              |      | 0.8       | V                   |
| Input High or Low Current<br>$I_{INH}$ and $I_{INL}$ | $V_{IN} = 5\text{V}, 0\text{V}$                                                 | ●                  |                              |      | $\pm 1$   |                              |      | $\pm 1$   | $\mu\text{A}$       |
| $C_S$ (OFF)                                          |                                                                                 |                    |                              | 5    |           |                              | 5    |           | pF                  |
| $C_D$ (OFF)                                          |                                                                                 |                    |                              | 12   |           |                              | 12   |           | pF                  |
| $C_D, C_S$ (ON)                                      |                                                                                 |                    |                              | 30   |           |                              | 30   |           | pF                  |
| $I^+$                                                | All Logic Inputs Tied Together<br>$V_{IN} = 0\text{V}$ OR $4.0\text{V}$         |                    |                              | 8    | 20        |                              | 8    | 20        | $\mu\text{A}$       |
|                                                      |                                                                                 | ●                  |                              |      | 30        |                              |      | 30        | $\mu\text{A}$       |

## AC ELECTRICAL CHARACTERISTICS

$V^+ = 5\text{V}$ ,  $V^- = \text{GND} = 0\text{V}$  unless otherwise noted.

| PARAMETER                     | CONDITIONS                                                  | LTC201AM/LTC202M/<br>LTC203M |      |     | LTC201AC/LTC202C/<br>LTC203C |      |     | UNITS |
|-------------------------------|-------------------------------------------------------------|------------------------------|------|-----|------------------------------|------|-----|-------|
|                               |                                                             | MIN                          | TYP  | MAX | MIN                          | TYP  | MAX |       |
| $t_{ON}$                      | $V_S = 2\text{V}, R_L = 1\text{k}\Omega, C_L = 35\text{pF}$ |                              | 450  | 600 |                              | 450  | 600 | ns    |
| $t_{OFF}$                     |                                                             |                              | 190  | 300 |                              | 190  | 300 | ns    |
| $t_{OPEN}$                    |                                                             | 100                          | 250  |     | 100                          | 250  |     | ns    |
| Off Isolation                 | $V_S = 2V_{P-P}, R_L = 1\text{k}\Omega, f = 100\text{Hz}$   |                              | 75   |     |                              | 75   |     | dB    |
| Crosstalk                     |                                                             |                              | 90   |     |                              | 90   |     | dB    |
| Charge Injection $Q_{INJ}$    | $R_S = 0\Omega, C_L = 1000\text{pF}, V_S = 2.5\text{V}$     |                              | 2    |     |                              | 2    |     | pC    |
| Total Harmonic Distortion THD | $V_S = 2V_{P-P}, R_L = 10\text{k}\Omega$                    |                              | 0.01 |     |                              | 0.01 |     | %     |


**Note 1:** Absolute Maximum Ratings are those values beyond which the life of a device may be impaired.

**Note 2:** Signals on S, D, or IN exceeding  $V^+$  or  $V^-$  will be clamped by internal diodes. Limit forward diode current to maximum current rating.


**Note 3:** In-circuit ESD on the switch pins (S or D) exceeds 4kV (see test circuit).

**Note 4:** Leakage current with a single 5V supply is guaranteed by correlation with the  $\pm 15\text{V}$  leakage current.


## TYPICAL PERFORMANCE CHARACTERISTICS

 **$R_{ON}$  vs  $V_S$  Over Supply Voltage**


LT201\_202\_203 • TPC01

 **$R_{ON}$  vs  $V_S$  Over Temperature**


LT201\_202\_203 • TPC02

 **$R_{ON}$  vs  $V_S$  Over Temperature**


LT201\_202\_203 • TPC03

 **$Q_{INJ}$  vs  $V_S$  Over Supply Voltage**

LT201\_202\_203 • TPC04

**Positive Supply Current vs Logic Input Voltage**

LT201\_202\_203 • TPC05

**Supply Current vs Logic Input Voltage**

LT201\_202\_203 • TPC06



## APPLICATIONS INFORMATION

### Switching Time Test Circuit

Switch output waveform shown for  $V_S = \text{constant}$  with logic input waveform as shown. Note that  $V_S$  may be + or – as per switching time test circuit.  $V_O$  is the steady state


output switch on. Feedthrough via gate capacitance may result in spikes at leading and trailing edge of output waveform.

### Switching Time Test Circuit




LT201\_202\_203 • A102

### Charge Injection Test Circuit




LT201\_202\_203 • A103




$\Delta V_O$  IS THE MEASURED VOLTAGE ERROR DUE TO CHARGE INJECTION.  
THE ERROR VOLTAGE IN COULOMBS IS  $\Delta Q = C_L \cdot \Delta V_O$

LT201\_202\_203 • A104



# APPLICATIONS INFORMATION

**OIRR-Off Isolation Test Circuit**


| $V_{IN}$ |    |
|----------|----|
| 3V       | NC |
| 0V       | NO |


**CCRR-Channel to Channel Crosstalk Test Circuit**


| $V_{IN}$ |    |
|----------|----|
| 3V       | NC |
| 0V       | NO |


**In-Circuit ESD Test Circuit**

**Micropower, 4.5V to 15V Input,  
Voltage Doubler Using the LTC203**


| $V_{IN}$ | $I_Q$ | $V_{OUT}$ , NO LOAD | $R_{OUT}$ |
|----------|-------|---------------------|-----------|
| 4.5V     | 20μA  | 8.988V(12mV Error)  | 1.2k      |
| 15V      | 130μA | 29.96V(40mV Error)  | 600Ω      |

## Micropower, $\pm 4.5\text{V}$ to $\pm 15\text{V}$ , Voltage Inverter Using the LTC203



## Quad 12-Bit Sample-and-Hold






[illegible]

The graph displays a noisy signal. The vertical axis represents voltage (V) with a scale of 50nV. The horizontal axis represents time (t) with a scale of 10 seconds. The signal fluctuates rapidly around a central horizontal line.

9

## APPLICATIONS INFORMATION

### Bipolar (AC) Input V/F Converter



LT201\_202\_203 • AI13

6V

TYPE K THERMOCOUPLE

“A”

100k

6V

0.02μF

6V

10k

1M

Q2 2N3906

C1 100pF

74C14

6V

100k

C4 300pF

Q1 2N3904

NC

OUTPUT 0°C to 100°C D.C. to 1kHz

LT1025

+V

GND

R-

6.81kΩ\*\*

C3 0.47μF

100°C 1.5kΩ TRIM

240k

6V

6.8μF

LT1004-1.2V

LTC203

S1

S2

IN1

IN2

IN3

IN4

S3

S4

D1

D2

NC

V+

V-

GND

D3

D4

6V

C2 390pF\*

NOTES:

\* POLYSTYRENE

\*\* IRC/TRW MTR/5/+ 120ppm

360μA OPERATING CURRENT

4.75V TO 10V SUPPLY VOLTAGE


FOR 4mV FULL SCALE “GENERAL PURPOSE”

V → F DELETE LT1025 AND THERMOCOUPLE AND DRIVE POINT “A”


LT201\_202\_203 • A114

## APPLICATIONS INFORMATION

### Precision Current Sensing in Supply Rails




### Precision Voltage Divide by 2 Circuit



## PACKAGE DESCRIPTION


**J Package**  
**16-Lead CERDIP (Narrow .300 Inch, Hermetic)**  
 (Reference LTC DWG # 05-08-1110)



**OBSOLETE PACKAGE**

## PACKAGE DESCRIPTION

### N Package 16-Lead PDIP (Narrow .300 Inch) (Reference LTC DWG # 05-08-1510)



NOTE:  
1. DIMENSIONS ARE  $\frac{\text{INCHES}}{\text{MILLIMETERS}}$

\*THESE DIMENSIONS DO NOT INCLUDE MOLD FLASH OR PROTRUSIONS.  
MOLD FLASH OR PROTRUSIONS SHALL NOT EXCEED .010 INCH (0.254mm)

N16 1002



# LTC201A/LTC202/LTC203

## RELATED PARTS

| PART NUMBER     | DESCRIPTION                                                              | COMMENTS                                                                    |
|-----------------|--------------------------------------------------------------------------|-----------------------------------------------------------------------------|
| LTC221/LTC222   | Micropower, Low Charge Injection, Quad CMOS Analog Switches              | Parallel Controlled with Data Latches                                       |
| LTC1380/LTC1393 | 8-Channel/4-Channel Differential Analog Multiplexer with SMBus Interface | 3V to $\pm 15V$ , $R_{ON} = 35\Omega$ Single-Ended/ $70\Omega$ Differential |
| LTC1390/LTC1391 | 8-Channel, Analog Multiplexer with Serial Interface                      | 3V to $\pm 15V$ , $R_{ON} = 45\Omega$ , Low Charge Injection                |
| LT1675/LT1675-1 | 250MHz, Triple and Single RGB Multiplexer                                | 100MHz Pixel Switching, 1100V/ $\mu s$ Slew Rate                            |